

KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 1 / 10

Replaced revision:1 (Dated 12/07/2017)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: CK321430000

Product name KRAFT WOOD STYLE AQUA MAT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Water based polyurethane decorative wood varnish

1.3. Details of the supplier of the safety data sheet

Name DRUCKFARBEN HELLAS SA Full address MEGARIDOS AVENUE

District and Country 19300 ASPROPYRGOS (ATTIKI)

GREECE

Tel. +30 210 5519500 Fax +30 210 5519501

e-mail address of the competent person

responsible for the Safety Data Sheet psafety@druckfarben.gr

1.4. Emergency telephone number

For urgent inquiries refer to 0030-210-7793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

EUH208 Contains: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-Benzisothiazol-3(2H)-one (ECHA) 1,2-Benzisothiazol-3(2H)-one (BW20)

May produce an allergic reaction.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P312 Call a POISON CENTRE / doctor, if you feel unwell.

P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local /

national / international regulations.



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 2 / 10

Replaced revision:1 (Dated 12/07/2017)

SECTION 2. Hazards identification .../>>

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

FC

CAS

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

1,2-Benzisothiazol-3(2H)-one (BW20)

220-120-9

INDEX 613-088-00-6 0 ≤ x < 0.05 Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

Skin Sens. 1 H317: ≥ 0,05%

2634-33-5 LD50 Oral: 1150 mg/kg, STA Inhalation mists/powders: 0,051 mg/l

REACH Reg. 01-2120761540-60 1,2-Benzisothiazol-3(2H)-one (ECHA)

INDEX 613-088-00-6 0 ≤ x < 0.05 Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317,

Aquatic Acute 1 H400 M=1

EC 220-120-9 Skin Sens. 1 H317: ≥ 0,05%

CAS 2634-33-5 LD50 Oral: 1150 mg/kg

REACH Reg. 01-2120761540-60

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

INDEX 613-167-00-5 0 ≤ x < 0,0015 Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C

H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100, EUH071

EC 611-341-5 Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥

0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%

CAS 55965-84-9 STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours:

0,501 mg/l

REACH Reg. 01-2120764691-48

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 3 / 10

Replaced revision:1 (Dated 12/07/2017)

SECTION 5. Firefighting measures .../>>

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU Deutschland Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und

Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung

gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 4 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 8. Exposure controls/personal protection .../>>

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1) Threshold Limit Value

THI CONTOIN ENTIRE VALUE											
Type	Country	TWA/8h		STEL/15	min	Remarks / Observations					
		mg/m3	ppm	mg/m3	ppm						
AGW	DEU	0,05				SKIN					

Mono Propylene Glycol (MPG)										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
WEL	GBR	10				Particulates				

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pН	8,5-9,5	Concentration: 100 %
		Temperature: 25 °C
Kinematic viscosity	260 mm2/s	Method:Converting Formula from Dynamic
		Viscosity & Density
		Temperature: 25 °C
Dynamic viscosity	85-145 sec	Method:Flow Cup No 4
		Remark:ISO 2431
		* FRV. 4.5.0.000.40



KRAFT WOOD STYLE AQUA MAT

g/cm3

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 5 / 10

Temperature: 25 °C

Method:ISO 2811 Temperature: 25 °C

Replaced revision:1 (Dated 12/07/2017)

SECTION 9. Physical and chemical properties/>>

Solubility not available Partition coefficient: n-octanol/water not available

Vapour pressure not available Density and/or relative density 1,04±0,02

Relative vapour density not available

Particle characteristics not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Method:ISO 3251 Total solids (250°C / 482°F) 34,00 % Temperature: 25 °C

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 6 / 10

Replaced revision:1 (Dated 12/07/2017)

SECTION 11. Toxicological information .../>>

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

1,2-Benzisothiazol-3(2H)-one (ECHA)

LD50 (Dermal): > 2000 mg/kg Rat LD50 (Oral): 1150 mg/kg Mouse

1,2-Benzisothiazol-3(2H)-one (BW20)

LD50 (Dermal): > 2000 mg/kg Rat LD50 (Oral): 1150 mg/kg Mouse

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

LD50 (Dermal): 1000 mg/kg Rat

STA (Dermal): 50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 550 mg/kg Rat LC50 (Inhalation vapours): 0,31 mg/l Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-Benzisothiazol-3(2H)-one (ECHA)

1,2-Benzisothiazol-3(2H)-one (BW20)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 260 mm2/s

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page no. 7 / 10

Replaced revision:1 (Dated 12/07/2017)

disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-Benzisothiazol-3(2H)-one (ECHA)

LC50 - for Fish 0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα) EC50 - for Algae / Aquatic Plants 4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)

1,2-Benzisothiazol-3(2H)-one (BW20)

LC50 - for Fish 0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα) EC50 - for Algae / Aquatic Plants 4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

 LC50 - for Fish
 0,58 mg/l/96h

 EC50 - for Algae / Aquatic Plants
 0,161 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 0,032 mg/l 96h

12.2. Persistence and degradability

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) NOT rapidly degradable

30 %, Exposure time: 28 d, OECD Test Guideline 301B

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 8 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 14. Transport information .../>>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 9 / 10

Replaced revision:1 (Dated 12/07/2017)

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2
Acute toxicity, category 2
Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Skin Corr. 1C
Skin corrosion, category 1C
Eye Dam. 1
Skin Irrit. 2
Skin sensitization, category 2
Skin Sens. 1

Acute toxicity, category 4
Skin corrosion, category 1
Skin irritation, category 2
Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H310 Fatal in contact with skin.H330 Fatal if inhaled.H301 Toxic if swallowed.

H302 Harmful if swallowed.H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.
EUH210 Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TI V: Threshold I imit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 10 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 16. Other information .../>>

- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

 $02 \, / \, 03 \, / \, 04 \, / \, 08 \, / \, 09 \, / \, 11 \, / \, 12 \, / \, 14 \, / \, 15 \, / \, 16.$