

Antigraf

**THINNING**
0%**COVERAGE**
15 – 25 m²/L**APPLICATION**
roller, brush or
airless spray gun**DRYING**
1 – 2 hours**Transparent surface
protection****» Antigrffiti protection of
construction surfaces**

Transparent water-based solution for buildings and construction surfaces protection against graffiti and spray paints. It is user- and environment-friendly, resistant to UV radiation, fully permeable and does not impact the shade or the natural appearance of the surfaces. It can be applied on vertical and horizontal surfaces of concrete, stucco, plaster, marble, natural stones, etc. Being sacrificial means that after removal of the graffiti with hot water and scrubbing or with pressure washing, a new coat of KRAFT ANTIGRAF needs to be applied.

» Sacrificial**» No impact on the
surface appearance****TECHNICAL DATA**

Density ISO 2811 @ 25°C	0.99 g/mL (±0.02)
Viscosity Flow Cup No4 ISO 2431 @ 25°C	12 sec (±2)
Coverage per coat	15 – 25 m ² /L*
pH	8.0-9.0

* Depending on the application method and the surface absorption.

A/c (WB) Exterior walls of mineral substrate.

- VOC Limit Value: 40g/L
- Maximum VOC concentration of the ready to use product: 39 g/L

Antigraf

Transparent surface
protection

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean, and free of dust, grease, salts, residues, etc. Fresh concrete, stucco and plaster surfaces must be allowed to dry for at least 28 days prior to application. Apply one coat and remove excess material using a cloth after 15 min. For stronger protection, it is recommended to apply a second coat 3 hours after the first one.

» **On very porous substrates:** Apply 2 coats of KRAFT ANTIGRAF under favorable drying conditions.

APPLICATION INSTRUCTIONS

- » For graffiti removal: Use hot water (>60°C) and soak the surface to keep it damp for approximately 2-4 minutes. Remove KRAFT ANTIGRAF from the surface with a high-pressure hot water unit. Adjust water pressure according to the surface. Once the graffiti is removed, wash the surface thoroughly with hot water and re-protect the cleaned area with KRAFT ANTIGRAF.
- » You can apply with a brush, a roller or an airless spray gun.
- » No thinning is required.
- » Dry to touch: 1-2 hours at 25°C and 50% relative humidity (drying time is longer in humid/cold conditions).
- » Recoating time: Minimum 3 hours after application of the first coat in favorable drying conditions.
- » Maximum protection and complete hardening are achieved no earlier than 24 hours after application in favorable drying conditions.
- » Stir well before and regularly during application.
- » Do not apply at temperatures below 10°C or above 35°C and at a relative humidity 65% or higher.
- » Do not apply in case of expected rain.

AFTER USE INSTRUCTIONS

» Cleaning: Clean the tools and product residues immediately with warm water and soap or detergent.

PACKAGING

Available in transparent, in 18L plastic containers.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

CERTIFIED SYSTEMS

ISO 9001 ISO 140001 ISO 50001 ISO 45001

09/2026 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarbengroup.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr