

Antigraffiti Primer



THINNING
0%



COVERAGE
16-20m²/L



APPLICATION
Brush or roller



DRYING
15-30 min

Antigraffiti varnish
adhesion primer

» Strong adhesion

Innovative technology transparent adhesion primer for the permanent surface protection varnish KRAFT ANTIGRAFFITI SHIELD. It is distinguished for its strong adhesion to porous and non-porous surfaces. It dries extremely fast, does not alter the appearance of the substrate and is repainted with the final varnish within a few minutes.

Binding Primers A/h (SB).

- VOC Limit Value: 750g/L.
- Maximum content of VOC of the product in its ready to use condition: 749 g/L

» Extremely fast drying

» Does not alter the substrate appearance

TECHNICAL DATA

Density ISO 2811 @ 25°C	0,78 g/mL(±0,02)
Viscosity Flow Cup No4 @ 25°C ISO 2431	12sec (±2)
Coverage	16-20 m ² /L*

* Depending on the application conditions and surface absorption

Antigraffiti Primer

Antigraffiti varnish
adhesion primer

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint or varnish etc.

APPLICATION INSTRUCTIONS

- » Apply it outdoor or in a well-ventilated area.
- » Stir well before use. The product is ready to use.
- » Suitable application tool: Brush or roller.

Applicable on the following substrates:

- » **On already painted surfaces** with emulsion paints, decorative plasters, silicate paints, silicon emulsion paints (SREP) or epoxies.
- » **On surfaces** of PVC, slate, glass, marble, steel, aluminum, wood, polycarbonate, powder coatings, PU, PMMA.
- » **On surfaces** of concrete, mortar, brick, FCB, cotto, lime sandstone and granite
- » **For the protection of existing graffiti (eg Street Art).**
- » Before priming, cover with paint the graffiti, or remove it with suitable cleaner.
- » Apply one coat of **KRAFT ANTIGRAFFITI PRIMER** with consumption rate 50 - 60 mL/m².
- » Drying time 15 – 30 mins at 25°C and RH 50% (drying times are longer in wet / cold conditions).
- » Avoid application at temperatures below 5°C or greater than 35°C and relative humidity greater than 60%.

AFTER USE INSTRUCTIONS

- » Close the bucket well to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight, frost conditions and humidity.
- » Clean the tools immediately with **NITRO-1100**.
- » Apply **KRAFT ANTIGRAFFITI SHIELD** after 15-30 minutes and the material is completely dry.

PACKAGING

Available in transparent finish in 1L canister.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read label before use. For further information please consult the Material Safety Data sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product before and after opening at temperatures between 5°C to 35°C & humidity no more than 60%.

KEEP OUT OF REACH OF CHILDREN.

04/2021 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr