
	DECLARATION OF PERFORMANCE	
		Page 1 of 1
No 05.27		

1. Unique identification code of the product-type:

FixoTile Gel Max, C2TES1

Intended use:

Improved deformable cementitious adhesive with reduced slip and extended open time for internal and external tiling

2. Manufacturer:

Druckfarben Hellas S.A. Megaridos Ave., Kallistiri area, GR-19300 Aspropyrgos, Greece

3. Systems of AVCP (Assessment and Verification of Constancy of Performance):

System 3 & System 3 for Reaction to Fire

4. Harmonised Standard: **EN 12004:2007 + A1:2012**

Notified Bodies:

EUROTEST - CONTROL, NB 2085

Technicky a Skusobny Ustav Stavebny, n. o. (TSUS), NB 1301

National Technical University of Athens, Laboratory of Heterogenous Mixtures & Combustion Systems-Fire Eng. Unit (HMCS), NB 2878

5. Declared Performances:

Essential Characteristics	Performance
Reaction to fire	Pending
Bond Strength as:	
-Initial tensile adhesion strength	≥ 1.0 N/mm ²
Durability, for:	
-Tensile adhesion strength after water immersion	≥ 1.0 N/mm ²
-Tensile adhesion strength after heat ageing	≥ 1.0 N/mm ²
-Tensile adhesion strength after freeze-thaw cycles	≥ 1.0 N/mm ²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (legal representative):



Sokratis Vavatsikos

Chemist N.K.U.A. |

Regulatory & Specifications Compliance Manager

Aspropyrgos-GREECE, on 25/07/2024