



DRUCKFARBEN HELLAS SA

Revision nr. 6
Dated 09/02/2021
Printed on 09/02/2021
Page n. 1/18
Replaced revision:5
(Dated: 09/02/2021)

KRAFT SPORT COAT

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: CK271840000
Product name: KRAFT SPORT COAT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: 100% Acrylic paint for stadiums

1.3. Details of the supplier of the safety data sheet

Name: DRUCKFARBEN HELLAS SA
Full address: Megaridos Ave
District and Country: 193 00 Aspropyrgos (Attiki)
Greece
Tel. +30 210 5519500
Fax +30 210 5519501

e-mail address of the competent person responsible for the Safety Data Sheet: psafety@druckfarben.gr

1.4. Emergency telephone number

For urgent inquiries refer to: +30 210 7793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

KRAFT SPORT COAT

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: 2-Methylisothiazol-3(2H)-one, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-Benzisothiazol-3(2H)-one, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate
May produce an allergic reaction.

Precautionary statements:

P501 Dispose of contents and container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P102 Keep out of reach of children.
P312 Call a POISON CENTRE / doctor if you feel unwell.
P101 If medical advice is needed, have product container or label at hand.
P273 Avoid release to the environment.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
2-(2-BUTOXYETHOXY)ETHANOL		
CAS 112-34-5	0 < x < 0,5	Eye Irrit. 2 H319
EC 203-961-6		
INDEX 603-096-00-8		
Reg. no. 01-2119475104-44		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
CAS 1065336-91-5	0 < x < 0,1	Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 915-687-0		
INDEX -		
3-iodo-2-propynyl butylcarbamate		
CAS 55406-53-6	0 < x < 0,5	Acute Tox. 4 H302+H332, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=10
EC 259-627-5		
INDEX -		
toluene		
CAS 108-88-3	0 < x < 0,5	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

KRAFT SPORT COAT

EC 203-625-9

INDEX 601-021-00-3

Reg. no. 01-2119471310-51

1,2-Benzisothiazol-3(2H)-one

CAS 2634-33-5

0 < x < 0,05

Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317,
Aquatic Acute 1 H400 M=1

EC 220-120-9

INDEX 613-088-00-6

Pyrithione zinc

CAS 13463-41-7

0 < x < 0,025

Acute Tox. 3 H301, Acute Tox. 3 H331, Eye Dam. 1 H318, Aquatic Acute 1
H400 M=100, Aquatic Chronic 1 H410 M=10

EC 236-671-3

INDEX -

Reg. no. 01-2119511196-46-XXXX

TRIETHYLAMINE

CAS 121-44-8

0 < x < 0,5

Flam. Liq. 2 H225, Acute Tox. 3 H311, Acute Tox. 3 H331, Acute Tox. 4
H302, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335

EC 204-469-4

INDEX 612-004-00-5

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

CAS 55965-84-9

0 < x < 0,0015

Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C
H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100,
Aquatic Chronic 1 H410 M=100, EUH071

EC 611-341-5:

INDEX 613-167-00-5

2-Methylisothiazol-3(2H)-one

CAS 2682-20-4

0 < x < 0,0015

Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B
H314, Eye Dam. 1 H318, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic
Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, EUH071

EC 220-239-6

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	BGR	67,5	10	101,2	15	
TLV	GRC	67,5	10	101,2	15	
VLEP	ITA	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			



KRAFT SPORT COAT

toluene**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	150		300		
TLV	GRC	375	100	560	150	
VLEP	ITA	192	50			SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,68 mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin							VND	384 mg/kg

TRIETHYLAMINE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	8,4		12,6		SKIN
TLV	GRC	40	10	60	15	
VLEP	ITA	8,4	2	12,6	3	SKIN
WEL	GBR	8	2	17	4	SKIN
OEL	EU	8,4	2	12,6	3	SKIN
TLV-ACGIH		4,1	1	12,4	3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**KRAFT SPORT COAT****SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	as showed in color folder
Odour	characteristic
Odour threshold	Not available
pH	8,7 - 9,2
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,14-1,20 g/cm ³
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	130 - 140 KU

KRAFT SPORT COAT

Explosive properties Not available
Oxidising properties Not available

9.2. Other information

Total solids (250°C / 482°F) 1,27 %
VOC (Directive 2010/75/EC) : 1,10 %
VOC (volatile carbon) : 1,07 %

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

toluene

TOLUENE: breaks down in sunlight.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

toluene

TOLUENE: risk of explosion on contact with fuming sulphuric acid, nitric acid, silver perchlorates, nitrogen dioxide, non-metal halogenides, acetic acid, organic nitrocompounds. Can form explosive mixtures with the air. May react dangerously with: strong oxidising agents, strong acids, sulphur (in the presence of heat).

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL



KRAFT SPORT COAT

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

toluene

TOLUENE: it has a toxic effect on the central and peripheral nervous system (with encephalopathies and polyneuritis). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

3-iodo-2-propynyl butylcarbamate



KRAFT SPORT COAT

LD50 (Oral) 500 mg/kg Rat

LD50 (Dermal) > 2000 mg/kg Rat

toluene

LD50 (Oral) > 5000 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) > 20 mg/l/4h Rat

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Oral) 6560 mg/kg Rat

LD50 (Dermal) 2700 mg/kg Rabbit

TRIETHYLAMINE

LD50 (Oral) 460 mg/kg Rat

LD50 (Dermal) 580 mg/kg Rabbit

LC50 (Inhalation) 14,5 mg/l/4h Rat

1,2-Benzisothiazol-3(2H)-one

LD50 (Oral) 1150 mg/kg Mouse

LD50 (Dermal) > 2000 mg/kg Rat

2-Methylisothiazol-3(2H)-one

LD50 (Oral) 120 mg/kg Rat (females)

LD50 (Dermal) 242 mg/kg Rat

Pyrrithione zinc

LD50 (Oral) 269 mg/kg Rat

LD50 (Dermal) > 2 mg/kg Rabbit

LC50 (Inhalation) 1,03 mg/l/4h 4 hours (Rat)



DRUCKFARBEN HELLAS SA

Revision nr. 6

Dated 09/02/2021

Printed on 09/02/2021

Page n. 11/18

Replaced revision:5
(Dated: 09/02/2021)

KRAFT SPORT COAT

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LD50 (Oral) 550 mg/kg Rat

LD50 (Dermal) 1000 mg/kg Rat

LC50 (Inhalation) 0,31 mg/l Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: 2-Methylisothiazol-3(2H)-one

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
1,2-Benzisothiazol-3(2H)-one

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 130 - 140 KU

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

3-iodo-2-propynyl butylcarbamate

LC50 - for Fish	0,067 mg/l/96h
EC50 - for Crustacea	0,16 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,022 mg/l/72h

toluene

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Crustacea	2 mg/l Daphnia magna

2-(2-BUTOXYETHOXY)ETHANOL

LC50 - for Fish	1300 mg/l/96h
EC50 - for Crustacea	100 mg/l/48h

1,2-Benzisothiazol-3(2H)-one

LC50 - for Fish	0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα)
EC50 - for Algae / Aquatic Plants	4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)

2-Methylisothiazol-3(2H)-one

LC50 - for Fish	3,79 mg/l/96h
EC50 - for Crustacea	4,67 mg/l/48h Daphnia

Pyrrithione zinc

LC50 - for Fish	0,0026 mg/l/96h Pimephales promelas
EC50 - for Crustacea	0,0082 mg/l/48h Daphnia magna
Chronic NOEC for Crustacea	0,00046 mg/l

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50 - for Fish	0,58 mg/l/96h
EC50 - for Algae / Aquatic Plants	0,161 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,032 mg/l 96h

12.2. Persistence and degradability

3-iodo-2-propynyl butylcarbamate

Rapidly degradable

2-(2-BUTOXYETHOXY)ETHANOL

KRAFT SPORT COAT

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

TRIETHYLAMINE

Solubility in water > 10000 mg/l

Rapidly degradable

2-Methylisothiazol-3(2H)-one

NOT rapidly degradable

Pyrrithione zinc

Rapidly degradable

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

NOT rapidly degradable

30 %, Exposure time: 28 d, OECD Test Guideline 301B

12.3. Bioaccumulative potential

3-iodo-2-propynyl butylcarbamate

Partition coefficient: n-octanol/water 2,81

toluene

BCF 8,32

2-(2-BUTOXYETHOXY)ETHANOL

Partition coefficient: n-octanol/water 1

TRIETHYLAMINE

Partition coefficient: n-octanol/water 1,45

BCF < 0,5

2-Methylisothiazol-3(2H)-one

BCF 3,16

Pyrrithione zinc

BCF 50

12.4. Mobility in soil

TRIETHYLAMINE

Partition coefficient: soil/water 2,57

12.5. Results of PBT and vPvB assessment



KRAFT SPORT COAT

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards



DRUCKFARBEN HELLAS SA

Revision nr. 6

Dated 09/02/2021

Printed on 09/02/2021

Page n. 15/18

Replaced revision:5
(Dated: 09/02/2021)

KRAFT SPORT COAT

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 48 toluene Reg. no.: 01-2119471310-51

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H302+H332	Harmful if swallowed or if inhaled.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology



DRUCKFARBEN HELLAS SA

Revision nr. 6

Dated 09/02/2021

Printed on 09/02/2021

Page n. 18/18

Replaced revision:5
(Dated: 09/02/2021)

KRAFT SPORT COAT

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

09.