

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier**Trade name: KRAFT TOTAL PROOF PU-S****UFI: SDD0-40QM-800D-39FE**

1.2 Relevant identified uses of the substance or mixture and uses advised against Professional use
Application of the substance / the mixture: Polyurethane Waterproofing coating

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

DRUCKFARBEN HELLAS S.A.

Megaridos Ave., Kallistiri Area

19300, Aspropyrgos, Greece

T:+30 210 5519300, F:+30 210 5519301

psafety@druckfarben.gr

1.4 Emergency telephone number:

European Emergency Tel.: 112

* **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture**Classification according to Regulation EC No 1272/2008 CLP:**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 1)

Hazard pictograms:

GHS02 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

Reaction mass of ethylbenzene and m-xylene and p-xylene
 m-tolyldiene diisocyanate
 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Hazard statements:

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of water and soap.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

GB

(Contd. on page 3)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 2)

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Mixture: consisting of the following components.**Ingredients according Regulation (EU) 2020/878:**

EC number: 905-562-9	Reaction mass of ethylbenzene and m-xylene and p-xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥15-<20%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4	m-tolyldiene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	0.1-<0.5%
CAS: 64359-81-5 EINECS: 264-843-8 Index number: 613-335-00-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 567 mg/kg Specific concentration limits: Skin Irrit. 2; H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0025-<0.025%
CAS: 1317-65-3 EINECS: 215-279-6	limestone	≥30-<40%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide substance with a Community workplace exposure limit	≥2-<3%

Additional information:

(CAS:13463-67-7) Titanium dioxide

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice.

(Contd. on page 4)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 3)

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
 Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 Seek immediate medical advice.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water.
 Remove contact lenses and continue rinsing for several minutes
 Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.
 Rinse out mouth and then drink plenty of water.
 Drink plenty of water and provide fresh air. Call for a doctor immediately.
 Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Carbon dioxide (CO₂)

Carbon monoxide (CO)

5.3 Advice for firefighters**Protective equipment:**

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from ignition sources.

Ensure adequate ventilation.

Wear protective clothing.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Collect with absorbent material (sand, diatomite).

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections:

See Section 7 for information on safe handling.

(Contd. on page 5)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: **KRAFT TOTAL PROOF PU-S**

(Contd. of page 4)

See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use adequate personal protective equipment as required. For more information regarding protective equipment see section 8.

Avoid inhaling vapors.

Avoid contact with skin, eyes and clothing.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Store away from sources of ignition

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 13463-67-7 titanium dioxide

WEL (Great Britain)	Long-term value: 10* 4** mg/m ³ *total inhalable **respirable
---------------------	---

CAS: 26471-62-5 m-tolyldiene diisocyanate

WEL (Great Britain)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
---------------------	---

DNELs

Reaction mass of ethylbenzene, m-xylene and p-xylene | EC: 905-562-9.

Consumers:

Long-term Systemic effect Oral: 1.6 mg/kg bw/d

Long-term Systemic effect By inhalation: 14.8 mg/m³

Long-term Systemic effect Dermal: 108 mg/kg bw/d

Workers:

Long-term Systemic effect By inhalation: 77 mg/ml

Long-term Systemic effect Dermal: 180 mg/kg bw/d

(Contd. on page 6)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: **KRAFT TOTAL PROOF PU-S**

(Contd. of page 5)

Short-term Local effect By inhalation: 289 mg/ml
 Short-term Systemic effect By inhalation: 289 mg/m

PNECs

Reaction mass of ethylbenzene, m-xylene and p-xylene | EC: 905-562-9.

Fresh water: 0,327 mg / l

Marine water: 0.327 mg / l

Freshwater sediments: 12.46 mg / kg

Marine water sediments: 12,46 mg / kg

Soil: 2.31 mg / kg

Sewage treatment plant: 6.58 mg / l

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while using the product.

Be sure to clean skin thoroughly after work and before breaks.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter A2-P2 (EN529) is recommended.

Hand protection

Protective gloves resistant to chemicals (standard EN 374-1)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Recommendation: contaminated gloves should be disposed of.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 7)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 6)

Eye/face protection

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Chemically resistant, protective work clothing (EN 14605) and boots.

* **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Liquid

Viscous liquid

Colour:

Various colours

Odour:

Characteristic

Odour threshold:

Not determined

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

130-150 °C (Reaction mass of ethylbenzene and m-xylene and p-xylene)

Flammability

Not applicable

Lower and upper explosion limit**Lower:**

0.8 Vol %

Upper:

Not determined

Flash point:

31 °C (Pensky-Martens)

Auto-ignition temperature:

Product is not selfigniting.

Decomposition temperature:

Not determined

pH

Not determined

Viscosity:**Kinematic viscosity at 23 °C**

398 s (ISO 2431/Flow time tISO)

Dynamic:

Not determined

Solubility**water:**

Not miscible

Not determined

Partition coefficient n-octanol/water (log value)

Not determined

Vapour pressure:

Not determined

Density and/or relative density**Density at 20 °C:**1.39-1.41 g/cm³**Relative density**

Not determined

Vapour density

Not determined

9.2 Other information**Appearance:****Form:**

Viscous liquid

(Contd. on page 8)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 7)

Important information on protection of health and environment, and on safety.

Auto-ignition temperature:	480 °C (xylene, Reaction mass of ethylbenzene and m-xylene and p-xylene)
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent separation test:	<1 % (UN Part III, par. 32.5.1)
Solvent content:	
VOC (EC)	249 g/l
Cloud point / clarification point:	
Oxidising properties	Not oxidising
Evaporation rate	Not determined

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity**10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided** Stable at environment temperature.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** Avoid heat, sparkles, naked flame or other sources of ignition.**10.5 Incompatible materials** No further relevant information available.**10.6 Hazardous decomposition products** Carbon monoxide and carbon dioxide**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 8)

LD/LC50 values relevant for classification:

Dermal	ATEmix	9,434 mg/kg
Inhalative	ATEmix	35 mg/l

Reaction mass of ethylbenzene and m-xylene and p-xylene

Oral	LD50	4,300 mg/kg (rat)
Inhalative	LC50 (4h)	5,000 ppm (rat) 5,000 ppm (rabbit)

CAS: 26471-62-5 m-tolylidene diisocyanate

Oral	LD50	4,130 mg/kg (rat)
Dermal	LD50	>9,400 mg/kg (rabbit)

CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Oral	LD50	567 mg/kg (ATE)
Inhalative	LC50/4h (dusts and mists)	0.16 mg/l (ATE)

Skin corrosion/irritation Causes skin irritation.**Serious eye damage/irritation** Causes serious eye irritation.**Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure**

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

Additional toxicological information:**Sensitisation** Sensitization possible through skin contact**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****CAS: 26471-62-5 m-tolylidene diisocyanate**

EC50 (48h)	12.5 mg/l (daphnia magna)
LC50 (96h)	133 mg/l (Oncorhynchus mykiss)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 9)

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.**12.7 Other adverse effects****Remark:** Harmful to fish**Additional ecological information:****General notes:**


The product contains materials that are harmful to the environment.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information**14.1 UN number or ID number****ADR, IMDG, IATA**

UN1866

14.2 UN proper shipping name**ADR**

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

14.3 Transport hazard class(es)**ADR, IMDG, IATA****Class**

3 Flammable liquids.

Label

3

(Contd. on page 11)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 10)

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user
Hazard identification number (Kemler code):
EMS Number:
Stowage Category

Warning: Flammable liquids.

30

F-E,S-E

A

14.7 Maritime transport in bulk according to IMO
instruments

Not applicable.

Transport/Additional information:**ADR**

Limited quantities (LQ)
Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category
Tunnel restriction code
Remarks:

3

D/E

- Viscous liquid par. 2.2.3.1.5., 2.2.3.1.5.2 ADR and par. 2.3.2.5 of the IMDG Code.
- Exception for packages: ≤ 5 liters.

- In accordance to paragraphs 2.2.3.1.5, 2.2.3.1.5.2 of ADR (road transport) and 2.3.2.5 of the IMDG Code (marine transport) for packaging ≤ 5 liters (L), are not subject to the ADR agreement and are not subject to the provisions for the marking, labelling and testing of packages (IMDG).

IMDG

Limited quantities (LQ)
Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Remarks:

- Viscous liquid par. 2.2.3.1.5., 2.2.3.1.5.2 ADR and par. 2.3.2.5 of the IMDG Code.
- Exception for packages: ≤ 5 liters.

- In accordance to paragraphs 2.2.3.1.5, 2.2.3.1.5.2 of ADR (road transport) and 2.3.2.5 of the IMDG Code (marine transport) for packaging ≤ 5 liters (L), are not subject to the ADR agreement and are not subject to the provisions for the marking, labelling and testing of packages (IMDG).

UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

GB

(Contd. on page 12)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)

Revision: 18.03.2022

Trade name: KRAFT TOTAL PROOF PU-S

(Contd. of page 11)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 94/62/EC on packaging and packaging waste.

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as amended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Directive 2012/18/EU**Named dangerous substances - ANNEX I** Substance is not listed.**Seveso category** P5c FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74**National regulations:****Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 13)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 18.03.2022

Version number 6 (replaces version 5)


Revision: 18.03.2022

Trade name: **KRAFT TOTAL PROOF PU-S**

(Contd. of page 12)

EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:

SUST  SUSTCHEM S.A.
CHEM REACH & Chemical Services Department
CONSULTING
 A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece
 T: +30 210 8252510 | F: +30 210 8252575
 W: www.sustchem.gr | E: info@suschem.gr

Version number of previous version: 5**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Skin Corr. 1: Skin corrosion/irritation – Category 1
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* **Data compared to the previous version altered.**

GB