

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382981111.**
Product name: **BODENGUARD S-100 White (Comp.-A)**
Chemical name and synonym: **Professional Use only**

UFI: **S473-E029-100G-4JQV**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|---|
| Flammable liquid, category 3 | H226 | Flammable liquid and vapour. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity - repeated exposure, category 1 | H372 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains:

Cristobalite (STOT RE-1)
 Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene
 2-Methylpropan-1-ol
 Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)
 Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentametyl-4-piperidyl Sebacate
 4-morpholinecarbaldehyde

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|---|-----------------------|---|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | | |
| INDEX | 603-074-00-8 | 30 \leq x < 50 |
| EC | 500-033-5 | Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317 |
| CAS | 25068-38-6 | Skin Irrit. 2 H315: \geq 5%, Eye Irrit. 2 H319: \geq 5% |
| REACH Reg. | Polymer | |
| TITANIUM DIOXIDE | | |
| INDEX | | 9 \leq x < 30 |
| EC | 236-675-5 | |
| CAS | 13463-67-7 | |
| REACH Reg. | 01-2119489379-17-0000 | 01-2119489379-17-0197 01-2119489379-17 |
| Cristobalite (STOT RE-1) | | |
| INDEX | | 10 \leq x < 30 |
| EC | 238-455-4 | STOT RE 1 H372 |
| CAS | 14464-46-1 | |

SECTION 3. Composition/information on ingredients ... / >>

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

INDEX $10 \leq x < 20$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

EC 905-562-9

ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l

CAS

REACH Reg. 01-2119555267-33

Reaction mass of ethylbenzene and xylene

INDEX $5 \leq x < 9$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

EC 905-588-0

ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

2-Methylpropan-1-ol

INDEX 603-108-00-1 $3 \leq x < 5$

Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336

EC 201-148-0

CAS 78-83-1

REACH Reg. 01-2119484609-23-0006 01-2119484609-23-xxxx

Solvent naphtha (petroleum), light aromatic

INDEX 649-356-00-4 $1 \leq x < 2,5$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 265-199-0

CAS 64742-95-6

REACH Reg. 01-2119455851-35

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

INDEX $0,5 \leq x < 1$

Repr. 2 H361f, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 915-687-0

CAS 1065336-91-5

REACH Reg. 01-2119491304-40-0000 01-2119491304-40-0002

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32-xxxx 01-2119484661-33-xxxx

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

4-morpholinecarbaldehyde

INDEX $0 < x < 0,5$

Skin Sens. 1B H317

EC 224-518-3

CAS 4394-85-8

REACH Reg. 01-2119987993-12

Trimethylolpropane (TMP)

INDEX $0 < x < 0,5$

Repr. 2 H361fd

EC 201-074-9

CAS 77-99-6

REACH Reg. 01-2119486799-10-0000

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

LC50 Inhalation vapours: 17,2 mg/l/4h

CAS 100-41-4

SECTION 3. Composition/information on ingredients ... / >>

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 0 < x < 0,5 Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

Quartz (Crystalline Silica)

INDEX 0 < x < 0,5

Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

Toluene

INDEX 0 < x < 0,5

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

EC 203-625-9

CAS 108-88-3

REACH Reg. 01-2119471310-51

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

SECTION 5. Firefighting measures ... / >>

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------|--|
| ALB | Shqipëria | VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË" |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|-----------------|--|
| CZE | Česká Republika | Април 2024г.) NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe |
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

4-morpholinecarbaldehyde

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,5 | mg/l |
| Normal value in marine water | 0,05 | mg/l |
| Normal value for fresh water sediment | 1,85 | mg/kg |
| Normal value for marine water sediment | 0,0764 | mg/kg |
| Normal value for water, intermittent release | 5 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|-----------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | VND | 29 mg/m3 | | | VND | 98 mg/m3 |
| Skin | | | VND | 8 mg/kg/d | | | 0,293 mg/cm2 | VND |

Cristobalite (STOT RE-1)

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 3,6 mg/kg/d | | | | |
| Inhalation | | | VND | 0,08 mg/m3 | | | VND | 0,33 mg/m3 |

SECTION 8. Exposure controls/personal protection ... / >>

Xylene

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|---------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Quartz (Crystalline Silica)

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| VLEP | FRA | 0,1 | | | | RESP |
| VLEP | ITA | 0,1 | | | | RESP |
| NDS/NDSch | POL | 0,1 | | | | RESP |
| TLV | ROU | 0,1 | | | | RESP |
| OEL | EU | 0,1 | | | | RESP |
| ACGIH | | 0,025 | | | | RESP |

Solvent naphtha (petroleum), light aromatic

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | GRC | 100 | | | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 11 mg/kg/d | | | | |
| Inhalation | | | VND | 32 mg/m3 | | | VND | 150 mg/m3 |
| Skin | | | VND | 11 mg/kg/d | | | VND | 25 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

| Toluene | | | | | | |
|-----------------------|---------|-------------------|--------|-------------------|---------|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| TLV | BGR | 192 | 50 | 384 | 100 | SKIN |
| TLV | CZE | 192 | 50,112 | 384 | 100,224 | SKIN |
| AGW | DEU | 190 | 50 | 760 | 200 | SKIN |
| MAK | DEU | 190 | 50 | 380 | 100 | SKIN |
| VLEP | FRA | 76,8 | 20 | 384 | 100 | SKIN |
| TLV | GRC | 192 | 50 | 384 | 100 | |
| VLEP | ITA | 192 | 50 | | | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 192 | 50 | 384 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 192 | 50 | 384 | 100 | SKIN |
| WEL | GBR | 191 | 50 | 384 | 100 | SKIN |
| OEL | EU | 192 | 50 | 384 | 100 | SKIN |
| ACGIH | | | 20 | | | |

| Xylene (mixture of isomers) | | | | | | |
|-----------------------------|---------|-------------------|-----|-------------------|-----|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| TLV | CZE | 200 | | 400 | | |
| MAK | DEU | | 100 | | 200 | |
| VLEP | FRA | 221 | 50 | 442 | 100 | |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| NDS/NDSch | POL | 100 | | 350 | | |
| ESD | TUR | 221 | 50 | 442 | 100 | |
| WEL | GBR | | 50 | | 100 | |
| OEL | EU | 221 | 50 | 442 | 100 | |
| ACGIH | | | 100 | | 150 | |

| Predicted no-effect concentration - PNEC | | |
|--|-------|-------|
| Normal value in fresh water | 0,327 | mg/l |
| Normal value in marine water | 0,327 | mg/l |
| Normal value for fresh water sediment | 12,46 | mg/kg |
| Normal value for marine water sediment | 12,46 | mg/kg |

| Health - Derived no-effect level - DNEL / DMEL | | | | | | | | |
|--|-----------------------|-----------------------|---------------|------------------------|-----------------------|-----------------------|---------------|----------------------|
| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,6 mg/kg/d | | | | |
| Inhalation | 174 mg/m ³ | 174 mg/m ³ | VND | 14,8 mg/m ³ | 289 mg/m ³ | 289 mg/m ³ | VND | 77 mg/m ³ |
| Skin | | | VND | 108 mg/kg/d | | | VND | 180 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,635 | mg/l |
| Normal value in marine water | 0,0635 | ml/l |
| Normal value for fresh water sediment | 3,29 | mg/kg |
| Normal value for marine water sediment | 0,329 | mg/kg |
| Normal value for water, intermittent release | 6,35 | mg/l |
| Normal value of STP microorganisms | 100 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,67 mg/kg | | | | |
| Inhalation | | | VND | 33 mg/m3 | 553,5 mg/m3 | VND | VND | 275 mg/m3 |
| Skin | | | VND | 54,8 mg/kg | | | VND | 153,5 mg/kg |

TITANIUM DIOXIDE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 10 | | | | RESP |
| MAK | DEU | 0,3 | | 2,4 | | RESP Hinweis |
| VLEP | FRA | 10 | | | | |
| TLV | GRC | | 10 | | | |
| NDS/NDSch | POL | 10 | | | | INHAL |
| TLV | ROU | 10 | | 15 | | |
| ПДК | RUS | 10 | | | | a, φ |
| WEL | GBR | 10 | | | | INHAL |
| WEL | GBR | 4 | | | | RESP |
| ACGIH | | 0,2 | | | | RESP |

SECTION 8. Exposure controls/personal protection ... / >>

ETHYLBENZENE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|--------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | ALB | 442 | 100 | 884 | 200 | SKIN |
| TLV | BGR | 435 | | 545 | | SKIN |
| TLV | CZE | 200 | 45,33 | 500 | 113,32 | SKIN |
| AGW | DEU | 88 | 20 | 176 | 40 | SKIN |
| MAK | DEU | 88 | 20 | 176 | 40 | SKIN |
| VLEP | FRA | 88,4 | 20 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 545 | 125 | |
| VLEP | ITA | 442 | 100 | 884 | 200 | SKIN |
| NDS/NDSch | POL | 200 | | 400 | | SKIN |
| TLV | ROU | 442 | 100 | 884 | 200 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 442 | 100 | 884 | 200 | SKIN |
| WEL | GBR | 441 | 100 | 552 | 125 | SKIN |
| OEL | EU | 442 | 100 | 884 | 200 | SKIN |
| ACGIH | | 87 | 20 | | | |

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

SECTION 8. Exposure controls/personal protection ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|------------------------------|---|
| Appearance | liquid | Temperature: 25 °C |
| Colour | white | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | not available | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 23 ≤ T ≤ 60 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 4630-7770 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 6400-10400 mPa.s | Temperature: 25 °C Method: Spindle 5 mm @ 20 rpm Temperature: 25 °C |
| Solubility | not available | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 1,34-1,38 g/cm ³ | Method: ISO 2811 Temperature: 25 °C |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 86,56 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Toluene

Avoid exposure to: light.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

SECTION 10. Stability and reactivity ... / >>

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Toluene

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentamethyl-4-piperidyl Sebacate

Avoid contact with: strong oxidising agents, strong bases, strong acids.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

SECTION 11. Toxicological information ... / >>

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispeš). Is irritating for skin, conjunctiva and respiratory tract.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Toluene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

Toluene

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

| | |
|--|---|
| ATE (Inhalation - mists / powders) of the mixture: | > 5 mg/l |
| ATE (Inhalation - vapours) of the mixture: | > 20 mg/l |
| ATE (Oral) of the mixture: | Not classified (no significant component) |
| ATE (Dermal) of the mixture: | >2000 mg/kg |

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

ATE (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP

SECTION 11. Toxicological information ... / >>

| | |
|--|---|
| ATE (Inhalation vapours): | (figure used for calculation of the acute toxicity estimate of the mixture) 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| Reaction mass of ethylbenzene and xylene | |
| LD50 (Dermal): | 12126 mg/kg Rabbit |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 27,124 mg/l/4h Rat |
| ATE (Inhalation vapours): | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| n-Butyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 13100 mg/kg Rat |
| LC50 (Inhalation vapours): | > 21 mg/l Rat |
| Xylene (mixture of isomers) | |
| LD50 (Dermal): | > 1700 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 5000 ppm/4h Rat |
| 4-morpholinecarbaldehyde | |
| LD50 (Dermal): | > 18400 mg/kg Rabbit |
| LD50 (Oral): | > 7360 mg/kg Rat |
| ETHYLBENZENE | |
| LD50 (Dermal): | 15354 mg/kg Rabbit |
| LD50 (Oral): | 3500 mg/kg Rat |
| LC50 (Inhalation vapours): | 17,2 mg/l/4h Rat |
| 2-Methoxy-1-Methylethyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 8530 mg/kg Rat |
| Toluene | |
| LD50 (Dermal): | 12124 mg/kg Rabbit |
| LD50 (Oral): | 5580 mg/kg Rat |
| LC50 (Inhalation vapours): | 28,1 mg/l/4h Rat |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class



Druckfarben Hellas S.A.

BODENGUARD S-100 White (Comp.-A)

Revision nr.1
Dated 09/01/2026
First compilation
Printed on 12/01/2026
Page n. 15 / 20

EN

SECTION 11. Toxicological information ... / >>

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

Toluene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Reaction mass of ethylbenzene and xylene

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

4-morpholinecarbaldehyde

LC50 - for Fish > 500 mg/l/96h Leuciscus idus (Golden orfe)
EC50 - for Crustacea > 500 mg/l/48h Daphnia magna (Water flea)
EC50 - for Algae / Aquatic Plants 23880 mg/l/72h Scenedesmus subspicatus

12.2. Persistence and degradability

Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)

Solubility in water 0,1 - 100 mg/l
NOT rapidly degradable

TITANIUM DIOXIDE

Solubility in water < 0,001 mg/l
Degradability: information not available

2-Methylpropan-1-ol

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

SECTION 12. Ecological information ... / >>

| | |
|---------------------------------|-------------------|
| Xylene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |
| | |
| n-Butyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| | |
| Xylene (mixture of isomers) | |
| Rapidly degradable | |
| | |
| 4-morpholinecarbaldehyde | |
| Rapidly degradable | |
| | |
| ETHYLBENZENE | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| | |
| Toluene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |

12.3. Bioaccumulative potential

| | |
|--|---------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: n-octanol/water | > 2,918 |
| BCF | 31 |
| | |
| 2-Methylpropan-1-ol | |
| Partition coefficient: n-octanol/water | 1 |
| | |
| Xylene | |
| Partition coefficient: n-octanol/water | 3,12 |
| BCF | 25,9 |
| | |
| n-Butyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| | |
| ETHYLBENZENE | |
| Partition coefficient: n-octanol/water | 3,6 |
| | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| | |
| Toluene | |
| Partition coefficient: n-octanol/water | 2,73 |
| BCF | 90 |

12.4. Mobility in soil

| | |
|--|------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: soil/water | 2,65 |
| | |
| 2-Methylpropan-1-ol | |
| Partition coefficient: soil/water | 0,31 |
| | |
| Solvent naphtha (petroleum), light aromatic | |
| Partition coefficient: soil/water | 1,78 |
| | |
| Xylene | |
| Partition coefficient: soil/water | 2,73 |

12.5. Results of PBT and vPvB assessment

SECTION 12. Ecological information ... / >>

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION

IMDG: RESIN SOLUTION

IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30
 Special provision: -

Limited Quantities: 5 lt

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E

Limited Quantities: 5 lt

IATA: Cargo:

Maximum quantity: 220 L

Packaging instructions: 366

Passengers:

Maximum quantity: 60 L

Packaging instructions: 355

Special provision:

A3

SECTION 14. Transport information ... / >>

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 48

Toluene

REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Repr. 2 | Reproductive toxicity, category 2 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| STOT RE 1 | Specific target organ toxicity - repeated exposure, category 1 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1A | Skin sensitization, category 1A |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic toxicity, category 2 |

SECTION 16. Other information ... / >>

| | |
|--------------------------|--|
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H361d | Suspected of damaging the unborn child. |
| H361f | Suspected of damaging fertility. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament

SECTION 16. Other information ... / >>

12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382982111.**
Product name: **BODENGUARD S-100 (Comp.-B)**
Chemical name and synonym: **Professional use only**

UFI: **D973-E0F2-N00G-F7W0**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Flammable liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Specific target organ toxicity - repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, category 3 | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains: Xylene
 2-Methylpropan-1-ol
 Triethylenetetramine
 Ethylbenzene

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|--|---|--|
| Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine | | |
| <i>INDEX</i> | 50 ≤ x < 100 | Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| <i>EC</i> | 500-191-5 | |
| <i>CAS</i> | 68082-29-1 | |
| 2-Methylpropan-1-ol | | |
| <i>INDEX</i> | 20 ≤ x < 30 | Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336 |
| <i>EC</i> | 201-148-0 | |
| <i>CAS</i> | 78-83-1 | |
| <i>REACH Reg.</i> | 01-2119484609-23-0006 01-2119484609-23-xxxx | |
| Xylene | | |
| <i>INDEX</i> | 10 ≤ x < 20 | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C |
| <i>EC</i> | 215-535-7 | LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h |
| <i>CAS</i> | 1330-20-7 | |
| <i>REACH Reg.</i> | 01-2119488216-32-xxxx 01-2119484661-33-xxxx | |

SECTION 3. Composition/information on ingredients ... / >>

Ethylbenzene

INDEX 601-023-00-4 $5 \leq x < 9$

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

LC50 Inhalation vapours: 11 mg/l/4h

CAS 100-41-4

REACH Reg. 01-2119489370-35

Triethylenetetramine

INDEX 612-059-00-5 $1 \leq x < 3$

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412

EC 292-588-2

ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg

CAS 90640-67-8

REACH Reg. 01-2119487919-13

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

SECTION 5. Firefighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | gesundheits-schädlicher Arbeitsstoffe Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

Xylene

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|---------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

SECTION 8. Exposure controls/personal protection ... / >>

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|-----------------------------|--|
| Appearance | liquid | Temperature: 25 °C |
| Colour | brown | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | > 35 °C | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 22,85 ≤ T < 23 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 300-540 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 280-480 mPas | Temperature: 25 °C |
| Solubility | not available | Temperature: 20 °C |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 0,89-0,93 g/cm ³ | Method: ISO 2811 |
| Relative vapour density | not available | Temperature: 25 °C |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

SECTION 9. Physical and chemical properties ... / >>

Total solids (250°C / 482°F) 53,90 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l

ATE (Oral) of the mixture: >2000 mg/kg

SECTION 11. Toxicological information ... / >>

| | |
|------------------------------|---|
| ATE (Dermal) of the mixture: | >2000 mg/kg |
| | |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| | |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| | |
| Ethylbenzene | |
| LD50 (Dermal): | 15400 mg/kg |
| LD50 (Oral): | 3500 mg/kg |
| LC50 (Inhalation vapours): | 11 mg/l/4h |
| | |
| Triethylenetetramine | |
| ATE (Oral): | 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Ethylbenzene
 LC50 - for Fish 5,1 mg/l/96h Atlantic silverside (*Menidia menidia*)

12.2. Persistence and degradability

2-Methylpropan-1-ol
 Solubility in water 1000 - 10000 mg/l
 Rapidly degradable

Xylene
 Solubility in water 100 - 1000 mg/l
 Rapidly degradable

12.3. Bioaccumulative potential

2-Methylpropan-1-ol
 Partition coefficient: n-octanol/water 1

Xylene
 Partition coefficient: n-octanol/water 3,12
 BCF 25,9

12.4. Mobility in soil

2-Methylpropan-1-ol
 Partition coefficient: soil/water 0,31

Xylene
 Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
 IMDG: RESIN SOLUTION
 IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
 IMDG: not marine pollutant
 IATA: NO

14.6. Special precautions for user

| | | | |
|------------|---|---|--|
| ADR / RID: | HIN - Kemler: 33 Special provision: 640D | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: Passengers: Special provision: | Maximum quantity: 60 L Maximum quantity: 5 L A3 | Packaging instructions: 364 Packaging instructions: 353 |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | |
|----------------------------|--------|
| <u>Product</u> | |
| Point | 3 - 40 |
| <u>Contained substance</u> | |
| Point | 75 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
 not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Skin Corr. 1C | Skin corrosion, category 1C |
| Skin Corr. 1 | Skin corrosion, category 1 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

SECTION 16. Other information ... / >>

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health



Druckfarben Hellas S.A.

BODENGUARD S-100 (Comp.-B)

Revision nr.1
Dated 09/01/2026
First compilation
Printed on 12/01/2026
Page n. 13 / 13

EN

and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382987040**
Product name: **BODENGUARD S-100 RAL 7040 (Comp.-A)**
Chemical name and synonym: **Professional Use only**

UFI: **5A83-G0QU-A00E-DAVS**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|---|
| Flammable liquid, category 3 | H226 | Flammable liquid and vapour. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity - repeated exposure, category 1 | H372 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains:

Cristobalite (STOT RE-1)
 Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene
 2-Methylpropan-1-ol
 Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)
 Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentametyl-4-piperidyl Sebacate
 4-morpholinecarbaldehyde

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|---|-----------------------|---|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | | |
| INDEX | 603-074-00-8 | 30 \leq x < 50 |
| EC | 500-033-5 | Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317 |
| CAS | 25068-38-6 | Skin Irrit. 2 H315: \geq 5%, Eye Irrit. 2 H319: \geq 5% |
| REACH Reg. | Polymer | |
| TITANIUM DIOXIDE | | |
| INDEX | | 9 \leq x < 30 |
| EC | 236-675-5 | |
| CAS | 13463-67-7 | |
| REACH Reg. | 01-2119489379-17-0000 | 01-2119489379-17-0197 01-2119489379-17 |
| Cristobalite (STOT RE-1) | | |
| INDEX | | 10 \leq x < 30 |
| EC | 238-455-4 | STOT RE 1 H372 |
| CAS | 14464-46-1 | |



SECTION 3. Composition/information on ingredients ... / >>

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

INDEX $10 \leq x < 20$

EC 905-562-9

CAS

REACH Reg. 01-2119555267-33

Reaction mass of ethylbenzene and xylene

INDEX $5 \leq x < 9$

EC 905-588-0

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

2-Methylpropan-1-ol

INDEX 603-108-00-1 $3 \leq x < 5$

EC 201-148-0

CAS 78-83-1

REACH Reg. 01-2119484609-23-0006 01-2119484609-23-xxxx

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentamethyl-4-piperidyl Sebacate

INDEX $0,5 \leq x < 1$

EC 915-687-0

CAS 1065336-91-5

REACH Reg. 01-2119491304-40-0000 01-2119491304-40-0002

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32-xxxx 01-2119484661-33-xxxx

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

4-morpholinecarbaldehyde

INDEX $0 < x < 0,5$

EC 224-518-3

CAS 4394-85-8

REACH Reg. 01-2119987993-12

Trimethylolpropane (TMP)

INDEX $0 < x < 0,5$

EC 201-074-9

CAS 77-99-6

REACH Reg. 01-2119486799-10-0000

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$

EC 202-849-4

CAS 100-41-4

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336

Sepracat. 2 H361f, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C

LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

Skin Sens. 1B H317

Repr. 2 H361fd

Flam. Liq. 3 H226, STOT SE 3 H336

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

LC50 Inhalation vapours: 17,2 mg/l/4h

SECTION 3. Composition/information on ingredients ... / >>

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$

Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

Toluene

INDEX $0 < x < 0,5$

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

EC 203-625-9

CAS 108-88-3

REACH Reg. 01-2119471310-51

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| ALB | Shqipëria | VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË" |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe |



Druckfarben Hellas S.A.

BODENGUARD S-100 RAL 7040 (Comp.-A)

Revision nr.1
Dated 16/01/2026
First compilation
Printed on 16/01/2026
Page n. 6 / 20

EN

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

4-morpholinecarbaldehyde

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,5 | mg/l |
| Normal value in marine water | 0,05 | mg/l |
| Normal value for fresh water sediment | 1,85 | mg/kg |
| Normal value for marine water sediment | 0,0764 | mg/kg |
| Normal value for water, intermittent release | 5 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | VND | 29 | | | VND | 98 |
| | | | | mg/m3 | | | | mg/m3 |
| Skin | | | VND | 8 | | | 0,293 | VND |
| | | | | mg/kg/d | | | mg/cm2 | |

Cristobalite (STOT RE-1)

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 3,6 | | | | |
| | | | | mg/kg/d | | | | |
| Inhalation | | | VND | 0,08 | | | VND | 0,33 |
| | | | | mg/m3 | | | | mg/m3 |

SECTION 8. Exposure controls/personal protection ... / >>
Xylene
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|---------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Quartz (Crystalline Silica)
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| VLEP | FRA | 0,1 | | | | RESP |
| VLEP | ITA | 0,1 | | | | RESP |
| NDS/NDSch | POL | 0,1 | | | | RESP |
| TLV | ROU | 0,1 | | | | RESP |
| OEL | EU | 0,1 | | | | RESP |
| ACGIH | | 0,025 | | | | RESP |

Toluene
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|--------|------------|---------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 192 | 50 | 384 | 100 | SKIN |
| TLV | CZE | 192 | 50,112 | 384 | 100,224 | SKIN |
| AGW | DEU | 190 | 50 | 760 | 200 | SKIN |
| MAK | DEU | 190 | 50 | 380 | 100 | SKIN |
| VLEP | FRA | 76,8 | 20 | 384 | 100 | SKIN |
| TLV | GRC | 192 | 50 | 384 | 100 | |
| VLEP | ITA | 192 | 50 | | | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 192 | 50 | 384 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 192 | 50 | 384 | 100 | SKIN |
| WEL | GBR | 191 | 50 | 384 | 100 | SKIN |
| OEL | EU | 192 | 50 | 384 | 100 | SKIN |
| ACGIH | | | 20 | | | |

SECTION 8. Exposure controls/personal protection ... / >>

Xylene (mixture of isomers)

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|-------------------|-----|-------------------|-----|------------------------|
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| TLV | CZE | 200 | | 400 | | |
| MAK | DEU | | 100 | | 200 | |
| VLEP | FRA | 221 | 50 | 442 | 100 | |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| NDS/NDSch | POL | 100 | | 350 | | |
| ESD | TUR | 221 | 50 | 442 | 100 | |
| WEL | GBR | | 50 | | 100 | |
| OEL | EU | 221 | 50 | 442 | 100 | |
| ACGIH | | | 100 | | 150 | |

Predicted no-effect concentration - PNEC

| | | |
|--|-------|-------|
| Normal value in fresh water | 0,327 | mg/l |
| Normal value in marine water | 0,327 | mg/l |
| Normal value for fresh water sediment | 12,46 | mg/kg |
| Normal value for marine water sediment | 12,46 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|-----------------------|-----------------------|---------------|------------------------|-----------------------|-----------------------|---------------|----------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,6 mg/kg/d | | | | |
| Inhalation | 174 mg/m ³ | 174 mg/m ³ | VND | 14,8 mg/m ³ | 289 mg/m ³ | 289 mg/m ³ | VND | 77 mg/m ³ |
| Skin | | | VND | 108 mg/kg/d | | | VND | 180 mg/kg/d |

n-Butyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|-------------------|-------|-------------------|-------|------------------------|
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,635 | mg/l |
| Normal value in marine water | 0,0635 | ml/l |
| Normal value for fresh water sediment | 3,29 | mg/kg |
| Normal value for marine water sediment | 0,329 | mg/kg |
| Normal value for water, intermittent release | 6,35 | mg/l |
| Normal value of STP microorganisms | 100 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|----------------------|-------------------------|----------------|---------------|-----------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,67 mg/kg | | | | |
| Inhalation | | | VND | 33 mg/m ³ | 553,5 mg/m ³ | VND | VND | 275 mg/m ³ |
| Skin | | | VND | 54,8 mg/kg | | | VND | 153,5 mg/kg |

SECTION 8. Exposure controls/personal protection ... / >>

TITANIUM DIOXIDE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 10 | | | | RESP |
| MAK | DEU | 0,3 | | 2,4 | | RESP Hinweis |
| VLEP | FRA | 10 | | | | |
| TLV | GRC | | 10 | | | |
| NDS/NDSch | POL | 10 | | | | INHAL |
| TLV | ROU | 10 | | 15 | | |
| ΠΔΚ | RUS | 10 | | | | a, φ |
| WEL | GBR | 10 | | | | INHAL |
| WEL | GBR | 4 | | | | RESP |
| ACGIH | | 0,2 | | | | RESP |

ETHYLBENZENE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|--------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | ALB | 442 | 100 | 884 | 200 | SKIN |
| TLV | BGR | 435 | | 545 | | SKIN |
| TLV | CZE | 200 | 45,33 | 500 | 113,32 | SKIN |
| AGW | DEU | 88 | 20 | 176 | 40 | SKIN |
| MAK | DEU | 88 | 20 | 176 | 40 | SKIN |
| VLEP | FRA | 88,4 | 20 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 545 | 125 | |
| VLEP | ITA | 442 | 100 | 884 | 200 | SKIN |
| NDS/NDSch | POL | 200 | | 400 | | SKIN |
| TLV | ROU | 442 | 100 | 884 | 200 | SKIN |
| ΠΔΚ | RUS | 50 | | 150 | | n |
| ESD | TUR | 442 | 100 | 884 | 200 | SKIN |
| WEL | GBR | 441 | 100 | 552 | 125 | SKIN |
| OEL | EU | 442 | 100 | 884 | 200 | SKIN |
| ACGIH | | 87 | 20 | | | |

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ΠΔΚ | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

SECTION 8. Exposure controls/personal protection ... / >>

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|------------------------------|---|
| Appearance | liquid | Temperature: 25 °C |
| Colour | grey | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | not available | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 23 ≤ T ≤ 60 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 4630-7770 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density Temperature: 25 °C |
| Dynamic viscosity | 6400-10400 mPa.s | Method: Spindle 5 mm @ 20 rpm Temperature: 25 °C |
| Solubility | not available | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 1,34-1,38 g/cm ³ | Method: ISO 2811 Temperature: 25 °C |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |

Supplementary information for nanoforms

C.I. Pigment Blue 15:3

Denomination: Quinacridone Violet

9.2. Other information

9.2.1. Information with regard to physical hazard classes

SECTION 9. Physical and chemical properties ... / >>

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 86,05 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Toluene

Avoid exposure to: light.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Toluene

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

Avoid contact with: strong oxidising agents, strong bases, strong acids.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.



SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Toluene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

SECTION 11. Toxicological information ... / >>

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

Toluene

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l
ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: >2000 mg/kg

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Reaction mass of ethylbenzene and xylene

LD50 (Dermal): 12126 mg/kg Rabbit
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 27,124 mg/l/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

2-Methylpropan-1-ol

LD50 (Dermal): 2460 mg/kg Rabbit
LD50 (Oral): 2460 mg/kg Rat
LC50 (Inhalation vapours): 19,2 mg/l/4h Rat

n-Butyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

Xylene

LD50 (Dermal): 1100 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 11 mg/l/4h Rat

Xylene (mixture of isomers)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

4-morpholinecarbaldehyde

LD50 (Dermal): > 18400 mg/kg Rabbit
LD50 (Oral): > 7360 mg/kg Rat

2-Methoxy-1-Methylethyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat



SECTION 11. Toxicological information ... / >>

ETHYLBENZENE
LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat

Toluene
LD50 (Dermal): 12124 mg/kg Rabbit
LD50 (Oral): 5580 mg/kg Rat
LC50 (Inhalation vapours): 28,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

Toluene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

SECTION 12. Ecological information ... / >>

12.1. Toxicity

| | |
|--|---|
| Reaction mass of ethylbenzene and xylene | |
| LC50 - for Fish | 18 mg/l/96h Fresh Water Fish |
| EC50 - for Algae / Aquatic Plants | 1,3 mg/l/72h Algae |
| Xylene (mixture of isomers) | |
| LC50 - for Fish | > 100 mg/l/96h Microorganisms |
| 4-morpholinecarbaldehyde | |
| LC50 - for Fish | > 500 mg/l/96h Leuciscus idus (Golden orfe) |
| EC50 - for Crustacea | > 500 mg/l/48h Daphnia magna (Water flea) |
| EC50 - for Algae / Aquatic Plants | 23880 mg/l/72h Scenedesmus subspicatus |

12.2. Persistence and degradability

| | |
|--|-------------------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Solubility in water | 0,1 - 100 mg/l |
| NOT rapidly degradable | |
| TITANIUM DIOXIDE | |
| Solubility in water | < 0,001 mg/l |
| Degradability: information not available | |
| 2-Methylpropan-1-ol | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| n-Butyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| Xylene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |
| Xylene (mixture of isomers) | |
| Rapidly degradable | |
| 4-morpholinecarbaldehyde | |
| Rapidly degradable | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| ETHYLBENZENE | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| Toluene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |

12.3. Bioaccumulative potential

| | |
|--|---------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: n-octanol/water | > 2,918 |
| BCF | 31 |
| 2-Methylpropan-1-ol | |
| Partition coefficient: n-octanol/water | 1 |
| n-Butyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |

SECTION 12. Ecological information ... / >>

| | |
|--|------|
| Xylene | |
| Partition coefficient: n-octanol/water | 3,12 |
| BCF | 25,9 |
| | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| | |
| ETHYLBENZENE | |
| Partition coefficient: n-octanol/water | 3,6 |
| | |
| Toluene | |
| Partition coefficient: n-octanol/water | 2,73 |
| BCF | 90 |

12.4. Mobility in soil

| | |
|--|------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: soil/water | 2,65 |
| | |
| 2-Methylpropan-1-ol | |
| Partition coefficient: soil/water | 0,31 |
| | |
| Xylene | |
| Partition coefficient: soil/water | 2,73 |

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
 Waste transportation may be subject to ADR restrictions.
 The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
CONTAMINATED PACKAGING
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
 IMDG: RESIN SOLUTION
 IATA: RESIN SOLUTION

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

| | | | |
|------------|---|---|--|
| ADR / RID: | HIN - Kemler: 30 Special provision: - | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: Passengers: Special provision: | Maximum quantity: 220 L Maximum quantity: 60 L A3 | Packaging instructions: 366 Packaging instructions: 355 |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 48

Toluene

REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

SECTION 15. Regulatory information ... / >>

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Repr. 2 | Reproductive toxicity, category 2 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| STOT RE 1 | Specific target organ toxicity - repeated exposure, category 1 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1A | Skin sensitization, category 1A |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H361d | Suspected of damaging the unborn child. |
| H361f | Suspected of damaging fertility. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP

SECTION 16. Other information ... / >>

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for



Druckfarben Hellas S.A.

BODENGUARD S-100 RAL 7040 (Comp.-A)

Revision nr.1
Dated 16/01/2026
First compilation
Printed on 16/01/2026
Page n. 20 / 20

EN

evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382982111.**
Product name: **BODENGUARD S-100 (Comp.-B)**
Chemical name and synonym: **Professional use only**

UFI: **D973-E0F2-N00G-F7W0**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Flammable liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Specific target organ toxicity - repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, category 3 | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains: Xylene
 2-Methylpropan-1-ol
 Triethylenetetramine
 Ethylbenzene

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|--|---|--|
| Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine | | |
| <i>INDEX</i> | 50 ≤ x < 100 | Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| <i>EC</i> | 500-191-5 | |
| <i>CAS</i> | 68082-29-1 | |
| 2-Methylpropan-1-ol | | |
| <i>INDEX</i> | 20 ≤ x < 30 | Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336 |
| <i>EC</i> | 201-148-0 | |
| <i>CAS</i> | 78-83-1 | |
| <i>REACH Reg.</i> | 01-2119484609-23-0006 01-2119484609-23-xxxx | |
| Xylene | | |
| <i>INDEX</i> | 10 ≤ x < 20 | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C |
| <i>EC</i> | 215-535-7 | LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h |
| <i>CAS</i> | 1330-20-7 | |
| <i>REACH Reg.</i> | 01-2119488216-32-xxxx 01-2119484661-33-xxxx | |

SECTION 3. Composition/information on ingredients ... / >>

Ethylbenzene

INDEX 601-023-00-4 $5 \leq x < 9$

EC 202-849-4
CAS 100-41-4
REACH Reg. 01-2119489370-35

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373,
Aquatic Chronic 3 H412
LC50 Inhalation vapours: 11 mg/l/4h

Triethylenetetramine

INDEX 612-059-00-5 $1 \leq x < 3$

EC 292-588-2
CAS 90640-67-8
REACH Reg. 01-2119487919-13

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318,
Skin Sens. 1B H317, Aquatic Chronic 3 H412
ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

SECTION 5. Firefighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | gesundheits-schädlicher Arbeitsstoffe Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

Xylene

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|---------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

SECTION 8. Exposure controls/personal protection ... / >>

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|-----------------------------|--|
| Appearance | liquid | Temperature: 25 °C |
| Colour | brown | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | > 35 °C | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 22,85 ≤ T < 23 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 300-540 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 280-480 mPas | Temperature: 25 °C |
| Solubility | not available | Temperature: 20 °C |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 0,89-0,93 g/cm ³ | Method: ISO 2811 |
| Relative vapour density | not available | Temperature: 25 °C |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

SECTION 9. Physical and chemical properties ... / >>

Total solids (250°C / 482°F) 53,90 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l

ATE (Oral) of the mixture: >2000 mg/kg

SECTION 11. Toxicological information ... / >>

| | |
|------------------------------|---|
| ATE (Dermal) of the mixture: | >2000 mg/kg |
| | |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| | |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| | |
| Ethylbenzene | |
| LD50 (Dermal): | 15400 mg/kg |
| LD50 (Oral): | 3500 mg/kg |
| LC50 (Inhalation vapours): | 11 mg/l/4h |
| | |
| Triethylenetetramine | |
| ATE (Oral): | 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Ethylbenzene
LC50 - for Fish 5,1 mg/l/96h Atlantic silverside (*Menidia menidia*)

12.2. Persistence and degradability

2-Methylpropan-1-ol
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Xylene
Solubility in water 100 - 1000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

2-Methylpropan-1-ol
Partition coefficient: n-octanol/water 1

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

12.4. Mobility in soil

2-Methylpropan-1-ol
Partition coefficient: soil/water 0,31

Xylene
Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
 IMDG: RESIN SOLUTION
 IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
 IMDG: not marine pollutant
 IATA: NO

14.6. Special precautions for user

| | | | |
|------------|---|---|--|
| ADR / RID: | HIN - Kemler: 33 Special provision: 640D | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: Passengers: Special provision: | Maximum quantity: 60 L Maximum quantity: 5 L A3 | Packaging instructions: 364 Packaging instructions: 353 |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | |
|----------------------------|--------|
| <u>Product</u> | |
| Point | 3 - 40 |
| <u>Contained substance</u> | |
| Point | 75 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
 not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Skin Corr. 1C | Skin corrosion, category 1C |
| Skin Corr. 1 | Skin corrosion, category 1 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

SECTION 16. Other information ... / >>

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health



Druckfarben Hellas S.A.

BODENGUARD S-100 (Comp.-B)

Revision nr.1
Dated 09/01/2026
First compilation
Printed on 12/01/2026
Page n. 13 / 13

EN

and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382987035**
Product name: **BODENGUARD S-100 RAL 7035 (Comp.-A)**
Chemical name and synonym: **Professional Use only**

UFI: **Y783-001F-000X-R09Q**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|---|
| Flammable liquid, category 3 | H226 | Flammable liquid and vapour. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity - repeated exposure, category 1 | H372 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

| | |
|-------------|---|
| H226 | Flammable liquid and vapour. |
| H332 | Harmful if inhaled. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| H318 | Causes serious eye damage. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements:

| | |
|-----------------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P331 | Do NOT induce vomiting. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P280 | Wear protective gloves/ protective clothing / eye protection / face protection. |
| P310 | Immediately call a POISON CENTER or a doctor |
| P370+P378 | In case of fire: use alcohol resistant foam to extinguish. |
| P102 | Keep out of reach of children. |
| P501 | Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations. |

Contains:

Cristobalite (STOT RE-1)
Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene
2-Methylpropan-1-ol
Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)
Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentametyl-4-piperidyl Sebacate
4-morpholinecarbaldehyde

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|---|-----------------------|---|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | | |
| INDEX | 603-074-00-8 | $30 \leq x < 50$ Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317 |
| EC | 500-033-5 | Skin Irrit. 2 H315: $\geq 5\%$, Eye Irrit. 2 H319: $\geq 5\%$ |
| CAS | 25068-38-6 | |
| REACH Reg. | Polymer | |
| TITANIUM DIOXIDE | | |
| INDEX | | $9 \leq x < 30$ |
| EC | 236-675-5 | |
| CAS | 13463-67-7 | |
| REACH Reg. | 01-2119489379-17-0000 | 01-2119489379-17-0197 01-2119489379-17 |
| Cristobalite (STOT RE-1) | | |
| INDEX | | $10 \leq x < 30$ STOT RE 1 H372 |
| EC | 238-455-4 | |
| CAS | 14464-46-1 | |

SECTION 3. Composition/information on ingredients ... / >>

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

INDEX $10 \leq x < 20$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

EC 905-562-9

ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l

CAS

REACH Reg. 01-2119555267-33

Reaction mass of ethylbenzene and xylene

INDEX $5 \leq x < 9$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

EC 905-588-0

ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

2-Methylpropan-1-ol

INDEX 603-108-00-1 $3 \leq x < 5$

Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336

EC 201-148-0

CAS 78-83-1

REACH Reg. 01-2119484609-23-0006 01-2119484609-23-xxxx

Solvent naphtha (petroleum), light aromatic

INDEX 649-356-00-4 $1 \leq x < 2,5$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 265-199-0

CAS 64742-95-6

REACH Reg. 01-2119455851-35

Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentamethyl-4-piperidyl Sebacate

INDEX $0,5 \leq x < 1$

Repr. 2 H361f, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 915-687-0

CAS 1065336-91-5

REACH Reg. 01-2119491304-40-0000 01-2119491304-40-0002

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32-xxxx 01-2119484661-33-xxxx

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

4-morpholinecarbaldehyde

INDEX $0 < x < 0,5$

Skin Sens. 1B H317

EC 224-518-3

CAS 4394-85-8

REACH Reg. 01-2119987993-12

Trimethylolpropane (TMP)

INDEX $0 < x < 0,5$

Repr. 2 H361fd

EC 201-074-9

CAS 77-99-6

REACH Reg. 01-2119486799-10-0000

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$

Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

SECTION 3. Composition/information on ingredients ... / >>

ETHYLBENZENE

INDEX 601-023-00-4 0 < x < 0,5

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

CAS 100-41-4

LC50 Inhalation vapours: 17,2 mg/l/4h

Quartz (Crystalline Silica)

INDEX 0 < x < 0,5

Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

Toluene

INDEX 0 < x < 0,5

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

EC 203-625-9

CAS 108-88-3

REACH Reg. 01-2119471310-51

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

SECTION 5. Firefighting measures ... / >>

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------|--|
| ALB | Shqipëria | VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË" |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 |

**SECTION 8. Exposure controls/personal protection ... / >>**

| | | |
|-----|-----------------|--|
| CZE | Česká Republika | Април 2024г.) NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe |
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

4-morpholinecarbaldehyde**Predicted no-effect concentration - PNEC**

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,5 | mg/l |
| Normal value in marine water | 0,05 | mg/l |
| Normal value for fresh water sediment | 1,85 | mg/kg |
| Normal value for marine water sediment | 0,0764 | mg/kg |
| Normal value for water, intermittent release | 5 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|-----------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | VND | 29 mg/m3 | | | VND | 98 mg/m3 |
| Skin | | | VND | 8 mg/kg/d | | | 0,293 mg/cm2 | VND |

Cristobalite (STOT RE-1)**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 3,6 mg/kg/d | | | | |
| Inhalation | | | VND | 0,08 mg/m3 | | | VND | 0,33 mg/m3 |

SECTION 8. Exposure controls/personal protection ... / >>

Xylene

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|---------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Quartz (Crystalline Silica)

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| VLEP | FRA | 0,1 | | | | RESP |
| VLEP | ITA | 0,1 | | | | RESP |
| NDS/NDSch | POL | 0,1 | | | | RESP |
| TLV | ROU | 0,1 | | | | RESP |
| OEL | EU | 0,1 | | | | RESP |
| ACGIH | | 0,025 | | | | RESP |

Solvent naphtha (petroleum), light aromatic

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | GRC | 100 | | | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 11 mg/kg/d | | | | |
| Inhalation | | | VND | 32 mg/m3 | | | VND | 150 mg/m3 |
| Skin | | | VND | 11 mg/kg/d | | | VND | 25 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

| Toluene | | | | | | |
|-----------------------|---------|--------|--------|------------|---------|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 192 | 50 | 384 | 100 | SKIN |
| TLV | CZE | 192 | 50,112 | 384 | 100,224 | SKIN |
| AGW | DEU | 190 | 50 | 760 | 200 | SKIN |
| MAK | DEU | 190 | 50 | 380 | 100 | SKIN |
| VLEP | FRA | 76,8 | 20 | 384 | 100 | SKIN |
| TLV | GRC | 192 | 50 | 384 | 100 | |
| VLEP | ITA | 192 | 50 | | | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 192 | 50 | 384 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 192 | 50 | 384 | 100 | SKIN |
| WEL | GBR | 191 | 50 | 384 | 100 | SKIN |
| OEL | EU | 192 | 50 | 384 | 100 | SKIN |
| ACGIH | | | 20 | | | |

| Xylene (mixture of isomers) | | | | | | |
|-----------------------------|---------|--------|-----|------------|-----|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 200 | | 400 | | |
| MAK | DEU | | 100 | | 200 | |
| VLEP | FRA | 221 | 50 | 442 | 100 | |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| NDS/NDSch | POL | 100 | | 350 | | |
| ESD | TUR | 221 | 50 | 442 | 100 | |
| WEL | GBR | | 50 | | 100 | |
| OEL | EU | 221 | 50 | 442 | 100 | |
| ACGIH | | | 100 | | 150 | |

Predicted no-effect concentration - PNEC

| | | |
|--|-------|-------|
| Normal value in fresh water | 0,327 | mg/l |
| Normal value in marine water | 0,327 | mg/l |
| Normal value for fresh water sediment | 12,46 | mg/kg |
| Normal value for marine water sediment | 12,46 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,6 mg/kg/d | | | | |
| Inhalation | 174 mg/m3 | 174 mg/m3 | VND | 14,8 mg/m3 | 289 mg/m3 | 289 mg/m3 | VND | 77 mg/m3 |
| Skin | | | VND | 108 mg/kg/d | | | VND | 180 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,635 | mg/l |
| Normal value in marine water | 0,0635 | ml/l |
| Normal value for fresh water sediment | 3,29 | mg/kg |
| Normal value for marine water sediment | 0,329 | mg/kg |
| Normal value for water, intermittent release | 6,35 | mg/l |
| Normal value of STP microorganisms | 100 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,67 mg/kg | | | | |
| Inhalation | | | VND | 33 mg/m3 | 553,5 mg/m3 | VND | VND | 275 mg/m3 |
| Skin | | | VND | 54,8 mg/kg | | | VND | 153,5 mg/kg |

TITANIUM DIOXIDE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 10 | | | | RESP |
| MAK | DEU | 0,3 | | 2,4 | | RESP Hinweis |
| VLEP | FRA | 10 | | | | |
| TLV | GRC | | 10 | | | |
| NDS/NDSch | POL | 10 | | | | INHAL |
| TLV | ROU | 10 | | 15 | | |
| ПДК | RUS | 10 | | | | a, φ |
| WEL | GBR | 10 | | | | INHAL |
| WEL | GBR | 4 | | | | RESP |
| ACGIH | | 0,2 | | | | RESP |

SECTION 8. Exposure controls/personal protection ... / >>

ETHYLBENZENE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|--------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | ALB | 442 | 100 | 884 | 200 | SKIN |
| TLV | BGR | 435 | | 545 | | SKIN |
| TLV | CZE | 200 | 45,33 | 500 | 113,32 | SKIN |
| AGW | DEU | 88 | 20 | 176 | 40 | SKIN |
| MAK | DEU | 88 | 20 | 176 | 40 | SKIN |
| VLEP | FRA | 88,4 | 20 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 545 | 125 | |
| VLEP | ITA | 442 | 100 | 884 | 200 | SKIN |
| NDS/NDSch | POL | 200 | | 400 | | SKIN |
| TLV | ROU | 442 | 100 | 884 | 200 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 442 | 100 | 884 | 200 | SKIN |
| WEL | GBR | 441 | 100 | 552 | 125 | SKIN |
| OEL | EU | 442 | 100 | 884 | 200 | SKIN |
| ACGIH | | 87 | 20 | | | |

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

SECTION 8. Exposure controls/personal protection ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|------------------------------|---|
| Appearance | liquid | Temperature: 25 °C |
| Colour | light grey | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | not available | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 23 ≤ T ≤ 60 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 4630-7770 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 6400-10400 mPa.s | Temperature: 25 °C Method: Spindle 5 mm @ 20 rpm Temperature: 25 °C |
| Solubility | not available | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 1,34-1,38 g/cm ³ | Method: ISO 2811 Temperature: 25 °C |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |

Supplementary information for nanoforms

C.I. Pigment Blue 15:3

Denomination: Quinacridone Violet

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 86,45 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Toluene

Avoid exposure to: light.

n-Butyl Acetate

Stable in normal conditions of use and storage.

SECTION 10. Stability and reactivity ... / >>

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Toluene

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric acid and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

Avoid contact with: strong oxidising agents, strong bases, strong acids.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

SECTION 11. Toxicological information ... / >>

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesi). Is irritating for skin, conjunctiva and respiratory tract.

Toluene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

Toluene

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

| | |
|--|---|
| ATE (Inhalation - mists / powders) of the mixture: | > 5 mg/l |
| ATE (Inhalation - vapours) of the mixture: | > 20 mg/l |
| ATE (Oral) of the mixture: | Not classified (no significant component) |
| ATE (Dermal) of the mixture: | >2000 mg/kg |

SECTION 11. Toxicological information ... / >>

| | |
|---|---|
| TITANIUM DIOXIDE | |
| LD50 (Oral): | > 10000 mg/kg Rat |
| Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene | |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Inhalation mists/powders): | 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Inhalation vapours): | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| Reaction mass of ethylbenzene and xylene | |
| LD50 (Dermal): | 12126 mg/kg Rabbit |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 27,124 mg/l/4h Rat |
| ATE (Inhalation vapours): | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| n-Butyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 13100 mg/kg Rat |
| LC50 (Inhalation vapours): | > 21 mg/l Rat |
| Xylene (mixture of isomers) | |
| LD50 (Dermal): | > 1700 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 5000 ppm/4h Rat |
| 4-morpholinecarbaldehyde | |
| LD50 (Dermal): | > 18400 mg/kg Rabbit |
| LD50 (Oral): | > 7360 mg/kg Rat |
| 2-Methoxy-1-Methylethyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 8530 mg/kg Rat |
| ETHYLBENZENE | |
| LD50 (Dermal): | 15354 mg/kg Rabbit |
| LD50 (Oral): | 3500 mg/kg Rat |
| LC50 (Inhalation vapours): | 17,2 mg/l/4h Rat |
| Toluene | |
| LD50 (Dermal): | 12124 mg/kg Rabbit |
| LD50 (Oral): | 5580 mg/kg Rat |
| LC50 (Inhalation vapours): | 28,1 mg/l/4h Rat |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

SECTION 11. Toxicological information ... / >>

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

Toluene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Reaction mass of ethylbenzene and xylene

| | |
|-----------------------------------|------------------------------|
| LC50 - for Fish | 18 mg/l/96h Fresh Water Fish |
| EC50 - for Algae / Aquatic Plants | 1,3 mg/l/72h Algae |

Xylene (mixture of isomers)

| | |
|-----------------|-------------------------------|
| LC50 - for Fish | > 100 mg/l/96h Microorganisms |
|-----------------|-------------------------------|

4-morpholinecarbaldehyde

| | |
|-----------------------------------|---|
| LC50 - for Fish | > 500 mg/l/96h Leuciscus idus (Golden orfe) |
| EC50 - for Crustacea | > 500 mg/l/48h Daphnia magna (Water flea) |
| EC50 - for Algae / Aquatic Plants | 23880 mg/l/72h Scenedesmus subspicatus |

12.2. Persistence and degradability

Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)

| | |
|---------------------|----------------|
| Solubility in water | 0,1 - 100 mg/l |
|---------------------|----------------|

NOT rapidly degradable

SECTION 12. Ecological information ... / >>

| | |
|--|-------------------|
| TITANIUM DIOXIDE | |
| Solubility in water | < 0,001 mg/l |
| Degradability: information not available | |
| 2-Methylpropan-1-ol | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| Xylene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |
| n-Butyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| Xylene (mixture of isomers) | |
| Rapidly degradable | |
| 4-morpholinecarbaldehyde | |
| Rapidly degradable | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| ETHYLBENZENE | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| Toluene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |

12.3. Bioaccumulative potential

| | |
|--|---------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: n-octanol/water | > 2,918 |
| BCF | 31 |
| 2-Methylpropan-1-ol | |
| Partition coefficient: n-octanol/water | 1 |
| Xylene | |
| Partition coefficient: n-octanol/water | 3,12 |
| BCF | 25,9 |
| n-Butyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| 2-Methoxy-1-Methylethyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| ETHYLBENZENE | |
| Partition coefficient: n-octanol/water | 3,6 |
| Toluene | |
| Partition coefficient: n-octanol/water | 2,73 |
| BCF | 90 |

12.4. Mobility in soil

| | |
|--|------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: soil/water | 2,65 |

SECTION 12. Ecological information ... / >>

| | |
|--|------|
| 2-Methylpropan-1-ol Partition coefficient: soil/water | 0,31 |
| Solvent naphtha (petroleum), light aromatic Partition coefficient: soil/water | 1,78 |
| Xylene Partition coefficient: soil/water | 2,73 |

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
IMDG: RESIN SOLUTION
IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

| | | | |
|------------|----------------------|--------------------------|--------------------------------|
| ADR / RID: | HIN - Kemler: 30 | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| | Special provision: - | | |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: | Maximum quantity: 220 L | Packaging instructions: 366 |
| | Passengers: | Maximum quantity: 60 L | Packaging instructions: 355 |
| | Special provision: | A3 | |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 48

Toluene

REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|---------------------|------------------------------|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |

SECTION 16. Other information ... / >>

| | |
|--------------------------|--|
| Repr. 2 | Reproductive toxicity, category 2 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| STOT RE 1 | Specific target organ toxicity - repeated exposure, category 1 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1A | Skin sensitization, category 1A |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H361d | Suspected of damaging the unborn child. |
| H361f | Suspected of damaging fertility. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative

SECTION 16. Other information ... / >>

- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382982111.**
Product name: **BODENGUARD S-100 (Comp.-B)**
Chemical name and synonym: **Professional use only**

UFI: **D973-E0F2-N00G-F7W0**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Flammable liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Specific target organ toxicity - repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, category 3 | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains: Xylene
 2-Methylpropan-1-ol
 Triethylenetetramine
 Ethylbenzene

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|--|---|--|
| Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine | | |
| <i>INDEX</i> | 50 ≤ x < 100 | Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| <i>EC</i> | 500-191-5 | |
| <i>CAS</i> | 68082-29-1 | |
| 2-Methylpropan-1-ol | | |
| <i>INDEX</i> | 20 ≤ x < 30 | Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336 |
| <i>EC</i> | 201-148-0 | |
| <i>CAS</i> | 78-83-1 | |
| <i>REACH Reg.</i> | 01-2119484609-23-0006 01-2119484609-23-xxxx | |
| Xylene | | |
| <i>INDEX</i> | 10 ≤ x < 20 | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C |
| <i>EC</i> | 215-535-7 | LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h |
| <i>CAS</i> | 1330-20-7 | |
| <i>REACH Reg.</i> | 01-2119488216-32-xxxx 01-2119484661-33-xxxx | |

SECTION 3. Composition/information on ingredients ... / >>

Ethylbenzene

INDEX 601-023-00-4 $5 \leq x < 9$

EC 202-849-4
CAS 100-41-4
REACH Reg. 01-2119489370-35

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373,
Aquatic Chronic 3 H412
LC50 Inhalation vapours: 11 mg/l/4h

Triethylenetetramine

INDEX 612-059-00-5 $1 \leq x < 3$

EC 292-588-2
CAS 90640-67-8
REACH Reg. 01-2119487919-13

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318,
Skin Sens. 1B H317, Aquatic Chronic 3 H412
ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

SECTION 5. Firefighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | gesundheits-schädlicher Arbeitsstoffe Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

Xylene

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|---------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

SECTION 8. Exposure controls/personal protection ... / >>

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|-----------------------------|--|
| Appearance | liquid | Temperature: 25 °C |
| Colour | brown | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | > 35 °C | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 22,85 ≤ T < 23 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 300-540 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 280-480 mPas | Temperature: 25 °C |
| Solubility | not available | Temperature: 20 °C |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 0,89-0,93 g/cm ³ | Method: ISO 2811 |
| Relative vapour density | not available | Temperature: 25 °C |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

SECTION 9. Physical and chemical properties ... / >>

Total solids (250°C / 482°F) 53,90 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l

ATE (Oral) of the mixture: >2000 mg/kg

SECTION 11. Toxicological information ... / >>

| | |
|------------------------------|---|
| ATE (Dermal) of the mixture: | >2000 mg/kg |
| | |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| | |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| | |
| Ethylbenzene | |
| LD50 (Dermal): | 15400 mg/kg |
| LD50 (Oral): | 3500 mg/kg |
| LC50 (Inhalation vapours): | 11 mg/l/4h |
| | |
| Triethylenetetramine | |
| ATE (Oral): | 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
 May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

| | |
|---------------------------------|---|
| Ethylbenzene LC50 - for Fish | 5,1 mg/l/96h Atlantic silverside (<i>Menidia menidia</i>) |
|---------------------------------|---|

12.2. Persistence and degradability

| | |
|--|-------------------|
| 2-Methylpropan-1-ol Solubility in water Rapidly degradable | 1000 - 10000 mg/l |
|--|-------------------|

| | |
|---|-----------------|
| Xylene Solubility in water Rapidly degradable | 100 - 1000 mg/l |
|---|-----------------|

12.3. Bioaccumulative potential

| | |
|---|---|
| 2-Methylpropan-1-ol Partition coefficient: n-octanol/water | 1 |
|---|---|

| | |
|---|--------------|
| Xylene Partition coefficient: n-octanol/water BCF | 3,12 25,9 |
|---|--------------|

12.4. Mobility in soil

| | |
|--|------|
| 2-Methylpropan-1-ol Partition coefficient: soil/water | 0,31 |
|--|------|

| | |
|---|------|
| Xylene Partition coefficient: soil/water | 2,73 |
|---|------|

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
 IMDG: RESIN SOLUTION
 IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
 IMDG: not marine pollutant
 IATA: NO

14.6. Special precautions for user

| | | | |
|------------|---|---|--|
| ADR / RID: | HIN - Kemler: 33 Special provision: 640D | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: Passengers: Special provision: | Maximum quantity: 60 L Maximum quantity: 5 L A3 | Packaging instructions: 364 Packaging instructions: 353 |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | |
|----------------------------|--------|
| <u>Product</u> | |
| Point | 3 - 40 |
| <u>Contained substance</u> | |
| Point | 75 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
 not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Skin Corr. 1C | Skin corrosion, category 1C |
| Skin Corr. 1 | Skin corrosion, category 1 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

SECTION 16. Other information ... / >>

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health



Druckfarben Hellas S.A.

BODENGUARD S-100 (Comp.-B)

Revision nr.1
Dated 09/01/2026
First compilation
Printed on 12/01/2026
Page n. 13 / 13

EN

and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382987005**
Product name: **BODENGUARD S-100 RAL 7005 (Comp.-A)**
Chemical name and synonym: **Professional Use only**

UFI: **3583-G0C1-Q00E-2NQN**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**

e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|---|
| Flammable liquid, category 3 | H226 | Flammable liquid and vapour. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity - repeated exposure, category 1 | H372 | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains:

Cristobalite (STOT RE-1)
 Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene
 2-Methylpropan-1-ol
 Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)
 Reaction mass of: Bis(1,2,2,6,6- pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6 pentametyl-4-piperidyl Sebacate
 4-morpholinecarbaldehyde

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|---|------------------|---|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | | |
| INDEX 603-074-00-8 | 30 \leq x < 50 | Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317 |
| EC 500-033-5 | | Skin Irrit. 2 H315: \geq 5%, Eye Irrit. 2 H319: \geq 5% |
| CAS 25068-38-6 | | |
| REACH Reg. Polymer | | |
| Cristobalite (STOT RE-1) | | |
| INDEX | 10 \leq x < 30 | STOT RE 1 H372 |
| EC 238-455-4 | | |
| CAS 14464-46-1 | | |
| TITANIUM DIOXIDE | | |
| INDEX | 9 \leq x < 30 | |
| EC 236-675-5 | | |
| CAS 13463-67-7 | | |
| REACH Reg. 01-2119489379-17-0000 | | 01-2119489379-17-0197 01-2119489379-17 |

SECTION 3. Composition/information on ingredients ... / >>

Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene

INDEX $10 \leq x < 20$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412
ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l

EC 905-562-9

CAS

REACH Reg. 01-2119555267-33

Reaction mass of ethylbenzene and xylene

INDEX $5 \leq x < 9$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 905-588-0

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

2-Methylpropan-1-ol

INDEX 603-108-00-1 $3 \leq x < 5$

Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336

EC 201-148-0

CAS 78-83-1

REACH Reg. 01-2119484609-23-0006 01-2119484609-23-xxxx

Solvent naphtha (petroleum), light aromatic

INDEX 649-356-00-4 $1 \leq x < 2,5$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 265-199-0

CAS 64742-95-6

REACH Reg. 01-2119455851-35

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

INDEX $0,5 \leq x < 1$

Repr. 2 H361f, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 915-687-0

CAS 1065336-91-5

REACH Reg. 01-2119491304-40-0000 01-2119491304-40-0002

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32-xxxx 01-2119484661-33-xxxx

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

4-morpholinecarbaldehyde

INDEX $0 < x < 0,5$

Skin Sens. 1B H317

EC 224-518-3

CAS 4394-85-8

REACH Reg. 01-2119987993-12

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$

Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412
LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4

CAS 100-41-4

SECTION 3. Composition/information on ingredients ... / >>

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$
EC 238-878-4
CAS 14808-60-7

Substance with a community workplace exposure limit.

Toluene

INDEX $0 < x < 0,5$
EC 203-625-9
CAS 108-88-3
REACH Reg. 01-2119471310-51

Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| ALB | Shqipëria | VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES "PËR MBROJTJEN E SIGURISË DHE SHËNDETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË" |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe |



SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

4-morpholinecarbaldehyde

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,5 | mg/l |
| Normal value in marine water | 0,05 | mg/l |
| Normal value for fresh water sediment | 1,85 | mg/kg |
| Normal value for marine water sediment | 0,0764 | mg/kg |
| Normal value for water, intermittent release | 5 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | VND | 29 | | | VND | 98 |
| | | | | mg/m3 | | | | mg/m3 |
| Skin | | | VND | 8 | | | 0,293 | VND |
| | | | | mg/kg/d | | | mg/cm2 | |

Cristobalite (STOT RE-1)

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 3,6 | | | | |
| | | | | mg/kg/d | | | | |
| Inhalation | | | VND | 0,08 | | | VND | 0,33 |
| | | | | mg/m3 | | | | mg/m3 |

SECTION 8. Exposure controls/personal protection ... / >>

Xylene

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|---------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Quartz (Crystalline Silica)

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| VLEP | FRA | 0,1 | | | | RESP |
| VLEP | ITA | 0,1 | | | | RESP |
| NDS/NDSch | POL | 0,1 | | | | RESP |
| TLV | ROU | 0,1 | | | | RESP |
| OEL | EU | 0,1 | | | | RESP |
| ACGIH | | 0,025 | | | | RESP |

Solvent naphtha (petroleum), light aromatic

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | GRC | 100 | | | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 11 mg/kg/d | | | | |
| Inhalation | | | VND | 32 mg/m3 | | | VND | 150 mg/m3 |
| Skin | | | VND | 11 mg/kg/d | | | VND | 25 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

| Toluene | | | | | | |
|-----------------------|---------|--------|--------|------------|---------|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 192 | 50 | 384 | 100 | SKIN |
| TLV | CZE | 192 | 50,112 | 384 | 100,224 | SKIN |
| AGW | DEU | 190 | 50 | 760 | 200 | SKIN |
| MAK | DEU | 190 | 50 | 380 | 100 | SKIN |
| VLEP | FRA | 76,8 | 20 | 384 | 100 | SKIN |
| TLV | GRC | 192 | 50 | 384 | 100 | |
| VLEP | ITA | 192 | 50 | | | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 192 | 50 | 384 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 192 | 50 | 384 | 100 | SKIN |
| WEL | GBR | 191 | 50 | 384 | 100 | SKIN |
| OEL | EU | 192 | 50 | 384 | 100 | SKIN |
| ACGIH | | | 20 | | | |

| Xylene (mixture of isomers) | | | | | | |
|-----------------------------|---------|--------|-----|------------|-----|------------------------|
| Threshold Limit Value | | | | | | |
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 200 | | 400 | | |
| MAK | DEU | | 100 | | 200 | |
| VLEP | FRA | 221 | 50 | 442 | 100 | |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| NDS/NDSch | POL | 100 | | 350 | | |
| ESD | TUR | 221 | 50 | 442 | 100 | |
| WEL | GBR | | 50 | | 100 | |
| OEL | EU | 221 | 50 | 442 | 100 | |
| ACGIH | | | 100 | | 150 | |

Predicted no-effect concentration - PNEC

| | | |
|--|-------|-------|
| Normal value in fresh water | 0,327 | mg/l |
| Normal value in marine water | 0,327 | mg/l |
| Normal value for fresh water sediment | 12,46 | mg/kg |
| Normal value for marine water sediment | 12,46 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,6 mg/kg/d | | | | |
| Inhalation | 174 mg/m3 | 174 mg/m3 | VND | 14,8 mg/m3 | 289 mg/m3 | 289 mg/m3 | VND | 77 mg/m3 |
| Skin | | | VND | 108 mg/kg/d | | | VND | 180 mg/kg/d |

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,635 | mg/l |
| Normal value in marine water | 0,0635 | ml/l |
| Normal value for fresh water sediment | 3,29 | mg/kg |
| Normal value for marine water sediment | 0,329 | mg/kg |
| Normal value for water, intermittent release | 6,35 | mg/l |
| Normal value of STP microorganisms | 100 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 1,67 mg/kg | | | | |
| Inhalation | | | VND | 33 mg/m3 | 553,5 mg/m3 | VND | VND | 275 mg/m3 |
| Skin | | | VND | 54,8 mg/kg | | | VND | 153,5 mg/kg |

TITANIUM DIOXIDE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 10 | | | | RESP |
| MAK | DEU | 0,3 | | 2,4 | | RESP Hinweis |
| VLEP | FRA | 10 | | | | |
| TLV | GRC | | 10 | | | |
| NDS/NDSch | POL | 10 | | | | INHAL |
| TLV | ROU | 10 | | 15 | | |
| ПДК | RUS | 10 | | | | a, φ |
| WEL | GBR | 10 | | | | INHAL |
| WEL | GBR | 4 | | | | RESP |
| ACGIH | | 0,2 | | | | RESP |

SECTION 8. Exposure controls/personal protection ... / >>

ETHYLBENZENE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|--------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | ALB | 442 | 100 | 884 | 200 | SKIN |
| TLV | BGR | 435 | | 545 | | SKIN |
| TLV | CZE | 200 | 45,33 | 500 | 113,32 | SKIN |
| AGW | DEU | 88 | 20 | 176 | 40 | SKIN |
| MAK | DEU | 88 | 20 | 176 | 40 | SKIN |
| VLEP | FRA | 88,4 | 20 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 545 | 125 | |
| VLEP | ITA | 442 | 100 | 884 | 200 | SKIN |
| NDS/NDSch | POL | 200 | | 400 | | SKIN |
| TLV | ROU | 442 | 100 | 884 | 200 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 442 | 100 | 884 | 200 | SKIN |
| WEL | GBR | 441 | 100 | 552 | 125 | SKIN |
| OEL | EU | 442 | 100 | 884 | 200 | SKIN |
| ACGIH | | 87 | 20 | | | |

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 275 | 50 | 550 | 100 | SKIN |
| TLV | CZE | 270 | 49,14 | 550 | 100,1 | SKIN |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| TLV | GRC | 275 | 50 | 550 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| NDS/NDSch | POL | 260 | | 520 | | SKIN |
| TLV | ROU | 275 | 50 | 550 | 100 | SKIN |
| ПДК | RUS | | | 10 | | n |
| ESD | TUR | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard

; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

SECTION 8. Exposure controls/personal protection ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|------------------------------|---|
| Appearance | liquid | Temperature: 25 °C |
| Colour | dark grey | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | not available | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 23 ≤ T ≤ 60 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 4630-7770 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 6400-10400 mPa.s | Temperature: 25 °C Method: Spindle 5 mm @ 20 rpm Temperature: 25 °C |
| Solubility | not available | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 1,34-1,38 g/cm ³ | Method: ISO 2811 Temperature: 25 °C |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |

Supplementary information for nanoforms

C.I. Pigment Blue 15:3

Denomination: Quinacridone Violet

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 86,05 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Toluene

Avoid exposure to: light.

n-Butyl Acetate

Stable in normal conditions of use and storage.

SECTION 10. Stability and reactivity ... / >>

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Toluene

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric acid and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Reaction mass of: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) Sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

Avoid contact with: strong oxidising agents, strong bases, strong acids.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

SECTION 11. Toxicological information ... / >>

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesi). Is irritating for skin, conjunctiva and respiratory tract.

Toluene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

Toluene

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

| | |
|--|---|
| ATE (Inhalation - mists / powders) of the mixture: | > 5 mg/l |
| ATE (Inhalation - vapours) of the mixture: | > 20 mg/l |
| ATE (Oral) of the mixture: | Not classified (no significant component) |
| ATE (Dermal) of the mixture: | >2000 mg/kg |

SECTION 11. Toxicological information ... / >>

| | |
|---|---|
| TITANIUM DIOXIDE | |
| LD50 (Oral): | > 10000 mg/kg Rat |
| Reaction mass of Ethylbenzene (6-26%) and m-Xylene and p-Xylene | |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Inhalation mists/powders): | 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Inhalation vapours): | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| Reaction mass of ethylbenzene and xylene | |
| LD50 (Dermal): | 12126 mg/kg Rabbit |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 27,124 mg/l/4h Rat |
| ATE (Inhalation vapours): | 11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| n-Butyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 13100 mg/kg Rat |
| LC50 (Inhalation vapours): | > 21 mg/l Rat |
| Xylene (mixture of isomers) | |
| LD50 (Dermal): | > 1700 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 5000 ppm/4h Rat |
| 4-morpholinecarbaldehyde | |
| LD50 (Dermal): | > 18400 mg/kg Rabbit |
| LD50 (Oral): | > 7360 mg/kg Rat |
| 2-Methoxy-1-Methylethyl Acetate | |
| LD50 (Dermal): | > 5000 mg/kg Rat |
| LD50 (Oral): | 8530 mg/kg Rat |
| ETHYLBENZENE | |
| LD50 (Dermal): | 15354 mg/kg Rabbit |
| LD50 (Oral): | 3500 mg/kg Rat |
| LC50 (Inhalation vapours): | 17,2 mg/l/4h Rat |
| Toluene | |
| LD50 (Dermal): | 12124 mg/kg Rabbit |
| LD50 (Oral): | 5580 mg/kg Rat |
| LC50 (Inhalation vapours): | 28,1 mg/l/4h Rat |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin



SECTION 11. Toxicological information ... / >>

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

Toluene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Reaction mass of ethylbenzene and xylene

| | |
|-----------------------------------|------------------------------|
| LC50 - for Fish | 18 mg/l/96h Fresh Water Fish |
| EC50 - for Algae / Aquatic Plants | 1,3 mg/l/72h Algae |

Xylene (mixture of isomers)

| | |
|-----------------|-------------------------------|
| LC50 - for Fish | > 100 mg/l/96h Microorganisms |
|-----------------|-------------------------------|

4-morpholinecarbaldehyde

| | |
|-----------------------------------|---|
| LC50 - for Fish | > 500 mg/l/96h Leuciscus idus (Golden orfe) |
| EC50 - for Crustacea | > 500 mg/l/48h Daphnia magna (Water flea) |
| EC50 - for Algae / Aquatic Plants | 23880 mg/l/72h Scenedesmus subspicatus |

12.2. Persistence and degradability

Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100)

| | |
|---------------------|----------------|
| Solubility in water | 0,1 - 100 mg/l |
|---------------------|----------------|

NOT rapidly degradable

SECTION 12. Ecological information ... / >>

| | |
|--|-------------------|
| TITANIUM DIOXIDE | |
| Solubility in water | < 0,001 mg/l |
| Degradability: information not available | |
| 2-Methylpropan-1-ol | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| Xylene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |
| n-Butyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| Xylene (mixture of isomers) | |
| Rapidly degradable | |
| 4-morpholinecarbaldehyde | |
| Rapidly degradable | |
| 2-Methoxy-1-Methylethyl Acetate | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |
| ETHYLBENZENE | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |
| Toluene | |
| Solubility in water | 100 - 1000 mg/l |
| Rapidly degradable | |

12.3. Bioaccumulative potential

| | |
|--|---------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: n-octanol/water | > 2,918 |
| BCF | 31 |
| 2-Methylpropan-1-ol | |
| Partition coefficient: n-octanol/water | 1 |
| Xylene | |
| Partition coefficient: n-octanol/water | 3,12 |
| BCF | 25,9 |
| n-Butyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| 2-Methoxy-1-Methylethyl Acetate | |
| Partition coefficient: n-octanol/water | 1,2 |
| ETHYLBENZENE | |
| Partition coefficient: n-octanol/water | 3,6 |
| Toluene | |
| Partition coefficient: n-octanol/water | 2,73 |
| BCF | 90 |

12.4. Mobility in soil

| | |
|--|------|
| Reaction Product: BISPHENOL A-(Epichlorhydrin); EPOXY RESIN (number average molecular weight 700-1100) | |
| Partition coefficient: soil/water | 2,65 |

SECTION 12. Ecological information ... / >>

| | |
|--|------|
| 2-Methylpropan-1-ol Partition coefficient: soil/water | 0,31 |
| Solvent naphtha (petroleum), light aromatic Partition coefficient: soil/water | 1,78 |
| Xylene Partition coefficient: soil/water | 2,73 |

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
IMDG: RESIN SOLUTION
IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

| | | | |
|------------|----------------------|--------------------------|--------------------------------|
| ADR / RID: | HIN - Kemler: 30 | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| | Special provision: - | | |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: | Maximum quantity: 220 L | Packaging instructions: 366 |
| | Passengers: | Maximum quantity: 60 L | Packaging instructions: 355 |
| | Special provision: | A3 | |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 48

Toluene

REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|---------------------|------------------------------|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |

SECTION 16. Other information ... / >>

| | |
|--------------------------|--|
| Repr. 2 | Reproductive toxicity, category 2 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| STOT RE 1 | Specific target organ toxicity - repeated exposure, category 1 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1A | Skin sensitization, category 1A |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H361d | Suspected of damaging the unborn child. |
| H361f | Suspected of damaging fertility. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile

SECTION 16. Other information ... / >>

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK382982111.**
 Product name: **BODENGUARD S-100 (Comp.-B)**
 Chemical name and synonym: **Professional use only**
 UFI: **D973-E0F2-N00G-F7W0**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2-Component, solvent-based, epoxy coating**

1.3. Details of the supplier of the safety data sheet

Name: **Druckfarben Hellas S.A.**
 Full address: **MEGARIDOS AVENUE**
 District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
 Tel.: **+30 210 5519500**
 Fax: **+30 210 5519501**
 e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Flammable liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Aspiration hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Specific target organ toxicity - repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, category 3 | H336 | May cause drowsiness or dizziness. |
| Hazardous to the aquatic environment, chronic toxicity, category 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER or a doctor
P370+P378 In case of fire: use alcohol resistant foam to extinguish.
P102 Keep out of reach of children.
P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.

Contains: Xylene
 2-Methylpropan-1-ol
 Triethylenetetramine
 Ethylbenzene

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|--|---|---|
| Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine | | |
| <i>INDEX</i> | 50 ≤ x < 100 | Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| <i>EC</i> | 500-191-5 | |
| <i>CAS</i> | 68082-29-1 | |
| 2-Methylpropan-1-ol | | |
| <i>INDEX</i> | 20 ≤ x < 30 | Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336 |
| <i>EC</i> | 201-148-0 | |
| <i>CAS</i> | 78-83-1 | |
| <i>REACH Reg.</i> | 01-2119484609-23-0006 01-2119484609-23-xxxx | |
| Xylene | | |
| <i>INDEX</i> | 10 ≤ x < 20 | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C |
| <i>EC</i> | 215-535-7 | LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h |
| <i>CAS</i> | 1330-20-7 | |
| <i>REACH Reg.</i> | 01-2119488216-32-xxxx 01-2119484661-33-xxxx | |

SECTION 3. Composition/information on ingredients ... / >>

Ethylbenzene

INDEX 601-023-00-4 $5 \leq x < 9$

EC 202-849-4
CAS 100-41-4
REACH Reg. 01-2119489370-35

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373,
Aquatic Chronic 3 H412
LC50 Inhalation vapours: 11 mg/l/4h

Triethylenetetramine

INDEX 612-059-00-5 $1 \leq x < 3$

EC 292-588-2
CAS 90640-67-8
REACH Reg. 01-2119487919-13

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318,
Skin Sens. 1B H317, Aquatic Chronic 3 H412
ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

SECTION 5. Firefighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

| | | |
|-----|-----------------|--|
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.28 от 2 Април 2024г.) |
| CZE | Česká Republika | NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung |

SECTION 8. Exposure controls/personal protection ... / >>

| | | |
|-----|----------------|--|
| FRA | France | gesundheits-schädlicher Arbeitsstoffe Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"» |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| ROU | România | HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca |
| RUS | Россия | ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" |
| TUR | Türkiye | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345. |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| EU | OEL EU | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. |
| | ACGIH | ACGIH 2025 |

Xylene

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 221 | 50 | 442 | 100 | SKIN |
| TLV | CZE | 200 | 45,4 | 400 | 90,8 | SKIN |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| TLV | GRC | 435 | 100 | 650 | 150 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 221 | 50 | 442 | 100 | SKIN |
| ПДК | RUS | 50 | | 150 | | n |
| ESD | TUR | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | SKIN |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| ACGIH | | 434 | 100 | 651 | 150 | |

2-Methylpropan-1-ol

| Threshold Limit Value | | | | | | |
|-----------------------|---------|--------|------|------------|---------|------------------------|
| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 300 | 97,5 | 600 | 195 | |
| AGW | DEU | 310 | 100 | 310 (C) | 100 (C) | |
| MAK | DEU | 310 | 100 | 310 | 100 | |
| VLEP | FRA | 150 | 50 | | | |
| TLV | GRC | 300 | 100 | 300 | 100 | |
| NDS/NDSch | POL | 100 | | 200 | | SKIN |
| TLV | ROU | 100 | 33 | 200 | 66 | |
| ПДК | RUS | | | 10 | | n |
| WEL | GBR | 154 | 50 | 231 | 75 | |
| ACGIH | | 152 | 50 | | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

SECTION 8. Exposure controls/personal protection ... / >>

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--|-----------------------------|--|
| Appearance | liquid | Temperature: 25 °C |
| Colour | brown | Temperature: 25 °C |
| Odour | characteristic of solvent | |
| Melting point / freezing point | not available | |
| Initial boiling point | > 35 °C | |
| Flammability | not available | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point | 22,85 ≤ T < 23 °C | |
| Auto-ignition temperature | not available | |
| Decomposition temperature | not available | |
| pH | not available | Reason for missing data: substance/mixture is non-soluble (in water) |
| Kinematic viscosity | 300-540 mm ² /s | Method: Converting Formula from Dynamic Viscosity & Density |
| Dynamic viscosity | 280-480 mPas | Temperature: 25 °C |
| Solubility | not available | Temperature: 20 °C |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 0,89-0,93 g/cm ³ | Method: ISO 2811 |
| Relative vapour density | not available | Temperature: 25 °C |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

SECTION 9. Physical and chemical properties ... / >>

Total solids (250°C / 482°F) 53,90 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l

ATE (Oral) of the mixture: >2000 mg/kg

SECTION 11. Toxicological information ... / >>

| | |
|------------------------------|---|
| ATE (Dermal) of the mixture: | >2000 mg/kg |
| | |
| 2-Methylpropan-1-ol | |
| LD50 (Dermal): | 2460 mg/kg Rabbit |
| LD50 (Oral): | 2460 mg/kg Rat |
| LC50 (Inhalation vapours): | 19,2 mg/l/4h Rat |
| | |
| Xylene | |
| LD50 (Dermal): | 1100 mg/kg Rabbit |
| LD50 (Oral): | 3523 mg/kg Rat |
| LC50 (Inhalation vapours): | 11 mg/l/4h Rat |
| | |
| Ethylbenzene | |
| LD50 (Dermal): | 15400 mg/kg |
| LD50 (Oral): | 3500 mg/kg |
| LC50 (Inhalation vapours): | 11 mg/l/4h |
| | |
| Triethylenetetramine | |
| ATE (Oral): | 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |
| ATE (Dermal): | 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) |

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

| | |
|---------------------------------|--|
| Ethylbenzene LC50 - for Fish | 5,1 mg/l/96h Atlantic silverside (Menidia menidia) |
|---------------------------------|--|

12.2. Persistence and degradability

| | |
|--|-------------------|
| 2-Methylpropan-1-ol Solubility in water Rapidly degradable | 1000 - 10000 mg/l |
|--|-------------------|

| | |
|---|-----------------|
| Xylene Solubility in water Rapidly degradable | 100 - 1000 mg/l |
|---|-----------------|

12.3. Bioaccumulative potential

| | |
|---|---|
| 2-Methylpropan-1-ol Partition coefficient: n-octanol/water | 1 |
|---|---|

| | |
|---|--------------|
| Xylene Partition coefficient: n-octanol/water BCF | 3,12 25,9 |
|---|--------------|

12.4. Mobility in soil

| | |
|--|------|
| 2-Methylpropan-1-ol Partition coefficient: soil/water | 0,31 |
|--|------|

| | |
|---|------|
| Xylene Partition coefficient: soil/water | 2,73 |
|---|------|

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
 IMDG: RESIN SOLUTION
 IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
 IMDG: not marine pollutant
 IATA: NO

14.6. Special precautions for user

| | | | |
|------------|---|---|--|
| ADR / RID: | HIN - Kemler: 33 Special provision: 640D | Limited Quantities: 5 lt | Tunnel restriction code: (D/E) |
| IMDG: | EMS: F-E, S-E | Limited Quantities: 5 lt | |
| IATA: | Cargo: Passengers: Special provision: | Maximum quantity: 60 L Maximum quantity: 5 L A3 | Packaging instructions: 364 Packaging instructions: 353 |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

| | |
|----------------------------|--------|
| <u>Product</u> | |
| Point | 3 - 40 |
| <u>Contained substance</u> | |
| Point | 75 |

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
 not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Skin Corr. 1C | Skin corrosion, category 1C |
| Skin Corr. 1 | Skin corrosion, category 1 |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Skin Sens. 1B | Skin sensitization, category 1B |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

SECTION 16. Other information ... / >>

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health



Druckfarben Hellas S.A.

BODENGUARD S-100 (Comp.-B)

Revision nr.1
Dated 09/01/2026
First compilation
Printed on 12/01/2026
Page n. 13 / 13

EN

and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.