

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32250P000.**
 Product name: **UNIVERSE RED SEAL GLOSS Base 1**
 UFI: **4E52-K031-A00X-3GQ9**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
 Full address: **MEGARIDOS AVENUE**
 District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
 Tel.: **+30 210 5519500**
 Fax: **+30 210 5519501**
 e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Aliphatic polyether esterified with maleic acid
Maleic anhydride
XYLENE (reaction mass of ethylbenzene and xylene)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	$20 \leq x < 30$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
TITANIUM DIOXIDE		
INDEX		$9 \leq x < 30$
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Xylene (ortho-)		
INDEX	601-022-00-9	$1 \leq x < 5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	$1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	

SECTION 3. Composition/information on ingredients ... / >>

XYLENE (reaction mass of ethylbenzene and xylene)

INDEX $1 \leq x < 5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 905-588-0

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

Calcium Neodecanoate

INDEX $1 \leq x < 3$ Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 248-375-1

CAS 27253-33-4

REACH Reg. 01-2120769660-48-XXXX

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX $1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5

CAS 64742-48-9

REACH Reg. 01-2119463258-33-0000

Hydrocarbons, C9, aromatics

INDEX $1 \leq x < 2,5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 918-668-5

CAS 64742-95-6

REACH Reg. 01-2119455851-35-0001 01-2119486773-24 01-2119455851-35

Aliphatic polyether esterified with maleic acid

INDEX $1 \leq x < 5$ Skin Sens. 1 H317

EC

CAS 709014-50-6

Ethylene Glycol Monobutyl Ether

INDEX $603-014-00-0$ $0,5 \leq x < 1$ Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 203-905-0

CAS 111-76-2

REACH Reg. 01-2119475108-36

n-Butyl Acetate

INDEX $607-025-00-1$ $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene

INDEX $601-022-00-9$ $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

Xylene (mixture of isomers)

INDEX $601-022-00-9$ $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C

LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

2-Methoxy-1-Methylethyl Acetate

INDEX $607-195-00-7$ $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

ETHYLBENZENE

INDEX $601-023-00-4$ $0 < x < 0,5$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4

CAS 100-41-4

SECTION 3. Composition/information on ingredients ... / >>

Maleic anhydride

INDEX 607-096-00-9 0,001 ≤ x < 0,1

EC 203-571-6
CAS 108-31-6
REACH Reg. 01-2119472428-31

Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071
Skin Sens. 1A H317: ≥ 0,001%
ATE Oral: 500 mg/kg

Quartz (Crystalline Silica)

INDEX 0 < x < 0,5

EC 238-878-4
CAS 14808-60-7

Substance with a community workplace exposure limit.

2,6-di-tert-Butyl-p-cresol

INDEX 0 < x < 0,25

EC 204-881-4
CAS 128-37-0
REACH Reg. 01-2119565113-46

Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

2-(2-BUTOXYETHOXY)ETHANOL

INDEX 603-096-00-8 0 < x < 0,5

EC 203-961-6
CAS 112-34-5

Eye Irrit. 2 H319

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT



SECTION 5. Firefighting measures ... / >>

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	10				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value in marine water	0,00002	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
ПДК	RUS	50		150		n
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

SECTION 8. Exposure controls/personal protection ... / >>

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Ethylene Glycol Monobutyl Ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	100						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU		100		200			
TLV	GRC	435	100	650	150			
ESD	TUR	221	50	442	100			
WEL	GBR		50		100			
OEL	EU	221	50	442	100			
TLV-ACGIH			100		150			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
ПДК	RUS	10				a, Φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

SECTION 8. Exposure controls/personal protection ... / >>

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

SECTION 8. Exposure controls/personal protection ... / >>

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

SECTION 10. Stability and reactivity ... / >>

Stable in normal conditions of use and storage.
With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.
With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispest). Is irritating for skin, conjunctiva and respiratory tract.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

SECTION 11. Toxicological information ... / >>

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: >2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal): 12126 mg/kg Rabbit
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 27,124 mg/l/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal): 1100 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral): 1200 mg/kg Guinea pig
LC50 (Inhalation vapours): 2,2 mg/l/4h Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (ortho-)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate

LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9, aromatics

LD50 (Dermal): > 3400 mg/kg Rabbit
LD50 (Oral): > 6800 mg/kg Rat
LC50 (Inhalation vapours): > 10,2 mg/l/4h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (mixture of isomers)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

SECTION 11. Toxicological information ... / >>

TITANIUM DIOXIDE	
LD50 (Oral):	> 10000 mg/kg Rat
2-(2-BUTOXYETHOXY)ETHANOL	
LD50 (Dermal):	2700 mg/kg Rabbit
LD50 (Oral):	3384 mg/kg Rat
ETHYLBENZENE	
LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat
2-Methoxy-1-Methylethyl Acetate	
LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
 The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
 Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.



SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9, aromatics

LC50 - for Fish > 1 mg/l/96h
EC50 - for Crustacea > 1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol

Degradability: information not available

Xylene

Solubility in water 100 - 1000 mg/l
Rapidly degradable

Ethylene Glycol Monobutyl Ether

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

Xylene (ortho-)

Rapidly degradable

SECTION 12. Ecological information ... / >>

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9, aromatics
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (mixture of isomers)
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

ETHYLBENZENE
Partition coefficient: n-octanol/water 3,6

2-Methoxy-1-Methylethyl Acetate
Partition coefficient: n-octanol/water 1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 12. Ecological information ... / >>

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 lt

Special provision: 163, 367, 650

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E Limited Quantities: 5 lt

IATA: Cargo: Maximum quantity: 220 L

Packaging instructions: 366

Passengers: Maximum quantity: 60 L

Packaging instructions: 355

Special provision: A3, A72, A192

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.

SECTION 16. Other information ... / >>

H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)



SECTION 16. Other information ... / >>

16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32250D000.**
 Product name: **UNIVERSE RED SEAL GLOSS Base 2**
 UFI: **HG52-20SE-N00E-SU9C**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
 Full address: **MEGARIDOS AVENUE**
 District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
 Tel.: **+30 210 5519500**
 Fax: **+30 210 5519501**
 e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Aliphatic polyether esterified with maleic acid
Maleic anhydride
XYLENE (reaction mass of ethylbenzene and xylene)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	20 \leq x < 30
Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P		
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
TITANIUM DIOXIDE		
INDEX		5 \leq x < 9
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Xylene (ortho-)		
INDEX	601-022-00-9	5 \leq x < 9
Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C		
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l		
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX		1 \leq x < 5
Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412		
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l		
EC	905-588-0	
CAS		

SECTION 3. Composition/information on ingredients ... / >>

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX 649-327-00-6 $1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5

CAS 64742-48-9

REACH Reg. 01-2119463258-33

Hydrocarbons, C9, aromatics

INDEX $1 \leq x < 2,5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 918-668-5

CAS 64742-95-6

REACH Reg. 01-2119455851-35-0001 01-2119486773-24 01-2119455851-35

Calcium Neodecanoate

INDEX $1 \leq x < 3$ Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 248-375-1

CAS 27253-33-4

REACH Reg. 01-2120769660-48-XXXX

Aliphatic polyether esterified with maleic acid

INDEX $1 \leq x < 5$ Skin Sens. 1 H317

EC

CAS 709014-50-6

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX $1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5

CAS 64742-48-9

REACH Reg. 01-2119463258-33-0000

Modified Poly-Acrylate

INDEX $1 \leq x < 2,5$ Aquatic Chronic 2 H411

EC

CAS

Ethylene Glycol Monobutyl Ether

INDEX 603-014-00-0 $0,5 \leq x < 1$ Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0 LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

CAS 111-76-2

REACH Reg. 01-2119475108-36

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4

CAS 100-41-4

Maleic anhydride

INDEX 607-096-00-9 $0,001 \leq x < 0,1$ Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071

Skin Sens. 1A H317: $\geq 0,001\%$

ATE Oral: 500 mg/kg

EC 203-571-6

CAS 108-31-6

REACH Reg. 01-2119472428-31

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$ Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

SECTION 3. Composition/information on ingredients ... / >>

2,6-di-tert-Butyl-p-cresol		
INDEX	0 < x < 0,25	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	204-881-4	
CAS	128-37-0	
REACH Reg.	01-2119565113-46	
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX	603-096-00-8	0 < x < 0,5
EC	203-961-6	Eye Irrit. 2 H319
CAS	112-34-5	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION



DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL GLOSS Base 2

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 5 / 20

EN

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006

SECTION 8. Exposure controls/personal protection ... / >>

RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EN40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
OEL	EU	10					

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value in marine water	0,00002	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	221	50	442	100	SKIN	
AGW	DEU	440	100	880	200	SKIN	
MAK	DEU	440	100	880	200	SKIN	
TLV	GRC	435	100	650	150		
TLV	ROU	221	50	442	100	SKIN	
ПДК	RUS	50		150			n
ESD	TUR	221	50	442	100	SKIN	
WEL	GBR	220	50	441	100	SKIN	
OEL	EU	221	50	442	100	SKIN	
TLV-ACGIH		434	100	651	150		

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	ROU	0,1				RESP	
OEL	EU	0,1				RESP	
TLV-ACGIH		0,025				RESP	

SECTION 8. Exposure controls/personal protection ... / >>

Ethylene Glycol Monobutyl Ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	100						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	275	50	550	100	SKIN		
AGW	DEU	270	50	270	50			
MAK	DEU	270	50	270	50			
TLV	GRC	275	50	550	100			
TLV	ROU	275	50	550	100	SKIN		
ПДК	RUS			10			n	
ESD	TUR	275	50	550	100	SKIN		
WEL	GBR	274	50	548	100	SKIN		
OEL	EU	275	50	550	100	SKIN		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
ПДК	RUS	10				a, φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic	Chronic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	300 mg/kg/d				
Inhalation				VND	900 mg/m3	VND	1500 mg/m3		
Skin				VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard

; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

SECTION 8. Exposure controls/personal protection ... / >>

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

SECTION 9. Physical and chemical properties ... / >>

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 10. Stability and reactivity ... / >>

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesi). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

SECTION 11. Toxicological information ... / >>

XYLENE (reaction mass of ethylbenzene and xylene)	
LD50 (Dermal):	12126 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,124 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
Xylene	
LD50 (Dermal):	1100 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h Rat
Ethylene Glycol Monobutyl Ether	
LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat
Xylene (ortho-)	
LD50 (Dermal):	> 1700 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	5000 ppm/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
Calcium Neodecanoate	
LD50 (Dermal):	> 3640 mg/kg rat
LD50 (Oral):	2066 mg/kg rat
Hydrocarbons, C9, aromatics	
LD50 (Dermal):	> 3400 mg/kg Rabbit
LD50 (Oral):	> 6800 mg/kg Rat
LC50 (Inhalation vapours):	> 10,2 mg/l/4h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat
n-Butyl Acetate	
LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	13100 mg/kg Rat
LC50 (Inhalation vapours):	> 21 mg/l Rat
TITANIUM DIOXIDE	
LD50 (Oral):	> 10000 mg/kg Rat
2-(2-BUTOXYETHOXY)ETHANOL	
LD50 (Dermal):	2700 mg/kg Rabbit
LD50 (Oral):	3384 mg/kg Rat
ETHYLBENZENE	
LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SECTION 11. Toxicological information ... / >>

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

SECTION 12. Ecological information ... / >>

Hydrocarbons, C9, aromatics	
LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50 - for Fish	> 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 0,1 mg/l
Chronic NOEC for Crustacea	> 0,1 mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50 - for Fish	> 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 0,1 mg/l
Chronic NOEC for Crustacea	> 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol
Degradability: information not available

Xylene
Solubility in water 100 - 1000 mg/l
Rapidly degradable

Ethylene Glycol Monobutyl Ether
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (ortho-)
Rapidly degradable

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9, aromatics
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

SECTION 12. Ecological information ... / >>

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

ETHYLBENZENE
Partition coefficient: n-octanol/water 3,6

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
 IMDG: not marine pollutant
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
 Point 3 - 40

Contained substance
 Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
 not applicable

Substances in Candidate List (Art. 59 REACH)
 On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)
 None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
 None

Substances subject to the Rotterdam Convention:
 None

Substances subject to the Stockholm Convention:
 None

Healthcare controls

SECTION 15. Regulatory information ... / >>

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods

SECTION 16. Other information ... / >>

- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.



DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL GLOSS Base 2

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 20 / 20

EN

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32250A000.**
 Product name: **UNIVERSE RED SEAL GLOSS Base 3**
 UFI: **FK52-K0FT-X00X-E5VE**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
 Full address: **MEGARIDOS AVENUE**
 District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
 Tel.: **+30 210 5519500**
 Fax: **+30 210 5519501**
 e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Aliphatic polyether esterified with maleic acid
Maleic anhydride

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	$30 \leq x < 50$
Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P		
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
Xylene (ortho-)		
INDEX	601-022-00-9	$5 \leq x < 9$
Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C		
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l		
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	$5 \leq x < 9$
Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P		
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX		$1 \leq x < 5$
Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412		
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l		
EC	905-588-0	
CAS		

SECTION 3. Composition/information on ingredients ... / >>

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

Calcium Neodecanoate

INDEX $1 \leq x < 3$ Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 248-375-1

CAS 27253-33-4

REACH Reg. 01-2120769660-48-XXXX

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX $1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5

CAS 64742-48-9

REACH Reg. 01-2119463258-33-0000

Aliphatic polyether esterified with maleic acid

INDEX $1 \leq x < 5$ Skin Sens. 1 H317

EC

CAS 709014-50-6

Hydrocarbons, C9, aromatics

INDEX $1 \leq x < 2,5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 918-668-5

CAS 64742-95-6

REACH Reg. 01-2119455851-35-0001 01-2119486773-24 01-2119455851-35

Ethylene Glycol Monobutyl Ether

INDEX 603-014-00-0 $0,5 \leq x < 1$ Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0

LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

CAS 111-76-2

REACH Reg. 01-2119475108-36

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

Acetone

INDEX 606-001-00-8 $0 < x < 0,5$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 200-662-2

CAS 67-64-1

REACH Reg. 01-2119471330-49-0003

Maleic anhydride

INDEX 607-096-00-9 $0,001 \leq x < 0,1$ Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071

EC 203-571-6

CAS 108-31-6

REACH Reg. 01-2119472428-31

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$ Substance with a community workplace exposure limit.

EC 238-878-4

CAS 14808-60-7

SECTION 3. Composition/information on ingredients ... / >>

2,6-di-tert-Butyl-p-cresol		
INDEX	0 < x < 0,25	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	204-881-4	
CAS	128-37-0	
REACH Reg.	01-2119565113-46	
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX	603-096-00-8	0 < x < 0,5
EC	203-961-6	Eye Irrit. 2 H319
CAS	112-34-5	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION



DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL GLOSS Base 3

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 5 / 21

EN

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006

SECTION 8. Exposure controls/personal protection ... / >>

RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EN40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
OEL	EU	10					

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value in marine water	0,00002	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	221	50	442	100	SKIN	
AGW	DEU	440	100	880	200	SKIN	
MAK	DEU	440	100	880	200	SKIN	
TLV	GRC	435	100	650	150		
TLV	ROU	221	50	442	100	SKIN	
ПДК	RUS	50		150			n
ESD	TUR	221	50	442	100	SKIN	
WEL	GBR	220	50	441	100	SKIN	
OEL	EU	221	50	442	100	SKIN	
TLV-ACGIH		434	100	651	150		

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	ROU	0,1				RESP	
OEL	EU	0,1				RESP	
TLV-ACGIH		0,025				RESP	

SECTION 8. Exposure controls/personal protection ... / >>
Acetone
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	BGR	600		1400		
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
TLV	GRC	1780		3560		
TLV	ROU	1210	500			
ПДК	RUS	200		800		n
ESD	TUR	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

Ethylene Glycol Monobutyl Ether
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m ³	VND	1500 mg/m ³		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC		100			

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC		1200			

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d



DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL GLOSS Base 3

Revision nr.1
 Dated 04/12/2024
 First compilation
 Printed on 04/12/2024
 Page n. 9 / 21

EN

SECTION 8. Exposure controls/personal protection ... / >>

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3		VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin				VND	108 mg/kg/d			VND	180 mg/kg/d

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,67 mg/kg				
Inhalation				VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin				VND	54,8 mg/kg			VND	153,5 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard

; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

SECTION 8. Exposure controls/personal protection ... / >>

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Acetone

Decomposes under the effect of heat.

Ethylene Glycol Monobutyl Ether

SECTION 10. Stability and reactivity ... / >>

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Acetone

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxy monosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Acetone

Avoid exposure to: sources of heat, naked flames.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

Acetone

Incompatible with: acids, oxidising substances.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

SECTION 10. Stability and reactivity ... / >>

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Acetone

May develop: ketenes, irritant substances.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the

SECTION 11. Toxicological information ... / >>

concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: >2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal): 12126 mg/kg Rabbit
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 27,124 mg/l/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal): 1100 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral): 1200 mg/kg Guinea pig
LC50 (Inhalation vapours): 2,2 mg/l/4h Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (ortho-)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate

LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9, aromatics

LD50 (Dermal): > 3400 mg/kg Rabbit
LD50 (Oral): > 6800 mg/kg Rat
LC50 (Inhalation vapours): > 10,2 mg/l/4h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (mixture of isomers)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Dermal): 2700 mg/kg Rabbit
LD50 (Oral): 3384 mg/kg Rat

SECTION 11. Toxicological information ... / >>

2-Methoxy-1-Methylethyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l

SECTION 12. Ecological information ... / >>

Chronic NOEC for Crustacea	> 0,1 mg/l
Xylene (ortho-) LC50 - for Fish	> 100 mg/l/96h Microorganisms
Calcium Neodecanoate EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish	> 100 mg/l/72h 0,199 mg/l
Hydrocarbons, C9, aromatics LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants	> 1 mg/l/96h > 1 mg/l/48h > 1 mg/l/72h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea	> 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms > 100 mg/l/48h > 100 mg/l/72h > 0,1 mg/l > 0,1 mg/l
Xylene (mixture of isomers) LC50 - for Fish	> 100 mg/l/96h Microorganisms
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea	> 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms > 100 mg/l/48h > 100 mg/l/72h > 0,1 mg/l > 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol Degradability: information not available	
Xylene Solubility in water Rapidly degradable	100 - 1000 mg/l
Acetone Rapidly degradable	
Ethylene Glycol Monobutyl Ether Solubility in water Rapidly degradable	1000 - 10000 mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Rapidly degradable	
Xylene (ortho-) Rapidly degradable	
Calcium Neodecanoate Degradability: information not available	
Hydrocarbons, C9, aromatics Rapidly degradable	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Rapidly degradable	
Xylene (mixture of isomers) Rapidly degradable	
n-Butyl Acetate Solubility in water Rapidly degradable	> 10000 mg/l

SECTION 12. Ecological information ... / >>

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Acetone
Partition coefficient: n-octanol/water -0,23
BCF 3

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

2-Methoxy-1-Methylethyl Acetate
Partition coefficient: n-octanol/water 1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

SECTION 15. Regulatory information ... / >>

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

SECTION 16. Other information ... / >>

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
 24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL GLOSS Base 3

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 21 / 21

EN

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK322500001.**
Product name: **UNIVERSE RED SEAL GLOSS White**
UFI: **1A52-20DN-100F-F547**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

SECTION 2. Hazards identification ... / >>

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
XYLENE (reaction mass of ethylbenzene and xylene)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
TITANIUM DIOXIDE		
INDEX	$9 \leq x < 30$	
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	$649-327-00-6$	$10 \leq x < 20$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	$649-327-00-6$	$1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	
Xylene (ortho-)		
INDEX	$601-022-00-9$	$1 \leq x < 5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX	$1 \leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

**SECTION 3. Composition/information on ingredients ... / >>**

EC	905-588-0		ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS			
REACH Reg.	01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29		
Calcium Neodecanoate			
INDEX		1 ≤ x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315
EC	248-375-1		
CAS	27253-33-4		
REACH Reg.	01-2120769660-48-XXXX		
Hydrocarbons, C9, aromatics			
INDEX		1 ≤ x < 2,5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	918-668-5		
CAS	64742-95-6		
REACH Reg.	01-2119455851-35-0001 01-2119486773-24 01-2119455851-35		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
INDEX		1 ≤ x < 5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5		
CAS	64742-48-9		
REACH Reg.	01-2119463258-33-0000		
Ethylene Glycol Monobutyl Ether			
INDEX	603-014-00-0	0,5 ≤ x < 1	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	203-905-0		LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	111-76-2		
REACH Reg.	01-2119475108-36		
n-Butyl Acetate			
INDEX	607-025-00-1	0 < x < 0,5	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC	204-658-1		
CAS	123-86-4		
REACH Reg.	01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29		
Xylene			
INDEX	601-022-00-9	0 < x < 0,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7		LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h
CAS	1330-20-7		
REACH Reg.	01-2119488216-32		
Xylene (mixture of isomers)			
INDEX	601-022-00-9	0 < x < 0,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7		LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	1330-20-7		
REACH Reg.	01-2119488216-32		
Trimethylolpropane (TMP)			
INDEX		0 < x < 0,5	Repr. 2 H361fd
EC	201-074-9		
CAS	77-99-6		
REACH Reg.	01-2119486799-10-0000		
2-Methoxy-1-Methylethyl Acetate			
INDEX	607-195-00-7	0 < x < 0,5	Flam. Liq. 3 H226, STOT SE 3 H336
EC	203-603-9		
CAS	108-65-6		
REACH Reg.	01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001		
ETHYLBENZENE			
INDEX	601-023-00-4	0 < x < 0,5	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412
EC	202-849-4		LC50 Inhalation vapours: 17,2 mg/l/4h
CAS	100-41-4		
Quartz (Crystalline Silica)			
INDEX		0 < x < 0,5	Substance with a community workplace exposure limit.
EC	238-878-4		
CAS	14808-60-7		

SECTION 3. Composition/information on ingredients ... / >>

2,6-di-tert-Butyl-p-cresol		
INDEX	0 < x < 0,25	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	204-881-4	
CAS	128-37-0	
REACH Reg.	01-2119565113-46	
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX	603-096-00-8	0 < x < 0,5
EC	203-961-6	Eye Irrit. 2 H319
CAS	112-34-5	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006

SECTION 8. Exposure controls/personal protection ... / >>

RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EN40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	10						

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value in marine water	0,00002	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	221	50	442	100	SKIN		
AGW	DEU	440	100	880	200	SKIN		
MAK	DEU	440	100	880	200	SKIN		
TLV	GRC	435	100	650	150			
TLV	ROU	221	50	442	100	SKIN		
ПДК	RUS	50		150				n
ESD	TUR	221	50	442	100	SKIN		
WEL	GBR	220	50	441	100	SKIN		
OEL	EU	221	50	442	100	SKIN		
TLV-ACGIH		434	100	651	150			

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	ROU	0,1				RESP		
OEL	EU	0,1				RESP		
TLV-ACGIH		0,025				RESP		

SECTION 8. Exposure controls/personal protection ... / >>

Ethylene Glycol Monobutyl Ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	100						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU		100		200			
TLV	GRC	435	100	650	150			
ESD	TUR	221	50	442	100			
WEL	GBR		50		100			
OEL	EU	221	50	442	100			
TLV-ACGIH			100		150			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
ПДК	RUS	10				a, Φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

SECTION 8. Exposure controls/personal protection ... / >>

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

SECTION 8. Exposure controls/personal protection ... / >>

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

SECTION 10. Stability and reactivity ... / >>

Stable in normal conditions of use and storage.
With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.
With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispes). Is irritating for skin, conjunctiva and respiratory tract.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side

SECTION 11. Toxicological information ... / >>

effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: >2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal): 12126 mg/kg Rabbit
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 27,124 mg/l/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal): 1100 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral): 1200 mg/kg Guinea pig
LC50 (Inhalation vapours): 2,2 mg/l/4h Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (ortho-)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate

LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9, aromatics

LD50 (Dermal): > 3400 mg/kg Rabbit
LD50 (Oral): > 6800 mg/kg Rat
LC50 (Inhalation vapours): > 10,2 mg/l/4h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (mixture of isomers)

LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

SECTION 11. Toxicological information ... / >>

2-(2-BUTOXYETHOXY)ETHANOL
LD50 (Dermal): 2700 mg/kg Rabbit
LD50 (Oral): 3384 mg/kg Rat

ETHYLBENZENE
LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat

2-Methoxy-1-Methylethyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9, aromatics

LC50 - for Fish > 1 mg/l/96h
EC50 - for Crustacea > 1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol

Degradability: information not available

Xylene

Solubility in water 100 - 1000 mg/l
Rapidly degradable

Ethylene Glycol Monobutyl Ether

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

Xylene (ortho-)

Rapidly degradable

SECTION 12. Ecological information ... / >>

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9, aromatics
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (mixture of isomers)
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

ETHYLBENZENE
Partition coefficient: n-octanol/water 3,6

2-Methoxy-1-Methylethyl Acetate
Partition coefficient: n-octanol/water 1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 12. Ecological information ... / >>

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 lt

Special provision: 163, 367, 650

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E Limited Quantities: 5 lt

IATA: Cargo: Maximum quantity: 220 L

Packaging instructions: 366

Passengers: Maximum quantity: 60 L

Packaging instructions: 355

Special provision: A3, A72, A192

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.

SECTION 16. Other information ... / >>

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707



SECTION 16. Other information ... / >>

- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32251P000.**
Product name: **UNIVERSE RED SEAL SATIN Base 1**
UFI: **7R52-K0UM-J00W-RV1J**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

SECTION 2. Hazards identification ... / >>

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains:	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics XYLENE (reaction mass of ethylbenzene and xylene) Hydrocarbons, C9, aromatics
------------------	---

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
TITANIUM DIOXIDE		
<i>INDEX</i>	$9 \leq x < 30$	
<i>EC</i>	236-675-5	
<i>CAS</i>	13463-67-7	
<i>REACH Reg.</i>	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
<i>INDEX</i>	$10 \leq x < 20$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
<i>EC</i>	919-857-5	
<i>CAS</i>	64742-48-9	
<i>REACH Reg.</i>	01-21119463258-33	
Xylene (ortho-)		
<i>INDEX</i>	$1 \leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
<i>EC</i>	202-422-2	
<i>CAS</i>	95-47-6	
<i>REACH Reg.</i>	01-2119488216	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
<i>INDEX</i>	$1 \leq x < 5$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
<i>EC</i>	919-857-5	
<i>CAS</i>	64742-48-9	
<i>REACH Reg.</i>	01-2119463258-33	

SECTION 3. Composition/information on ingredients ... / >>

XYLENE (reaction mass of ethylbenzene and xylene)

INDEX $1 \leq x < 5$ **Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412**
ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 905-588-0

CAS

REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29

Hydrocarbons, C9, aromatics

INDEX $1 \leq x < 2,5$ **Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P**

EC 918-668-5

CAS 64742-95-6

REACH Reg. 01-2119455851-35-0001 01-2119486773-24 01-2119455851-35

Calcium Neodecanoate

INDEX $1 \leq x < 3$ **Eye Dam. 1 H318, Skin Irrit. 2 H315**

EC 248-375-1

CAS 27253-33-4

REACH Reg. 01-2120769660-48-XXXX

Ethylene Glycol Monobutyl Ether

INDEX 603-014-00-0 $0,5 \leq x < 1$ **Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315**
LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 203-905-0

CAS 111-76-2

REACH Reg. 01-2119475108-36

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$ **Flam. Liq. 3 H226, STOT SE 3 H336, EUH066**

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$ **Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C**
LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$ **Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C**
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 215-535-7

CAS 1330-20-7

REACH Reg. 01-2119488216-32

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$ **Flam. Liq. 3 H226, STOT SE 3 H336**

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$ **Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412**
LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4

CAS 100-41-4

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$ **Substance with a community workplace exposure limit.**

EC 238-878-4

CAS 14808-60-7

2,6-di-tert-Butyl-p-cresol

INDEX $0 < x < 0,25$ **Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1**

EC 204-881-4

CAS 128-37-0

REACH Reg. 01-2119565113-46

SECTION 3. Composition/information on ingredients ... / >>

2-(2-BUTOXYETHOXY)ETHANOL

INDEX 603-096-00-8 0 < x < 0,5 Eye Irrit. 2 H319
EC 203-961-6
CAS 112-34-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with



self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)

SECTION 8. Exposure controls/personal protection ... / >>

EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	10						
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,0002	mg/l	
Normal value in marine water						0,00002	mg/l	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	systemic	local	systemic	systemic	local	systemic	systemic
Inhalation						VND		3,5 mg/kg
Skin						VND		0,5 mg/kg bw/d

Xylene

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
ПДК	RUS	50		150		n
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Quartz (Crystalline Silica)

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Ethylene Glycol Monobutyl Ether

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

**SECTION 8. Exposure controls/personal protection ... / >>****Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			

TLV GRC 1200

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			

MAK DEU 100

TLV GRC 435

ESD TUR 221

WEL GBR 50

OEL EU 221

TLV-ACGIH 100

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

Hydrocarbons, C9, aromatics**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			

TLV GRC 100

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3		VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin				VND	108 mg/kg/d			VND	180 mg/kg/d

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,67 mg/kg				
Inhalation				VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin				VND	54,8 mg/kg			VND	153,5 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
ПДК	RUS	10				a, φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH		

SECTION 9. Physical and chemical properties ... / >>

	not available		Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s		Method:Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU		Temperature: 25 °C Method:ASTM D 562-05 Temperature: 25 °C
Solubility	not available		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	0,91-1,23	g/cm ³	Method:ISO 2811 Temperature: 25 °C
Relative vapour density	not available		
Particle characteristics	not applicable		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium,oxidising agents.Formes peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances,strong acids,alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances.May form peroxides with: oxygen.Develops hydrogen on contact with: aluminium.May form explosive

SECTION 10. Stability and reactivity ... / >>

mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

SECTION 11. Toxicological information ... / >>

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal):	12126 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,124 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal):	1100 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

Xylene (ortho-)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate
LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9, aromatics
LD50 (Dermal): > 3400 mg/kg Rabbit
LD50 (Oral): > 6800 mg/kg Rat
LC50 (Inhalation vapours): > 10,2 mg/l/4h

Xylene (mixture of isomers)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

TITANIUM DIOXIDE
LD50 (Oral): > 10000 mg/kg Rat

2-(2-BUTOXYETHOXY)ETHANOL
LD50 (Dermal): 2700 mg/kg Rabbit
LD50 (Oral): 3384 mg/kg Rat

ETHYLBENZENE
LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat

2-Methoxy-1-Methylethyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9, aromatics

LC50 - for Fish > 1 mg/l/96h
EC50 - for Crustacea > 1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

SECTION 12. Ecological information ... / >>

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol
Degradability: information not available

Xylene
Solubility in water 100 - 1000 mg/l
Rapidly degradable

Ethylene Glycol Monobutyl Ether
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (ortho-)
Rapidly degradable

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9, aromatics
Rapidly degradable

Xylene (mixture of isomers)
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

SECTION 12. Ecological information ... / >>

2-(2-BUTOXYETHOXY)ETHANOL Partition coefficient: n-octanol/water	1
ETHYLBENZENE Partition coefficient: n-octanol/water	3,6
2-Methoxy-1-Methylethyl Acetate Partition coefficient: n-octanol/water	1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1

SECTION 16. Other information ... / >>

STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL SATIN Base 1

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 20 / 20

EN

SECTION 16. Other information ... / >>

8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32251D000.**
Product name: **UNIVERSE RED SEAL SATIN Base 2**
UFI: **7U52-30J0-V00E-E6MM**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

SECTION 2. Hazards identification ... / >>

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
XYLENE (reaction mass of ethylbenzene and xylene)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	20 \leq x < 30
EC	919-857-5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
TITANIUM DIOXIDE		
INDEX		5 \leq x < 9
EC	236-675-5	01-2119489379-17-0197 01-2119489379-17
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	
Xylene (ortho-)		
INDEX	601-022-00-9	5 \leq x < 9
EC	202-422-2	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	95-47-6	
REACH Reg.	01-2119488216	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	5 \leq x < 9
EC	919-857-5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX		1 \leq x < 5
		Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412

SECTION 3. Composition/information on ingredients ... / >>

EC	905-588-0		ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS			
REACH Reg.	01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29		
Hydrocarbons, C9, aromatics			
INDEX	1 ≤ x < 2,5		Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	918-668-5		
CAS	64742-95-6		
REACH Reg.	01-2119455851-35-0001 01-2119486773-24 01-2119455851-35		
Calcium Neodecanoate			
INDEX	1 ≤ x < 3		Eye Dam. 1 H318, Skin Irrit. 2 H315
EC	248-375-1		
CAS	27253-33-4		
REACH Reg.	01-2120769660-48-XXXX		
Modified Poly-Acrylate			
INDEX	1 ≤ x < 2,5		Aquatic Chronic 2 H411
EC			
CAS			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
INDEX	1 ≤ x < 5		Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5		
CAS	64742-48-9		
REACH Reg.	01-2119463258-33-0000		
Ethylene Glycol Monobutyl Ether			
INDEX	603-014-00-0	0,5 ≤ x < 1	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	203-905-0		LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	111-76-2		
REACH Reg.	01-2119475108-36		
Xylene			
INDEX	601-022-00-9	0 < x < 0,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7		LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h
CAS	1330-20-7		
REACH Reg.	01-2119488216-32		
n-Butyl Acetate			
INDEX	607-025-00-1	0 < x < 0,5	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC	204-658-1		
CAS	123-86-4		
REACH Reg.	01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29		
ETHYLBENZENE			
INDEX	601-023-00-4	0 < x < 0,5	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412
EC	202-849-4		LC50 Inhalation vapours: 17,2 mg/l/4h
CAS	100-41-4		
Quartz (Crystalline Silica)			
INDEX		0 < x < 0,5	Substance with a community workplace exposure limit.
EC	238-878-4		
CAS	14808-60-7		
2,6-di-tert-Butyl-p-cresol			
INDEX		0 < x < 0,25	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	204-881-4		
CAS	128-37-0		
REACH Reg.	01-2119565113-46		
2-(2-BUTOXYETHOXY)ETHANOL			
INDEX	603-096-00-8	0 < x < 0,5	Eye Irrit. 2 H319
EC	203-961-6		
CAS	112-34-5		

The full wording of hazard (H) phrases is given in section 16 of the sheet.



SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ФЕК 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

SECTION 8. Exposure controls/personal protection ... / >>

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
ACGIH 2023

TLV-ACGIH

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	10				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0002	mg/l
Normal value in marine water	0,00002	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
ПДК	RUS	50		150		n
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Ethylene Glycol Monobutyl Ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU		100		200			
TLV	GRC	435	100	650	150			
ESD	TUR	221	50	442	100			
WEL	GBR		50		100			
OEL	EU	221	50	442	100			
TLV-ACGIH			100		150			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	100						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	275	50	550	100	SKIN		
AGW	DEU	270	50	270	50			
MAK	DEU	270	50	270	50			
TLV	GRC	275	50	550	100			
TLV	ROU	275	50	550	100	SKIN		
ПДК	RUS			10			n	
ESD	TUR	275	50	550	100	SKIN		
WEL	GBR	274	50	548	100	SKIN		
OEL	EU	275	50	550	100	SKIN		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	10				RESP		
MAK	DEU	0,3		2,4		RESP	Hinweis	
TLV	GRC		10					
TLV	ROU	10		15				
ПДК	RUS	10					a, φ	
WEL	GBR	10				INHAL		
WEL	GBR	4				RESP		
TLV-ACGIH		0,2				RESP		

SECTION 8. Exposure controls/personal protection ... / >>

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

SECTION 8. Exposure controls/personal protection ... / >>

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

SECTION 10. Stability and reactivity ... / >>

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

SECTION 11. Toxicological information ... / >>

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal):	12126 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,124 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal):	1100 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

Ethylene Glycol Monobutyl Ether	
LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat
Xylene (ortho-)	
LD50 (Dermal):	> 1700 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	5000 ppm/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
Calcium Neodecanoate	
LD50 (Dermal):	> 3640 mg/kg rat
LD50 (Oral):	2066 mg/kg rat
Hydrocarbons, C9, aromatics	
LD50 (Dermal):	> 3400 mg/kg Rabbit
LD50 (Oral):	> 6800 mg/kg Rat
LC50 (Inhalation vapours):	> 10,2 mg/l/4h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat
n-Butyl Acetate	
LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	13100 mg/kg Rat
LC50 (Inhalation vapours):	> 21 mg/l Rat
TITANIUM DIOXIDE	
LD50 (Oral):	> 10000 mg/kg Rat
2-(2-BUTOXYETHOXY)ETHANOL	
LD50 (Dermal):	2700 mg/kg Rabbit
LD50 (Oral):	3384 mg/kg Rat
ETHYLBENZENE	
LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish

EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms

EC50 - for Crustacea > 100 mg/l/48h

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

Chronic NOEC for Fish > 0,1 mg/l

Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9, aromatics

LC50 - for Fish > 1 mg/l/96h

EC50 - for Crustacea > 1 mg/l/48h

EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms

EC50 - for Crustacea > 100 mg/l/48h

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

Chronic NOEC for Fish > 0,1 mg/l

Chronic NOEC for Crustacea > 0,1 mg/l

SECTION 12. Ecological information ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
 EC50 - for Crustacea > 100 mg/l/48h
 EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
 Chronic NOEC for Fish > 0,1 mg/l
 Chronic NOEC for Crustacea > 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol
 Degradability: information not available

Xylene
 Solubility in water 100 - 1000 mg/l
 Rapidly degradable

Ethylene Glycol Monobutyl Ether
 Solubility in water 1000 - 10000 mg/l
 Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Rapidly degradable

Xylene (ortho-)
 Rapidly degradable

Calcium Neodecanoate
 Degradability: information not available

Hydrocarbons, C9, aromatics
 Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Rapidly degradable

n-Butyl Acetate
 Solubility in water > 10000 mg/l
 Rapidly degradable

TITANIUM DIOXIDE
 Solubility in water < 0,001 mg/l
 Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
 Solubility in water 1000 - 10000 mg/l
 Rapidly degradable

ETHYLBENZENE
 Solubility in water 1000 - 10000 mg/l
 Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
 Partition coefficient: n-octanol/water 5,1 Log Kow
 BCF < 1800

Xylene
 Partition coefficient: n-octanol/water 3,12
 BCF 25,9

Ethylene Glycol Monobutyl Ether
 Partition coefficient: n-octanol/water 0,81

SECTION 12. Ecological information ... / >>

n-Butyl Acetate	
Partition coefficient: n-octanol/water	1,2
2-(2-BUTOXYETHOXY)ETHANOL	
Partition coefficient: n-octanol/water	1
ETHYLBENZENE	
Partition coefficient: n-octanol/water	3,6

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1

SECTION 16. Other information ... / >>

STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament



KRAFT
PAINTS
DRIVEN BY INNOVATION

DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL SATIN Base 2

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 19 / 19

EN

SECTION 16. Other information ... / >>

8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK32251A000.**
Product name: **UNIVERSE RED SEAL SATIN Base 3**
UFI: **UX52-M07E-500W-2J6P**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Maleic anhydride
XYLENE (reaction mass of ethylbenzene and xylene)
Aliphatic polyether esterified with maleic acid

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6 $20 \leq x < 30$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
Xylene (ortho-)		
INDEX	601-022-00-9 $5 \leq x < 9$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6 $5 \leq x < 9$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX	1 $\leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412 ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	905-588-0	

**SECTION 3. Composition/information on ingredients ... / >>**

CAS		
REACH Reg. 01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29		
Calcium Neodecanoate		
INDEX	1 ≤ x < 3	Eye Dam. 1 H318, Skin Irrit. 2 H315
EC	248-375-1	
CAS	27253-33-4	
REACH Reg. 01-2120769660-48-XXXX		
Modified Poly-Acrylate		
INDEX	1 ≤ x < 2,5	Aquatic Chronic 2 H411
EC		
CAS		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	1 ≤ x < 5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg. 01-2119463258-33-0000		
Aliphatic polyether esterified with maleic acid		
INDEX	0,5 ≤ x < 1	Skin Sens. 1 H317
EC		
CAS	709014-50-6	
Ethylene Glycol Monobutyl Ether		
INDEX	603-014-00-0	0,5 ≤ x < 1
EC	203-905-0	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315 LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	111-76-2	
REACH Reg. 01-2119475108-36		
n-Butyl Acetate		
INDEX	607-025-00-1	0 < x < 0,5
EC	204-658-1	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
CAS	123-86-4	
REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29		
Quartz (Crystalline Silica)		
INDEX	0 < x < 0,5	Substance with a community workplace exposure limit.
EC	238-878-4	
CAS	14808-60-7	
Maleic anhydride		
INDEX	607-096-00-9	0,001 ≤ x < 0,1
EC	203-571-6	Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071
CAS	108-31-6	Skin Sens. 1A H317: ≥ 0,001%
REACH Reg. 01-2119472428-31		
Xylene (mixture of isomers)		
INDEX	601-022-00-9	0 < x < 0,5
EC	215-535-7	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
CAS	1330-20-7	LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
REACH Reg. 01-2119488216-32		
2,6-di-tert-Butyl-p-cresol		
INDEX	0 < x < 0,25	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	204-881-4	
CAS	128-37-0	
REACH Reg. 01-2119565113-46		
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX	603-096-00-8	0 < x < 0,5
EC	203-961-6	Eye Irrit. 2 H319
CAS	112-34-5	
2-Methoxy-1-Methylethyl Acetate		
INDEX	607-195-00-7	0 < x < 0,5
EC	203-603-9	Flam. Liq. 3 H226, STOT SE 3 H336
CAS	108-65-6	
REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001		
Xylene		
INDEX	601-022-00-9	0 < x < 0,5
EC	215-535-7	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
		LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h



SECTION 3. Composition/information on ingredients ... / >>

CAS 1330-20-7
REACH Reg. 01-2119488216-32

Acetone

INDEX 606-001-00-8 0 < x < 0,5 **Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066**
EC 200-662-2
CAS 67-64-1
REACH Reg. 01-2119471330-49-0003

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of



contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК)

SECTION 8. Exposure controls/personal protection ... / >>

TUR	Türkiye	ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ" Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	10						
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,0002	mg/l	
Normal value in marine water						0,00002	mg/l	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	3,5 mg/kg
Skin							VND	0,5 mg/kg bw/d

Xylene

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
ПДК	RUS	50		150		n
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Quartz (Crystalline Silica)

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Acetone

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
TLV	GRC	1780		3560		
TLV	ROU	1210	500			
ПДК	RUS	200		800		n
ESD	TUR	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

SECTION 8. Exposure controls/personal protection ... / >>

Ethylene Glycol Monobutyl Ether

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU		100		200			
TLV	GRC	435	100	650	150			
ESD	TUR	221	50	442	100			
WEL	GBR		50		100			
OEL	EU	221	50	442	100			
TLV-ACGIH			100		150			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	GRC	1200							
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure		Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	300 mg/kg/d				
Inhalation				VND	900 mg/m3	VND	1500 mg/m3		
Skin				VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH		

SECTION 9. Physical and chemical properties ... / >>

	not available		Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s		Method: Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU		Temperature: 25 °C Method: ASTM D 562-05 Temperature: 25 °C
Solubility	not available		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	0,91-1,23 g/cm ³		Method: ISO 2811 Temperature: 25 °C
Relative vapour density	not available		
Particle characteristics	not applicable		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Acetone

Decomposes under the effect of heat.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Acetone

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3-

butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline

hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric

acid, chloroform, peroxy monosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

SECTION 10. Stability and reactivity ... / >>

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Acetone

Avoid exposure to: sources of heat, naked flames.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

Acetone

Incompatible with: acids, oxidising substances.

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Acetone

May develop: ketenes, irritant substances.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

SECTION 11. Toxicological information ... / >>

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal):	12126 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,124 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal):	1100 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (ortho-)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate
LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

Xylene (mixture of isomers)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

2-(2-BUTOXYETHOXY)ETHANOL
LD50 (Dermal): 2700 mg/kg Rabbit
LD50 (Oral): 3384 mg/kg Rat

2-Methoxy-1-Methylethyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol

Degradability: information not available

Xylene

Solubility in water 100 - 1000 mg/l
Rapidly degradable



SECTION 12. Ecological information ... / >>

Acetone
Rapidly degradable

Ethylene Glycol Monobutyl Ether
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (ortho-)
Rapidly degradable

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (mixture of isomers)
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Acetone
Partition coefficient: n-octanol/water -0,23
BCF 3

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

2-(2-BUTOXYETHOXY)ETHANOL
Partition coefficient: n-octanol/water 1

2-Methoxy-1-Methylethyl Acetate
Partition coefficient: n-octanol/water 1,2

12.4. Mobility in soil

Information not available

SECTION 12. Ecological information ... / >>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 lt
Special provision: 163, 367, 650

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E Limited Quantities: 5 lt
IATA: Cargo: Maximum quantity: 220 L
Passengers: Maximum quantity: 60 L
Special provision: A3, A72, A192

Packaging instructions: 366

Packaging instructions: 355

SECTION 14. Transport information ... / >>

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.

SECTION 16. Other information ... / >>

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)



SECTION 16. Other information ... / >>

13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK322510001.**
Product name: **UNIVERSE RED SEAL SATIN White**
UFI: **4P52-3057-800E-3HFG**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Highly performance enamel paint for metals**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

SECTION 2. Hazards identification ... / >>

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTRE / doctor, if you feel unwell.
P405	Store locked up.

Contains:	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics XYLENE (reaction mass of ethylbenzene and xylene) Hydrocarbons, C9, aromatics
------------------	---

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
TITANIUM DIOXIDE		
INDEX	$9 \leq x < 30$	
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	$10 \leq x < 20$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-21119463258-33	
XYLENE (reaction mass of ethylbenzene and xylene)		
INDEX	$1 \leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412 ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	905-588-0	
CAS		
REACH Reg.	01-2119486136-34 01-2119539452-40 01-2119539452-40-0055 01-2119485493-29	
Xylene (ortho-)		
INDEX	$1 \leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	202-422-2	
CAS	95-47-6	
REACH Reg.	01-2119488216	

SECTION 3. Composition/information on ingredients ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX 649-327-00-6 $1 \leq x < 5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 919-857-5
CAS 64742-48-9
REACH Reg. 01-2119463258-33

Hydrocarbons, C9, aromatics

INDEX $1 \leq x < 2,5$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 918-668-5
CAS 64742-95-6
REACH Reg. 01-2119455851-35-0001 01-2119486773-24 01-2119455851-35

Calcium Neodecanoate

INDEX $1 \leq x < 3$ Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 248-375-1
CAS 27253-33-4
REACH Reg. 01-2120769660-48-XXXX

Ethylene Glycol Monobutyl Ether

INDEX 603-014-00-0 $0,5 \leq x < 1$ Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
LD50 Oral: 1200 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 203-905-0
CAS 111-76-2
REACH Reg. 01-2119475108-36

n-Butyl Acetate

INDEX 607-025-00-1 $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1
CAS 123-86-4
REACH Reg. 01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29

Xylene

INDEX 601-022-00-9 $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h

EC 215-535-7
CAS 1330-20-7
REACH Reg. 01-2119488216-32

Xylene (mixture of isomers)

INDEX 601-022-00-9 $0 < x < 0,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
LD50 Dermal: >1700 mg/kg, ATE Inhalation vapours: 11 mg/l

EC 215-535-7
CAS 1330-20-7
REACH Reg. 01-2119488216-32

Trimethylolpropane (TMP)

INDEX $0 < x < 0,5$ Repr. 2 H361fd

EC 201-074-9
CAS 77-99-6
REACH Reg. 01-2119486799-10-0000

2-Methoxy-1-Methylethyl Acetate

INDEX 607-195-00-7 $0 < x < 0,5$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9
CAS 108-65-6
REACH Reg. 01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001

ETHYLBENZENE

INDEX 601-023-00-4 $0 < x < 0,5$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412
LC50 Inhalation vapours: 17,2 mg/l/4h

EC 202-849-4
CAS 100-41-4

Quartz (Crystalline Silica)

INDEX $0 < x < 0,5$ Substance with a community workplace exposure limit.

EC 238-878-4
CAS 14808-60-7

2,6-di-tert-Butyl-p-cresol

INDEX $0 < x < 0,25$ Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 204-881-4
CAS 128-37-0
REACH Reg. 01-2119565113-46

SECTION 3. Composition/information on ingredients ... / >>

2-(2-BUTOXYETHOXY)ETHANOL

INDEX 603-096-00-8 0 < x < 0,5 Eye Irrit. 2 H319
EC 203-961-6
CAS 112-34-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: immediately call a POISON CENTER or a doctor

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with

self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)

SECTION 8. Exposure controls/personal protection ... / >>

EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2,6-di-tert-Butyl-p-cresol

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	10						
Predicted no-effect concentration - PNEC								
Normal value in fresh water						0,0002	mg/l	
Normal value in marine water						0,00002	mg/l	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	systemic	local	systemic	systemic	local	systemic	systemic
Inhalation						VND		3,5 mg/kg
Skin						VND		0,5 mg/kg bw/d

Xylene

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
ПДК	RUS	50		150		n
ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Quartz (Crystalline Silica)

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Ethylene Glycol Monobutyl Ether

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
TLV	GRC	120	25			
TLV	ROU	98	20	246	50	SKIN
ПДК	RUS			10		n
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Xylene (ortho-)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU		100		200			
TLV	GRC	435	100	650	150			
ESD	TUR	221	50	442	100			
WEL	GBR		50		100			
OEL	EU	221	50	442	100			
TLV-ACGIH			100		150			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

Hydrocarbons, C9, aromatics

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	100						

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
ESD	TUR	221	50	442	100	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3		VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin				VND	108 mg/kg/d			VND	180 mg/kg/d

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic				Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	1,67 mg/kg				
Inhalation				VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin				VND	54,8 mg/kg			VND	153,5 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
ПДК	RUS	10				a, φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
TLV	GRC	67,5	10	101,2	15	
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
ESD	TUR	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
TLV	GRC	435	100	545	125	
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
ESD	TUR	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	GRC	1200						
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH		



SECTION 9. Physical and chemical properties ... / >>

	not available	Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	585-2565 mm ² /s	Method:Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	75-115 KU	Temperature: 25 °C Method:ASTM D 562-05 Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,91-1,23 g/cm ³	Method:ISO 2811 Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 60,00 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethylene Glycol Monobutyl Ether

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

Ethylene Glycol Monobutyl Ether

May react dangerously with: aluminium,oxidising agents.Formes peroxides with: air.

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances,strong acids,alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances.May form peroxides with: oxygen.Develops hydrogen on contact with: aluminium.May form explosive

SECTION 10. Stability and reactivity ... / >>

mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Ethylene Glycol Monobutyl Ether

Avoid exposure to: sources of heat, naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

n-Butyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Ethylene Glycol Monobutyl Ether

May develop: hydrogen.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (ortho-)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

SECTION 11. Toxicological information ... / >>

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

XYLENE (reaction mass of ethylbenzene and xylene)

LD50 (Dermal):	12126 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,124 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Xylene

LD50 (Dermal):	1100 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h Rat

Ethylene Glycol Monobutyl Ether

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

Xylene (ortho-)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Calcium Neodecanoate
LD50 (Dermal): > 3640 mg/kg rat
LD50 (Oral): 2066 mg/kg rat

Hydrocarbons, C9, aromatics
LD50 (Dermal): > 3400 mg/kg Rabbit
LD50 (Oral): > 6800 mg/kg Rat
LC50 (Inhalation vapours): > 10,2 mg/l/4h

Xylene (mixture of isomers)
LD50 (Dermal): > 1700 mg/kg Rabbit
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 13100 mg/kg Rat
LC50 (Inhalation vapours): > 21 mg/l Rat

TITANIUM DIOXIDE
LD50 (Oral): > 10000 mg/kg Rat

2-(2-BUTOXYETHOXY)ETHANOL
LD50 (Dermal): 2700 mg/kg Rabbit
LD50 (Oral): 3384 mg/kg Rat

ETHYLBENZENE
LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat

2-Methoxy-1-Methylethyl Acetate
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

XYLENE (reaction mass of ethylbenzene and xylene)

LC50 - for Fish 18 mg/l/96h Fresh Water Fish
EC50 - for Algae / Aquatic Plants 1,3 mg/l/72h Algae

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

Xylene (ortho-)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Calcium Neodecanoate

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish 0,199 mg/l

Hydrocarbons, C9, aromatics

LC50 - for Fish > 1 mg/l/96h
EC50 - for Crustacea > 1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms
EC50 - for Crustacea > 100 mg/l/48h
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l
Chronic NOEC for Crustacea > 0,1 mg/l

SECTION 12. Ecological information ... / >>

12.2. Persistence and degradability

2,6-di-tert-Butyl-p-cresol
Degradability: information not available

Xylene
Solubility in water 100 - 1000 mg/l
Rapidly degradable

Ethylene Glycol Monobutyl Ether
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

Xylene (ortho-)
Rapidly degradable

Calcium Neodecanoate
Degradability: information not available

Hydrocarbons, C9, aromatics
Rapidly degradable

Xylene (mixture of isomers)
Rapidly degradable

n-Butyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

TITANIUM DIOXIDE
Solubility in water < 0,001 mg/l
Degradability: information not available

2-(2-BUTOXYETHOXY)ETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

ETHYLBENZENE
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

2-Methoxy-1-Methylethyl Acetate
Solubility in water > 10000 mg/l
Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-Butyl-p-cresol
Partition coefficient: n-octanol/water 5,1 Log Kow
BCF < 1800

Xylene
Partition coefficient: n-octanol/water 3,12
BCF 25,9

Ethylene Glycol Monobutyl Ether
Partition coefficient: n-octanol/water 0,81

n-Butyl Acetate
Partition coefficient: n-octanol/water 1,2

SECTION 12. Ecological information ... / >>

2-(2-BUTOXYETHOXY)ETHANOL Partition coefficient: n-octanol/water	1
ETHYLBENZENE Partition coefficient: n-octanol/water	3,6
2-Methoxy-1-Methylethyl Acetate Partition coefficient: n-octanol/water	1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
 Waste transportation may be subject to ADR restrictions.
 CONTAMINATED PACKAGING
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
 IMDG: PAINT or PAINT RELATED MATERIAL
 IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III



DRUCKFARBEN HELLAS SA

UNIVERSE RED SEAL SATIN White

Revision nr.1
Dated 04/12/2024
First compilation
Printed on 04/12/2024
Page n. 18 / 20

EN

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3 - 40
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4

SECTION 16. Other information ... / >>

Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament

SECTION 16. Other information ... / >>

6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.