

Product Data Sheet

08/2022: THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT



PRATT & LAMBERT PAINTS
Never compromise®

Universe® Ultra Matt

Universe® Ultra Matt is an emulsion mat paint for indoor use. It is almost odorless, is easy to wash and withstands frequent washing with detergents.

Due to its very low sheen it effectively covers the imperfections of the wall, offering a uniform mat finish. The bright white and the thousands of shades resist to time and can withstand yellowing by aesthetically upgrading the spaces.

- Excellent resistance to washing
- High coverage
- Easy to apply

Surface Preparation

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc. Avoid dust generation and exposure to it. Wet sanding is recommended for the surface preparation

Recommended Systems

On new surfaces

Drywall: before applying the topcoat, apply one coat of a water-based primer such as **Universe® Primer**

Masonry (cured 30+ days): before applying the topcoat, apply one coat of a water-based primer such as **Universe® Primer** or **Pratt & Lambert® Int/Ext Multi-Purpose Waterborne Primer** or **Universe Multiprimer**

On surfaces that need repairing

Use 100% acrylic putty where needed.

Technical Data

| | | |
|--|--|--|
| Vehicle: | PVA-VeoVa / PAc | |
| Finish:* | Matt | 3 – 6 units @ 85° |
| Flash Point: | N/A | |
| Volume Solids:* | Matt | 47 ±2% |
| Weight Solids:* | Matt | 60±2% |
| Weight/Liter:* | Matt | 1.46kg (±0.02) |
| VOC: | Interior matt walls and ceilings A/a (W/B) VOC Limit Value 30g/L. | <10g/L |
| Spread Rate: | | 9 – 14 m ² per Liter per coat |
| Film Thickness: | Matt | @ 100µm wet; 40µm dry |
| Drying Time (@ 25°C, 50% R.H.): | To Touch | 1-2 hours |
| | To Recoat | 4-6 hours |
| Reduction | | Water |
| Tinting | Kraft Inspired Color Universal Colorants | Mat |
| | Base 1 | √ |
| | Base 2 | √ |
| | Base 3 | √ |
| Sizes: | 1 Quart (0.946L), 1 Gallon (3.785L), 2.5 Gallon (9.46L) | |

* Product data calculated on White

Product Data Sheet

08/2022: THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

Application

Temperature (air, surface and material): Apply at temperatures above 5°C

More than one coat of paint may be necessary for new and uncoated surfaces, dramatic color changes, or when using dark/vibrant colors for optimal appearance and hide

Airless Spray: Pressure/Tip/Reduction

2000 psi/.015'' - .019'' / 5-10% by volume water

Brush: Brush/Reduction

Nylon-Polyester / 5-10% by volume water

Roller: Reduction

5-10% by volume water

After use instructions

- Clean the tools thoroughly with water and detergent.
- Close the bucket to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.
- Allow at least 15 days before cleaning and washing newly painted surfaces. Dark shades are less resistant to frequent washing.
- You can wash the painted surfaces gently with a soft sponge and water and in cases of bad stains with a mild detergent.

Cautions - Storage

- Do not apply at temperatures <5 °C or > 35 °C and humidity >65%.
- Keep the product in temperature from 5 °C to 35 °C and humidity level <50%.
- Keep container tightly closed.

Health, Safety & Environmental Information

Read label before use. For further information please refer to the Material Safety Data Sheet according to EC Regulation 1272/2008 (CLP)

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA, GREECE | TEL.: +30 210 55 19 500

FAX: +30 210 55 19 501

www.druckfarben.gr | www.kraftpaints.gr

Toll Free Number

800 111 7700 Monday - Friday, 8.00 a.m - 04.00 p.m.

Email: paints.orders@druckfarben.gr