

Go Exterior



THINNING
0 - 10%



COVERAGE
10 - 12m²/L



APPLICATION
brush
or roller



DRYING
1 - 2 hours

Cost-effective acrylic paint
for exterior walls

» **Very good coverage**

» **Easy to apply**

» **Suitable for frequent repainting**

Cost-effective acrylic paint for exterior use. It is suitable for frequent repainting, it effectively covers imperfections and it is easy to apply creating an even and water vapor permeable matt finish.

A/c (WB) Exterior walls of mineral substrate.

- VOC Limit Value: 40g/L.
- Maximum VOC concentration of the ready to use product: 39g/L.

TECHNICAL DATA

Density ISO 2811 @ 25°C	1.56g/mL (±0,05) *
Solids Content w/w ISO 3251	64% (±3) *
Viscosity ASTM D 562-05 @ 25°C	110KU (±15)
Application Viscosity ASTM D 562-05 @ 25°C	80 KU (±15)
Gloss Level @ 60° ISO 2813	<3 GU
Gloss Level @ 85° ISO 2813	<11 GU
pH	8.5 - 9.5
Whiteness Index ASTM E 313-98	88.5 (±1.5) **
Yellowness Index ASTM E 313-98	0.6 (±0.5) **
Coverage per coat	10 - 12 m ² /L ***
Recommended dry film thickness (2 coats)	70 µm(±5)

* Depending on the shade and the tinting base.

** Only for white.

*** Depending on the shade, the application method and the surface absorption.

Go Exterior

Cost-effective acrylic paint
for exterior walls

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, grease, residues, blistered paint, etc. Avoid dust generation and exposure to it.

- » **On new surfaces:** Before applying the topcoat, apply one coat of a primer, such as KRAFT ECO DUR AQUA or KRAFT HAFT or KRAFT DUR.
- » **On surfaces that need repair:** Use KRAFT SPACHTEL or KRAFT PUTTY or a suitable KRAFT repairing material.

Allow new surfaces of plaster or concrete to dry completely for at least 30 days before the paint application.

APPLICATION INSTRUCTIONS

- » In case of expected rain, avoid applying in the next 7 days.
- » Before start painting, thin the paint up to 10% v/v with tap water and stir well.
- » You can apply with a brush or a roller.
- » The product should be tinted only with the KRAFT INSPIRED COLOR tinting system on the recommended tinting base.
- » For shade and finish consistency, it is advisable to use containers of the same batch number. In case of different batch numbers, it is recommended to have them mixed in a larger container.
- » Tonal shift may occur in some shades.
- » KRAFT GO EXTERIOR White can be tinted with the KRAFT MASTER BASICS basic colors for countless light shades.
- » Apply two coats of KRAFT GO EXTERIOR for an ideal result.
- » Minimum recoating time: 3-4 hours.
- » Dry to touch: 1-2 hours at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » Avoid patching after the completion of painting. A slight difference in absorbance or in the application method might cause color or gloss unevenness. If necessary, it is advisable to recoat the whole surface.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 65% or higher.

AFTER USE INSTRUCTIONS

- » Clean the tools immediately with warm water and soap.
- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.

PACKAGING

Available in White, in 750ml, 3L and 9L containers, and in tinting base P in 1L, 3L and 9L containers.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

06/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarbengroup.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr