

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **CK202640001**
Product name: **KRAFT Stain Blocker**
UFI: **K3R1-403G-V007-KKD9**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Acrylic undercoat for walls**

1.3. Details of the supplier of the safety data sheet

Name: **DRUCKFARBEN HELLAS SA**
Full address: **MEGARIDOS AVENUE**
District and Country: **19300 ASPROPYRGOS (ATTIKI) GREECE**
Tel.: **+30 210 5519500**
Fax: **+30 210 5519501**
e-mail address of the competent person responsible for the Safety Data Sheet: **psafety@druckfarben.gr**

1.4. Emergency telephone number

For urgent inquiries refer to: **0030-210-7793777**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

SECTION 2. Hazards identification ... / >>

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER or a doctor
P370+P378	In case of fire: use alcohol resistant foam to extinguish.
P501	Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local / national / international regulations.
P102	Keep out of reach of children.

Contains: Naphtha (petroleum), hydrotreated heavy
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
TITANIUM DIOXIDE		
INDEX	9 ≤ x < 30	
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-0000	01-2119489379-17-0197 01-2119489379-17
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
INDEX	649-327-00-6	10 ≤ x < 20
EC	919-857-5	
CAS	64742-48-9	
REACH Reg.	01-2119463258-33	
Naphtha (petroleum), hydrotreated heavy		
INDEX	649-327-00-6	10 ≤ x < 20
EC	265-150-3	
CAS	64742-48-9	
REACH Reg.	01-2119463258-	
Xylene (mixture of isomers)		
INDEX	601-022-00-9	0 ≤ x < 0,5
EC	215-535-7	
CAS	1330-20-7	
REACH Reg.	01-2119488216-32	
2-Methoxy-1-Methylethyl Acetate		
INDEX	607-195-00-7	0 ≤ x < 0,5
EC	203-603-9	
CAS	108-65-6	
REACH Reg.	01-2119475791-29 01-2119565113-46-0017 01-2119475791-29-0045 01-2119475791-29-0001	
n-Butyl Acetate		
INDEX	607-025-00-1	0 ≤ x < 0,5
EC	204-658-1	
CAS	123-86-4	
REACH Reg.	01-2119485493-29-0007 01-2119485493-29-0005 01-2119485493-29-0003 01-2119485493-29	
Xylene		
INDEX	601-022-00-9	0 ≤ x < 0,5
EC	215-535-7	

SECTION 3. Composition/information on ingredients ... / >>

CAS 1330-20-7
REACH Reg. 01-2119488216-32

Acetone

INDEX 606-001-00-8 $0 \leq x < 0,5$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2
CAS 67-64-1
REACH Reg. 01-2119471330-49-0003

Quartz (Crystalline Silica)

INDEX $0 \leq x < 0,5$ Substance with a community workplace exposure limit.
EC 238-878-4
CAS 14808-60-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

SECTION 6. Accidental release measures ... / >>

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

SECTION 8. Exposure controls/personal protection ... / >>

Xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
TLV	GRC	435	100	650	150	
TLV	ROU	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Quartz (Crystalline Silica)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ROU	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Acetone

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
TLV	GRC	1780		3560		
TLV	ROU	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

Xylene (mixture of isomers)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU		100		200	
TLV	GRC	435	100	650	150	
WEL	GBR		50		100	
OEL	EU	221	50	442	100	
TLV-ACGIH			100		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

SECTION 8. Exposure controls/personal protection ... / >>

n-Butyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	ml/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3	553,5 mg/m3	VND	VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	10				RESP
MAK	DEU	0,3		2,4		RESP Hinweis
TLV	GRC		10			
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

2-Methoxy-1-Methylethyl Acetate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	GRC	275	50	550	100	
TLV	ROU	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

SECTION 8. Exposure controls/personal protection ... / >>

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	GRC	1200							
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure		Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	300 mg/kg/d				
Inhalation				VND	900 mg/m3	VND	1500 mg/m3		
Skin				VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Temperature: 25 °C
Colour	white	Temperature: 25 °C
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)

**SECTION 9. Physical and chemical properties ... / >>**

Kinematic viscosity	260-450 mm ² /s	Method:Converting Formula from Dynamic Viscosity & Density
Dynamic viscosity	63-73 KU	Temperature: 25 °C
Solubility	insoluble in water	Method:ASTM D 562-05
Partition coefficient: n-octanol/water	not available	Temperature: 25 °C
Vapour pressure	not available	
Density and/or relative density	1,41-1,45 g/cm ³	Method:ISO 2811
Relative vapour density	not available	Temperature: 25 °C
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	73,44 %
VOC (Directive 2010/75/EU)	499,00 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Acetone

Decomposes under the effect of heat.

n-Butyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

2-Methoxy-1-Methylethyl Acetate

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Xylene

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Acetone

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxy monosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

n-Butyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

2-Methoxy-1-Methylethyl Acetate

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid



SECTION 10. Stability and reactivity ... / >>

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Acetone

Avoid exposure to: sources of heat,naked flames.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

10.5. Incompatible materials

Acetone

Incompatible with: acids,oxidising substances.

n-Butyl Acetate

Incompatible with: oxidising substances,strong acids,alkaline metals.

2-Methoxy-1-Methylethyl Acetate

Incompatible with: oxidising substances,strong acids,alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Acetone

May develop: ketenes,irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Xylene (mixture of isomers)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

n-Butyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

2-Methoxy-1-Methylethyl Acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Xylene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

n-Butyl Acetate

WORKERS: inhalation; contact with the skin.

2-Methoxy-1-Methylethyl Acetate

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

n-Butyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

2-Methoxy-1-Methylethyl Acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

SECTION 11. Toxicological information ... / >>

Interactive effects

Xylene

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)
 ATE (Oral) of the mixture: Not classified (no significant component)
 ATE (Dermal) of the mixture: Not classified (no significant component)

Naphtha (petroleum), hydrotreated heavy

LD50 (Dermal): > 3000 mg/kg Rabbit
 LD50 (Oral): > 5000 mg/kg Rat

Xylene

LD50 (Dermal): 1100 mg/kg Rabbit
 LD50 (Oral): 3523 mg/kg Rat
 LC50 (Inhalation vapours): 11 mg/l/4h Rat

Xylene (mixture of isomers)

LD50 (Dermal): > 1700 mg/kg Rabbit
 LD50 (Oral): 3523 mg/kg Rat
 LC50 (Inhalation vapours): 5000 ppm/4h Rat

n-Butyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
 LD50 (Oral): 13100 mg/kg Rat
 LC50 (Inhalation vapours): > 21 mg/l Rat

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

2-Methoxy-1-Methylethyl Acetate

LD50 (Dermal): > 5000 mg/kg Rat
 LD50 (Oral): 8530 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 (Dermal): > 5000 mg/kg Rabbit
 LD50 (Oral): > 5000 mg/kg Rat
 LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

SECTION 11. Toxicological information ... / >>

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Xylene (mixture of isomers)

LC50 - for Fish > 100 mg/l/96h Microorganisms

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms

EC50 - for Crustacea > 100 mg/l/48h

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

Chronic NOEC for Fish > 0,1 mg/l

Chronic NOEC for Crustacea > 0,1 mg/l

12.2. Persistence and degradability

Xylene

Solubility in water 100 - 1000 mg/l

Rapidly degradable

Acetone

Rapidly degradable

Xylene (mixture of isomers)

Rapidly degradable

n-Butyl Acetate

Solubility in water > 10000 mg/l

Rapidly degradable

TITANIUM DIOXIDE

Solubility in water < 0,001 mg/l

Degradability: information not available

2-Methoxy-1-Methylethyl Acetate

Solubility in water > 10000 mg/l

Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

SECTION 12. Ecological information ... / >>

12.3. Bioaccumulative potential

Xylene	
Partition coefficient: n-octanol/water	3,12
BCF	25,9
Acetone	
Partition coefficient: n-octanol/water	-0,23
BCF	3
n-Butyl Acetate	
Partition coefficient: n-octanol/water	1,2
2-Methoxy-1-Methylethyl Acetate	
Partition coefficient: n-octanol/water	1,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

SECTION 15. Regulatory information ... / >>

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile



SECTION 16. Other information ... / >>

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.