



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 1 / 10

# Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: CK351040000

Product name KRAFT TOTAL PROOF AQUA Primer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Penetration Water-Based Primer for Roofs

1.3. Details of the supplier of the safety data sheet

Name DRUCKFARBEN HELLAS SA Full address MEGARIDOS AVENUE

District and Country 19300 ASPROPYRGOS (ATTIKI)

**GREECE** 

Tel. +30 210 5519500 Fax +30 210 5519501

e-mail address of the competent person

responsible for the Safety Data Sheet psafety@druckfarben.gr

1.4. Emergency telephone number

For urgent inquiries refer to 0030-210-7793777

## **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

**EUH208** Contains: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-Benzisothiazol-3(2H)-one (BW20)

May produce an allergic reaction.

Precautionary statements:

P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local /

national / international regulations.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P312 Call a POISON CENTRE / doctor, if you feel unwell.



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 2 / 10

#### SECTION 2. Hazards identification .../>>

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

# **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

2-Butoxy Ethanol

INDEX 603-014-00-0 1 ≤ x < 5 Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0 LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h

CAS 111-76-2

REACH Reg. 01-2119475108-36, 01-2119475108-36-0003

1,2-Benzisothiazol-3(2H)-one (BW20)

INDEX 613-088-00-6  $0 \le x < 0.05$  Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 220-120-9 Skin Sens. 1 H317: ≥ 0,05%

CAS 2634-33-5 LD50 Oral: 1150 mg/kg, STA Inhalation mists/powders: 0,051 mg/l

REACH Reg. 01-2120761540-60

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

INDEX 613-167-00-5  $0 \le x < 0,0015$  Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C

H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100, EUH071

EC 611-341-5 Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥

0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%

CAS 55965-84-9 STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours:

0,501 mg/l

REACH Reg. 01-2120764691-48

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.



# KRAFT TOTAL PROOF AQUA Primer

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 3 / 10

#### SECTION 5. Firefighting measures .../>>

### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Regulatory references:

ВGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,

СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17

Януари 2020г.)

DEU Deutschland Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur

Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58

GRC Ελλάδα Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των

οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με



ROU

# DRUCKFARBEN HELLAS SA

# KRAFT TOTAL PROOF AQUA Primer

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 4 / 10

SECTION 8. Exposure controls/personal protection

România

την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru

modificarea și completarea hotărârii guvernului nr. 1.093/2006

EH40/2005 Workplace exposure limits (Fourth Edition 2020) **GBR** United Kingdom

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) EU OEL EU 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/FFC

TLV-ACGIH **ACGIH 2023** 

# Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Threshold Lin	nit Value					
Type	Country	TWA/8h		STEL/15	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,05				SKIN

2-Butoxy Ethanol												
Threshold Limit	Value											
Type	Country	TWA/8h		STEL/15min		Remarks / Observations						
		mg/m3	ppm	mg/m3	ppm							
TLV	BGR	98	20	246	50	SKIN						
AGW	DEU	49	10	98	20	SKIN						
MAK	DEU	49	10	98	20	SKIN Hinweis						
TLV	GRC	120	25									
TLV	ROU	98	20	246	50	SKIN						
WEL	GBR	123	25	246	50	SKIN						
OEL	EU	98	20	246	50	SKIN						
TLV-ACGIH		97	20									

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION** 

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS** The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Properties** Value Information Temperature: 25 °C Appearance liauid Colour transparent Temperature: 25 °C Odour characteristic

# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 5 / 10

# SECTION 9. Physical and chemical properties ..../>>

Melting point / freezing point not available Initial boiling point not available Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point °C 60 Auto-ignition temperature not available Decomposition temperature not available 8,5-9,5

pH 8,5-9,5 Concentration: 100 % Temperature: 25 °C

Kinematic viscosity 24-65 mm2/s Method:Converting Formula from Dynamic

Viscosity & Density Temperature: 25 °C

15-35 sec Method:Flow Cup No 4
Temperature: 25 °C

Solubility not available
Partition coefficient: n-octanol/water not available
Vapour pressure not available

Density and/or relative density 1,00-1,04 g/cm3 Method:ISO 2811 Temperature: 25 °C

Relative vapour density not available Particle characteristics not applicable

#### 9.2. Other information

Dynamic viscosity

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 52,11 %

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-Butoxy Ethanol

Decomposes under the effect of heat.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-Butoxy Ethanol

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-Butoxy Ethanol

Avoid exposure to: sources of heat,naked flames.

### 10.5. Incompatible materials

Information not available

## 10.6. Hazardous decomposition products

2-Butoxy Ethanol

May develop: hydrogen.



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 6 / 10

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### **ACUTE TOXICITY**

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: > 2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

1,2-Benzisothiazol-3(2H)-one (BW20)

LD50 (Dermal): > 2000 mg/kg Rat LD50 (Oral): 1150 mg/kg Mouse

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

LD50 (Dermal): 1000 mg/kg Rat

STA (Dermal): 50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 550 mg/kg Rat LC50 (Inhalation vapours): 0,31 mg/l Rat

2-Butoxy Ethanol

LD50 (Oral): 1200 mg/kg Guinea pig

LC50 (Inhalation vapours): 3 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### **SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

#### RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 1,2-Benzisothiazol-3(2H)-one (BW20)

# **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### **CARCINOGENICITY**



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 7 / 10

### SECTION 11. Toxicological information .../>>

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

## **STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

1,2-Benzisothiazol-3(2H)-one (BW20)

LC50 - for Fish 0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα) EC50 - for Algae / Aquatic Plants 4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

 LC50 - for Fish
 0,58 mg/l/96h

 EC50 - for Algae / Aquatic Plants
 0,161 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 0,032 mg/l 96h

#### 12.2. Persistence and degradability

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

NOT rapidly degradable 30 %, Exposure time: 28 d, OECD Test Guideline 301B

2-Butoxy Ethanol

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

#### 12.3. Bioaccumulative potential

2-Butoxy Ethanol

Partition coefficient: n-octanol/water 0,81

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 8 / 10

## SECTION 12. Ecological information .../>>

#### 12.7. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

#### 14.2. UN proper shipping name

not applicable

#### 14.3. Transport hazard class(es)

not applicable

## 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

not applicable

### 14.6. Special precautions for user

not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)



# **KRAFT TOTAL PROOF AQUA Primer**

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 9 / 10

### SECTION 15. Regulatory information .../>>

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

<u>Healthcare controls</u> Information not available

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute toxicity, category 2 Acute Tox. 2 Acute Tox. 3 Acute toxicity, category 3 Acute toxicity, category 4 Acute Tox. 4 Skin corrosion, category 1C Skin Corr. 1C Eye Dam. 1 Serious eye damage, category 1 Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2 Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

**H310** Fatal in contact with skin.

H330 Fatal if inhaled.
H301 Toxic if swallowed.
H331 Toxic if inhaled.
H302 Harmful if swallowed.

**H314** Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

**H410** Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.
EUH210 Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level



# KRAFT TOTAL PROOF AQUA Primer

Revision nr.1 Dated 09/04/2024 First compilation Printed on 09/04/2024 Page n. 10 / 10

#### SECTION 16. Other information .../>>

- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.