

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 1 / 10 Replaced revision:3 (Dated 25/08/2020)

KRAFT WOOD STYLE AQUA GLOSS

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

1. Product identifier					
Code:		CK32141000	0		
Product name		KRAFT WOO	DD STYLE AQUA GLOSS	6	
.2. Relevant identified uses	of the substance	or mixture and us	es advised against		
Intended use		Water based	I polyurethane decorativ	ve wood varnish	
.3. Details of the supplier of	the safety data sl	heet			
Name		DRUCKFAR	BEN HELLAS SA		
Full address		MEGARIDO	S AVENUE		
District and Country		19300	ASPROPYRGOS	(ATTIKI)	
		T .1	GREECE		
		Tel. Fax	+30 210 5519500 +30 210 5519501		
e-mail address of the compe	tent nerson	Fax	+30 210 5519501		
responsible for the Safety D		psafety@dru	uckfarben.gr		
.4. Emergency telephone nu	ımber				
For urgent inquiries refer to		0030-210-77	93777		
5 1					
The product is not classified However, since the product	l as hazardous pur contains hazardou	suant to the provisi is substances in co	ncentrations such as to b	lation 1272/2008 (CLP). e declared in section no. 3, it i	requires a safety data
	l as hazardous pur contains hazardou nation, compliant to	suant to the provisions substances in co	ncentrations such as to b		requires a safety data
The product is not classified However, since the product sheet with appropriate inform	l as hazardous pur contains hazardou nation, compliant to	suant to the provisions substances in co	ncentrations such as to b		requires a safety data
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and inc	l as hazardous pur contains hazardou nation, compliant to dication:	suant to the provisi is substances in co o (EU) Regulation 2 	ncentrations such as to b 2020/878.	e declared in section no. 3, it r	requires a safety data
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and inc 2.2. Label elements	l as hazardous pur contains hazardou nation, compliant to dication:	suant to the provisi is substances in co o (EU) Regulation 2 	ncentrations such as to b 2020/878.	e declared in section no. 3, it r	requires a safety data
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and inc 2.2. Label elements Hazard labelling pursuant to	l as hazardous pur contains hazardou nation, compliant to dication:	suant to the provisi is substances in co o (EU) Regulation 2 	ncentrations such as to b 2020/878.	e declared in section no. 3, it r	requires a safety data
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words:	l as hazardous pur contains hazardou nation, compliant to dication:	suant to the provisi is substances in co o (EU) Regulation 2 	ncentrations such as to b 2020/878.	e declared in section no. 3, it r	requires a safety data
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements:	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 	suant to the provisi is substances in co o (EU) Regulation 2 ?72/2008 (CLP) and	ncentrations such as to b 2020/878. I subsequent amendment	e declared in section no. 3, it r	requires a safety data
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh	suant to the provisi is substances in co o (EU) Regulation 2 ?72/2008 (CLP) and eet available on rec	ncentrations such as to b 2020/878. I subsequent amendment quest.	e declared in section no. 3, it r	
The product is not classified However, since the product sheet with appropriate inforr Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements:	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 	suant to the provisi s substances in co o (EU) Regulation 2 972/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo	ncentrations such as to b 2020/878. I subsequent amendment 5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20)	be declared in section no. 3, it i is and supplements. hiazolin-3-one [EC no. 247-500	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains:	suant to the provisi s substances in co o (EU) Regulation 2 972/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo	ncentrations such as to b 2020/878. I subsequent amendment quest. : 5-chloro-2-methyl-4-isot iiazol-3-one [EC no. 220-2	be declared in section no. 3, it i is and supplements. hiazolin-3-one [EC no. 247-500	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains:	suant to the provisi is substances in co o (EU) Regulation 2 72/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo 1,2-Benzisothiazo	ncentrations such as to b 2020/878. I subsequent amendment 5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20)	be declared in section no. 3, it i is and supplements. hiazolin-3-one [EC no. 247-500	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains:	suant to the provisi is substances in co o (EU) Regulation 2 72/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo 1,2-Benzisothiazo	ncentrations such as to b 2020/878. I subsequent amendment 5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20)	be declared in section no. 3, it i is and supplements. hiazolin-3-one [EC no. 247-500	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains: May produce a	suant to the provisi is substances in co o (EU) Regulation 2 72/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo 1,2-Benzisothiazo an allergic reaction.	ncentrations such as to b 2020/878. I subsequent amendment 5-5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20) ol-3(2H)-one (ECHA)	e declared in section no. 3, it i ts and supplements. hiazolin-3-one [EC no. 247-500 239-6] (3:1)	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains: May produce a If medical advi	suant to the provisi is substances in co o (EU) Regulation 2 272/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo 1,2-Benzisothiazo an allergic reaction.	ncentrations such as to b 2020/878. I subsequent amendment 5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20)	e declared in section no. 3, it i ts and supplements. hiazolin-3-one [EC no. 247-500 239-6] (3:1)	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208 Precautionary statements: P101	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains: May produce a If medical advi Keep out of rea	suant to the provisi is substances in co o (EU) Regulation 2 72/2008 (CLP) and Reaction mass of 2-methyl-2H-isoth 1,2-Benzisothiazo 1,2-Benzisothiazo an allergic reaction.	ncentrations such as to b 2020/878. I subsequent amendment 5-5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20) ol-3(2H)-one (ECHA) product container or labe	e declared in section no. 3, it i ts and supplements. hiazolin-3-one [EC no. 247-500 239-6] (3:1)	
The product is not classified However, since the product sheet with appropriate inform Hazard classification and ind 2.2. Label elements Hazard labelling pursuant to Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208 Precautionary statements: P101 P102	l as hazardous pur contains hazardou nation, compliant to dication: • EC Regulation 12 Safety data sh Contains: May produce a If medical advi Keep out of rea Call a POISON	suant to the provisi is substances in co o (EU) Regulation 2 272/2008 (CLP) and 272/2008 (CLP) and 272/2008 (CLP) and 2.72/2008 (CLP) and 2.72/	ncentrations such as to b 2020/878. I subsequent amendment 5-5-chloro-2-methyl-4-isot iazol-3-one [EC no. 220-2 ol-3(2H)-one (BW20) ol-3(2H)-one (ECHA) product container or labe , if you feel unwell.	e declared in section no. 3, it i ts and supplements. hiazolin-3-one [EC no. 247-500 239-6] (3:1))-7] and



KRAFT WOOD STYLE AQUA GLOSS

ΕN

SECTION 2. Hazards identification ... / >>

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:			
Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
1,2-Benzisoth	niazol-3(2H)-one (E	CHA)	
INDEX	613-088-00-6	0 ≤ x < 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0,05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg
REACH Reg.	01-2120761540-6	0	
1,2-Benzisoth	niazol-3(2H)-one (B	W20)	
INDEX	613-088-00-6	0 ≤ x < 0,05	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0,05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg, STA Inhalation mists/powders: 0,051 mg/l
REACH Reg.	01-2120761540-6	0	
Reaction mas (3:1)	ss of: 5-chloro-2-m	ethyl-4-isothiazolin-3-o	one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]
INDEX	613-167-00-5	0 ≤ x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071
EC	611-341-5		Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%
CAS	55965-84-9		STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours: 0,501 mg/l
REACH Reg.	01-2120764691-4	8	-, g

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 3 / 10 Replaced revision:3 (Dated 25/08/2020)

SECTION 5. Firefighting measures ... / >>

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)



KRAFT WOOD STYLE AQUA GLOSS

ΕN

SECTION 8. Exposure controls/personal protection/>>

	239-6] (3:1)						
reshold Lin	nit Value						
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	0,05				SKIN	

Threshold Lim	it Value					•	
Туре	Country	TWA/8h		STEL/15	min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm		
WEL	GBR	10					Particulates

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	8,5-9,5	Concentration: 100 %
		Temperature: 25 °C
Kinematic viscosity	290 mm2/s	Method Converting Formula from Dynamic
-		Viscosity & Density
		Temperature: 25 °C
Dynamic viscosity	85-145 sec	Method:Flow Cup No 4
		Remark:ISO 2431



CECTION O Develoal

DRUCKFARBEN HELLAS SA

KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 5 / 10 Replaced revision:3 (Dated 25/08/2020) ΕN

SECTION 9. Physical and chemical prop	erties / >>		
			Temperature: 25 °C
Solubility	not available		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	1,04 (±0,02)	g/cm3	Method:ISO 2811
Polotivo vonour donaity	not available		Temperature: 25 °C
Relative vapour density Particle characteristics	not applicable		
	not applicable		
9.2. Other information			
9.2.1. Information with regard to physical haz	ard classes		
Information not available			
9.2.2. Other safety characteristics			
Total solids (250°C / 482°F)	34,00 %		Method:ISO 3251
			Temperature: 25 °C

-
There are no particular risks of reaction with other substances in normal conditions of use
10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

SECTION 10. Stability and reactivity

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

10.1. Reactivity

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 6 / 10 Replaced revision:3 (Dated 25/08/2020) ΕN

SECTION 11. Toxicological information ... / >>

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

> 1,2-Benzisothiazol-3(2H)-one (ECHA) LD50 (Dermal): LD50 (Oral):

Not classified (no significant component) Not classified (no significant component) Not classified (no significant component)

50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

> 2000 mg/kg Rat 1150 mg/kg Mouse

1,2-Benzisothiazol-3(2H)-one (BW20) LD50 (Dermal): LD50 (Oral):

> 2000 mg/kg Rat 1150 mg/kg Mouse

550 mg/kg Rat

0,31 mg/l Rat

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) LD50 (Dermal): 1000 mg/kg Rat

LD50 (Dermal): STA (Dermal):

LD50 (Oral): LC50 (Inhalation vapours):

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 1,2-Benzisothiazol-3(2H)-one (BW20)

1,2-Benzisothiazol-3(2H)-one (ECHA)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 290 mm2/s

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 7 / 10 Replaced revision:3 (Dated 25/08/2020)

(3:1)

disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-Benzisothiazol-3(2H)-one (ECHA) LC50 - for Fish EC50 - for Algae / Aquatic Plants	0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα) 4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)
1,2-Benzisothiazol-3(2H)-one (BW20)	
LC50 - for Fish	0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα)
EC50 - for Algae / Aquatic Plants	4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)
Reaction mass of: 5-chloro-2-methyl-4-isothiazo	olin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (
LC50 - for Fish	0,58 mg/l/96h
EC50 - for Algae / Aquatic Plants	0,161 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,032 mg/l 96h

12.2. Persistence and degradability

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) NOT rapidly degradable 30 %, Exposure time: 28 d, OECD Test Guideline 301B

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 8 / 10 Replaced revision:3 (Dated 25/08/2020)

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product 40 Point Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%. Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None Substances subject to the Rotterdam Convention: None Substances subject to the Stockholm Convention: None Healthcare controls Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 9 / 10 Replaced revision:3 (Dated 25/08/2020)

1

ΕN

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



KRAFT WOOD STYLE AQUA GLOSS

Revision nr.4 Dated 17/03/2023 Printed on 17/03/2023 Page n. 10 / 10 Replaced revision:3 (Dated 25/08/2020) ΕN

SECTION 16. Other information ... / >>

- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.



Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 1 / 10 Replaced revision:1 (Dated 12/07/2017)

ΕN

KRAFT WOOD STYLE AQUA MAT

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identific			
.1. Product identifier			
Code: Product name		CK321430000 KRAFT WOOD STYLE AQUA MAT	
.2. Relevant identified uses	s of the substance or	nixture and uses advised against	
Intended use		Water based polyurethane decorative wood var	nish
.3. Details of the supplier of	of the safety data she	t	
Name Full address District and Country		GREECE Tel. +30 210 5519500	(ΑΤΤΙΚΙ)
e-mail address of the compresponsible for the Safety	•	Fax +30 210 5519501 psafety@druckfarben.gr	
I.4. Emergency telephone n	umber		
For urgent inquiries refer to)	0030-210-7793777	
		nt to the provisions set forth in EC Regulation 1272/20	008 (CLP).
The product is not classifie	ostance or mixture ed as hazardous pursu t contains hazardous rmation, compliant to (nt to the provisions set forth in EC Regulation 1272/2(ubstances in concentrations such as to be declared in U) Regulation 2020/878.	
The product is not classifie However, since the produc sheet with appropriate info Hazard classification and in	ostance or mixture ed as hazardous pursu t contains hazardous rmation, compliant to (ubstances in concentrations such as to be declared in	
The product is not classifie However, since the produc sheet with appropriate info Hazard classification and in 2.2. Label elements	bstance or mixture ad as hazardous pursu t contains hazardous rmation, compliant to (ndication: -	ubstances in concentrations such as to be declared in	section no. 3, it requires a safety data
The product is not classifie However, since the produc sheet with appropriate info Hazard classification and in 2.2. Label elements	bstance or mixture ad as hazardous pursu t contains hazardous rmation, compliant to (ndication: -	ubstances in concentrations such as to be declared in U) Regulation 2020/878.	section no. 3, it requires a safety data
However, since the product sheet with appropriate info Hazard classification and in 2.2. Label elements Hazard labelling pursuant in	bstance or mixture ad as hazardous pursu t contains hazardous rmation, compliant to (ndication: -	ubstances in concentrations such as to be declared in U) Regulation 2020/878.	section no. 3, it requires a safety data
The product is not classifie However, since the product sheet with appropriate info Hazard classification and in 2.2. Label elements Hazard labelling pursuant in Hazard pictograms:	bostance or mixture ad as hazardous pursu t contains hazardous a rmation, compliant to (ndication: - to EC Regulation 1272 Safety data shee Contains: F	ubstances in concentrations such as to be declared in U) Regulation 2020/878.	n section no. 3, it requires a safety data
The product is not classifie However, since the product sheet with appropriate info Hazard classification and in 2.2. Label elements Hazard labelling pursuant in Hazard pictograms: Signal words: Hazard statements: EUH210	bostance or mixture ad as hazardous pursu t contains hazardous a rmation, compliant to (ndication: - to EC Regulation 1272 Safety data shee Contains: F	available on request. eaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 2-Benzisothiazol-3(2H)-one (ECHA) 2-Benzisothiazol-3(2H)-one (BW20)	n section no. 3, it requires a safety data



KRAFT WOOD STYLE AQUA MAT

ΕN

SECTION 2. Hazards identification ... / >>

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains.			
Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
1,2-Benzisoth	niazol-3(2H)-one (B	3W20)	
INDEX	613-088-00-6	$0 \le x < 0.05$	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0.05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg, STA Inhalation mists/powders: 0,051 mg/l
REACH Reg.	01-2120761540-6	50	
	niazol-3(2H)-one (E	CHA)	
INDEX	613-088-00-6	0 ≤ x < 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0,05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg
REACH Reg.	01-2120761540-6	50	
Reaction mas (3:1)	ss of: 5-chloro-2-n	nethyl-4-isothiazolin-3	-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]
INDEX	613-167-00-5	0 ≤ x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071
EC	611-341-5		Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%
CAS	55965-84-9		STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours: 0,501 mg/l
REACH Reg.	01-2120764691-4	18	-, ····g··

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 3 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 5. Firefighting measures ... / >>

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)



KRAFT WOOD STYLE AQUA MAT

ΕN

SECTION 8. Exposure controls/personal protection/>>

eshold Lim	it Value						
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	0,05				SKIN	

Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15r	min	Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
WEL	GBR	10				Particulates		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point >	60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	8,5-9,5	Concentration: 100 %
		Temperature: 25 °C
Kinematic viscosity	260 mm2/s	Method:Converting Formula from Dynamic
		Viscosity & Density
		Temperature: 25 °C
Dynamic viscosity	85-145 sec	Method:Flow Cup No 4
		Remark:ISO 2431



SECTION 0. Devoiced and chemical properties

DRUCKFARBEN HELLAS SA

KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 5 / 10 Replaced revision:1 (Dated 12/07/2017)

ΕN

Solubility not available Temperature: 25 °C Partition coefficient: n-octanol/water not available Method: ISO 2811 Vapour pressure not available Method: ISO 2811 Density and/or relative density 1,04±0,02 g/cm3 Method: ISO 2811 Relative vapour density not available Temperature: 25 °C Particle characteristics not available Particle characteristics 9.2.0 Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.1. Other safety characteristics 04.00 % Method 100.0051			J / * *	o non o. r nysical and chemical properties	
Partition coefficient: n-octanol/water not available Vapour pressure not available Density and/or relative density 1,04±0,02 g/cm3 Method:ISO 2811 Relative vapour density not available Temperature: 25 °C Relative characteristics not available not available Particle characteristics not available not available 9.2. Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics 9.2.2. Other safety characteristics 9.2.2. Other safety characteristics	Temperatu				
Vapour pressure Density and/or relative densitynot available 1,04±0,02g/cm3Method:ISO 2811 Temperature: 25 °CRelative vapour density Particle characteristicsnot available not applicableMethod:ISO 2811 Temperature: 25 °C9.2. Other information9.2.1. Information with regard to physical hazard classesInformation not available seesInformation with regard to physical hazard classes9.2.2. Other safety characteristics9.2.2. Other safety characteristicsInformation					
Density and/or relative density 1,04±0,02 g/cm3 Method:ISO 2811 Temperature: 25 °C Relative vapour density Particle characteristics not available not applicable Feature: 25 °C 9.2. Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics 9.2.2. Other safety characteristics Information					
Relative vapour density Particle characteristics not available not applicable 9.2. Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics	Method:ISC	a/cr			
Relative vapour density not available Particle characteristics not applicable 9.2. Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics		y/ci	1,04±0,02	Jensity and/or relative density	D
 9.2. Other information 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics 	· •		not available	Relative vapour density	R
9.2.1. Information with regard to physical hazard classesInformation not available9.2.2. Other safety characteristics			not applicable	Particle characteristics	P
9.2.2. Other safety characteristics			asses		
				nformation not available	In
				9.2.2. Other safety characteristics	9.
Total solids (250°C / 482°F) 34,00 % Method:ISO 3251 Temperature: 25 °C	Method:ISC Temperatu		34,00 %	Total solids (250°C / 482°F)	Т
	d:ISC eratur	n3 Metho Tempe Metho	g/cm3 Metho Tempe	Tempe not available not available 1,04±0,02 g/cm3 Methor not available not applicable asses 34,00 % Methor	olubility not available artition coefficient: n-octanol/water not available apour pressure not available ensity and/or relative density 1,04±0,02 g/cm3 elative vapour density not available article characteristics not available Other information not applicable 2.1. Information with regard to physical hazard classes formation not available 2.2. Other safety characteristics otal solids (250°C / 482°F) 34,00 %

SECTION 10. Stability and reactivity	
10.1. Reactivity	
There are no particular risks of reaction with other substances in normal conditions of use.	

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 6 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

SECTION 11. Toxicological information ... / >>

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

> 1,2-Benzisothiazol-3(2H)-one (ECHA) LD50 (Dermal): LD50 (Oral):

Not classified (no significant component) Not classified (no significant component) Not classified (no significant component)

50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

> 2000 mg/kg Rat 1150 mg/kg Mouse

1,2-Benzisothiazol-3(2H)-one (BW20) LD50 (Dermal): LD50 (Oral):

> 2000 mg/kg Rat 1150 mg/kg Mouse

550 mg/kg Rat

0,31 mg/l Rat

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) LD50 (Dermal): 1000 mg/kg Rat

LD50 (Dermal): STA (Dermal):

LD50 (Oral): LC50 (Inhalation vapours):

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 1,2-Benzisothiazol-3(2H)-one (ECHA)

1,2-Benzisothiazol-3(2H)-one (BW20)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 260 mm2/s

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 7 / 10 Replaced revision:1 (Dated 12/07/2017)

(3:1)

disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-Benzisothiazol-3(2H)-one (ECHA) LC50 - for Fish EC50 - for Algae / Aquatic Plants	0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα) 4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)
1,2-Benzisothiazol-3(2H)-one (BW20)	
LC50 - for Fish	0,8 mg/l/96h Oncorhynchus mykiss (Ιριδίζουσα πέστροφα)
EC50 - for Algae / Aquatic Plants	4,4 mg/l/72h Daphnia magna (Νερόψυλλος ο μέγας)
Reaction mass of: 5-chloro-2-methyl-4-isothiazol	lin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (
LC50 - for Fish	0,58 mg/l/96h
EC50 - for Algae / Aquatic Plants	0,161 mg/l/72h

0,032 mg/l 96h

12.2. Persistence and degradability

Chronic NOEC for Algae / Aquatic Plants

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)NOT rapidly degradable30 %, Exposure time: 28 d, OECD Test Guideline 301B

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 8 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product 40 Point Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%. Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None Substances subject to the Rotterdam Convention: None Substances subject to the Stockholm Convention: None Healthcare controls Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 9 / 10 Replaced revision:1 (Dated 12/07/2017)

1

ΕN

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



KRAFT WOOD STYLE AQUA MAT

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 10 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

SECTION 16. Other information ... / >>

- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 02 / 03 / 04 / 08 / 09 / 11 / 12 / 14 / 15 / 16.



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 1 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

1. Product identifier					
Code: Product name		CK3214200 KRAFT WC	000 DOD STYLE AQUA SATIN		
2. Relevant identified uses	s of the substance	e or mixture and u	ises advised against		
Intended use		Water base	ed polyurethane decorativ	ve wood varnish	
3. Details of the supplier o	of the safety data s	sheet			
Name Full address District and Country			RBEN HELLAS SA DS AVENUE ASPROPYRGOS GREECE +30 210 5519500 +30 210 5519501	(ATTIKI)	
e-mail address of the comp responsible for the Safety [psafety@d	ruckfarben.gr		
4. Emergency telephone n	umber				
For urgent inquiries refer to)	0030-210-7	793777		
1. Classification of the sub The product is not classifie	ostance or mixture d as hazardous pu t contains hazardou mation, compliant	e Irsuant to the provis us substances in c	concentrations such as to b	ation 1272/2008 (CLP). e declared in section no. 3, it requires a safety o	data
However, since the product sheet with appropriate infor Hazard classification and in	ostance or mixture d as hazardous pu t contains hazardou mation, compliant	e Irsuant to the provis us substances in c	concentrations such as to b		data
 Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and ir Label elements 	d as hazardous pu t contains hazardou mation, compliant	e Irsuant to the provis us substances in c to (EU) Regulation 	concentrations such as to b	e declared in section no. 3, it requires a safety o	data
1. Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and ir	d as hazardous pu t contains hazardou mation, compliant	e Irsuant to the provis us substances in c to (EU) Regulation 	concentrations such as to b	e declared in section no. 3, it requires a safety o	data
 Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and ir Label elements Hazard labelling pursuant t 	d as hazardous pu t contains hazardou mation, compliant	e Irsuant to the provis us substances in c to (EU) Regulation 	concentrations such as to b	e declared in section no. 3, it requires a safety o	data
 1. Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and in 2. Label elements Hazard labelling pursuant t Hazard pictograms: Signal words: Hazard statements: 	ostance or mixture d as hazardous pu t contains hazardou mation, compliant ndication: o EC Regulation 12 	e Irsuant to the provis us substances in c to (EU) Regulation 272/2008 (CLP) ar	concentrations such as to b a 2020/878.	e declared in section no. 3, it requires a safety o	data
 1. Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and in 2. Label elements Hazard labelling pursuant t Hazard pictograms: Signal words: 	d as hazardous pu t contains hazardou mation, compliant ndication: o EC Regulation 12 Safety data sh Contains:	e rrsuant to the provisus substances in o to (EU) Regulation 272/2008 (CLP) ar heet available on re Reaction mass o 2-methyl-2H-iso 1,2-Benzisothiaz 1,2-Benzisothiaz	equest. of: 5-chloro-2-methyl-4-isott thiazol-3-one [EC no. 220-2 zol-3(2H)-one (BW20) zol-3(2H)-one (ECHA)	e declared in section no. 3, it requires a safety o s and supplements. niazolin-3-one [EC no. 247-500-7] and	data
 Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and ir Label elements Hazard labelling pursuant t Hazard pictograms: Signal words: Hazard statements: EUH210 	d as hazardous pu t contains hazardou mation, compliant ndication: o EC Regulation 12 Safety data sh Contains:	e rrsuant to the provisus substances in o to (EU) Regulation 272/2008 (CLP) ar heet available on re Reaction mass o 2-methyl-2H-iso 1,2-Benzisothiaz	equest. of: 5-chloro-2-methyl-4-isott thiazol-3-one [EC no. 220-2 zol-3(2H)-one (BW20) zol-3(2H)-one (ECHA)	e declared in section no. 3, it requires a safety o s and supplements. niazolin-3-one [EC no. 247-500-7] and	data
 Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and in Label elements Hazard labelling pursuant t Hazard pictograms: Signal words: Hazard statements: EUH210 	d as hazardous pu t contains hazardous mation, compliant ndication: o EC Regulation 12 Safety data sh Contains: May produce Dispose of co national / inter	e rrsuant to the provisus substances in of to (EU) Regulation 272/2008 (CLP) ar heet available on re Reaction mass of 2-methyl-2H-iso 1,2-Benzisothiaz 1,2-Benzisothiaz an allergic reaction ontents / container for rnational regulation	equest. of: 5-chloro-2-methyl-4-isoti thiazol-3-one [EC no. 220-2 zol-3(2H)-one (BW20) zol-3(2H)-one (ECHA) n.	e declared in section no. 3, it requires a safety o s and supplements. niazolin-3-one [EC no. 247-500-7] and	data
 1. Classification of the sub The product is not classifie However, since the product sheet with appropriate infor Hazard classification and in 2. Label elements Hazard labelling pursuant t Hazard pictograms: Signal words: Hazard statements: EUH210 EUH208 	d as hazardous pu t contains hazardous mation, compliant ndication: o EC Regulation 12 Safety data sh Contains: May produce Dispose of co national / intel Keep out of re	e rrsuant to the provisus substances in of to (EU) Regulation 272/2008 (CLP) ar 272/2008 (CLP) ar Reaction mass of 2-methyl-2H-iso 1,2-Benzisothiaz 1,2-Benzisothiaz an allergic reaction ontents / container for rnational regulation each of children.	equest. of: 5-chloro-2-methyl-4-isoti thiazol-3-one [EC no. 220-2 zol-3(2H)-one (BW20) zol-3(2H)-one (ECHA) n.	e declared in section no. 3, it requires a safety of s and supplements. hiazolin-3-one [EC no. 247-500-7] and 239-6] (3:1)	data



KRAFT WOOD STYLE AQUA SATIN

ΕN

SECTION 2. Hazards identification ... / >>

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains.			
Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
1,2-Benzisoth	niazol-3(2H)-one (E	CHA)	
INDEX	613-088-00-6	0 ≤ x < 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0,05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg
REACH Reg.	01-2120761540-6	60	
	niazol-3(2H)-one (B	SW20)	
INDEX	613-088-00-6	$0 \le x < 0.05$	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	220-120-9		Skin Sens. 1 H317: ≥ 0,05%
CAS	2634-33-5		LD50 Oral: 1150 mg/kg, STA Inhalation mists/powders: 0,051 mg/l
REACH Reg.	01-2120761540-6	60	
Reaction mas (3:1)	ss of: 5-chloro-2-n	nethyl-4-isothiazolin-3	-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]
INDEX	613-167-00-5	0 ≤ x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071
EC	611-341-5		Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%
CAS	55965-84-9		STA Oral: 100 mg/kg, STA Dermal: 50,001 mg/kg, STA Inhalation vapours: 0,501 mg/l
REACH Reg.	01-2120764691-4	18	-,

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 3 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 5. Firefighting measures ... / >>

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und
		Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung
		gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)



KRAFT WOOD STYLE AQUA SATIN

ΕN

SECTION 8. Exposure controls/personal protection/>>

-220 hreshold Lin	239-6] (3:1) nit Value						
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	0,05				SKIN	

						(
Threshold Lin	nit Value					
Туре	Country	TWA/8h		STEL/15r	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
WEL	GBR	10				Particulates

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point >	60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
рН	8,5-9,5	Concentration: 100 %
		Temperature: 25 °C
Kinematic viscosity	320 mm2/s	Method:Converting Formula from Dynamic
		Viscosity & Density
		Temperature: 25 °C
Dynamic viscosity	85-145 sec	Method:Flow Cup No 4
		Remark:ISO 2431



SECTION 9. Devoiced and elemical properties

DRUCKFARBEN HELLAS SA

KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 5 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

SECTION 9. Physical and chemical propen	les/ >>		
			Temperature: 25 °C
Solubility	not available		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		M-4
Density and/or relative density	1,04±0,02	g/cm3	Method:ISO 2811 Temperature: 25 °C
Relative vapour density	not available		Temperature. 23 C
Particle characteristics	not applicable		
9.2. Other information			
9.2.1. Information with regard to physical hazard	classes		
Information not available			
9.2.2. Other safety characteristics			
J.Z.Z. Other safety characteristics			
Total solids (250°C / 482°F)	34,00 %		Method:ISO 3251
			Temperature: 25 °C

10.1. Reactivity	
There are no particular risks of reaction with other substances in normal conditions of use.	

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

SECTION 10. Stability and reactivity

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 6 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

S	ECTION 11	. Toxicological	information	/ >>

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

> 1,2-Benzisothiazol-3(2H)-one (ECHA) LD50 (Dermal): LD50 (Oral):

Not classified (no significant component) Not classified (no significant component) Not classified (no significant component)

50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

> 2000 mg/kg Rat 1150 mg/kg Mouse

1,2-Benzisothiazol-3(2H)-one (BW20) LD50 (Dermal): LD50 (Oral):

> 2000 mg/kg Rat 1150 mg/kg Mouse

550 mg/kg Rat

0,31 mg/l Rat

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) LD50 (Dermal): 1000 mg/kg Rat

LD50 (Dermal): STA (Dermal):

LD50 (Oral): LC50 (Inhalation vapours):

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 1,2-Benzisothiazol-3(2H)-one (BW20)

1,2-Benzisothiazol-3(2H)-one (ECHA)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 320 mm2/s

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 7 / 10 Replaced revision:1 (Dated 12/07/2017)

(3:1)

disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

us mykiss (Ιριδίζουσα πέστρα ιgna (Νερόψυλλος ο μέγας)	γα)
ius mykiss (Ιριδίζουσα πέστρα	ρα)
igna (Νερόψυλλος ο μέγας)	
2-methyl-2H-isothiazol-3-one	C no. 220-239-6]
?-methyl-2H-isothiazol-3-one	:C no. 220-239

0,032 mg/l 96h

12.2. Persistence and degradability

Chronic NOEC for Algae / Aquatic Plants

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)NOT rapidly degradable30 %, Exposure time: 28 d, OECD Test Guideline 301B

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 8 / 10 Replaced revision:1 (Dated 12/07/2017)

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product 40 Point Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%. Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None Substances subject to the Rotterdam Convention: None Substances subject to the Stockholm Convention: None Healthcare controls Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 9 / 10 Replaced revision:1 (Dated 12/07/2017)

1

ΕN

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament



KRAFT WOOD STYLE AQUA SATIN

Revision nr.2 Dated 17/03/2023 Printed on 17/03/2023 Page n. 10 / 10 Replaced revision:1 (Dated 12/07/2017) ΕN

SECTION 16. Other information ... / >>

- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 02 / 03 / 04 / 08 / 09 / 11 / 12 / 14 / 15 / 16.