



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 1 / 12

(ATTIKI)

Replaced revision:7 (Dated 17/07/2017)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: CK202480000

Product name KRAFT YACHT CARE

UFI: 9220-D0TX-800A-QQ86

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Yacht Varnish

1.3. Details of the supplier of the safety data sheet

Name DRUCKFARBEN HELLAS SA
Full address MEGARIDOS AVENUE

District and Country 19300 ASPROPYRGOS

GREECE

Tel. +30 210 5519500 Fax +30 210 5519501

e-mail address of the competent person

responsible for the Safety Data Sheet psafety@druckfarben.gr

1.4. Emergency telephone number

For urgent inquiries refer to 0030-210-7793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3 H226 Flammable liquid and vapour.

Aspiration hazard, category 1 H304 May be fatal if swallowed and enters airways.

Specific target organ toxicity - single exposure, H336 May cause drowsiness or dizziness.

category 3

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:







Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 2 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 2. Hazards identification .../>>

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P331 Do NOT induce vomiting.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310 IF SWALLOWED: immediately call a POISON CENTER or a doctor

P370+P378 In case of fire: use alcohol resistant foam to extinguish.

P501 Dispose of contents / container to an approved waste disposal plant or recycled in accordance with local /

national / international regulations.

P102 Keep out of reach of children.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX 649-327-00-6 20 ≤ x < 30 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification

note according to Annex VI to the CLP Regulation: P

EC 919-857-5 CAS 64742-48-9 REACH Reg. 01-21119463258-33

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

INDEX 649-327-00-6 9 ≤ x < 10 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification

note according to Annex VI to the CLP Regulation: P

EC 919-857-5 CAS 64742-48-9

REACH Reg. 01-2119463258-33-xxxx

A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates

INDEX 607-281-00-4 1 ≤ x < 2,5 Aquatic Chronic 2 H411

EC 407-000-3 CAS 127519-17-9 REACH Reg. 01-0000015648-61

2,6-di-tert-butyl-p-cresol

INDEX $0 \le x < 0.25$ Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 204-881-4 CAS 128-37-0 REACH Reg. 01-2119565113-46 2-(2-BUTOXYETHOXY)ETHANOL

INDEX 603-096-00-8 $0 \le x < 0.5$ Eye Irrit. 2 H319

EC 203-961-6 CAS 112-34-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.



DRUCKFARBEN HELLAS SA KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 3 / 12 Replaced revision:7 (Dated 17/07/2017)

SECTION 4. First aid measures .../>>

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 4 / 12 Replaced revision:7 (Dated 17/07/2017)

SECTION 7. Handling and storage .../>>

people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,

СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17

Януари 2020г.)

DEU Deutschland Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und

Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung

gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56

GRC Ελλάδα Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των

οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με

την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

ROU România Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru

modificarea și completarea hotărârii guvernului nr. 1.093/2006

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH ACGIH 2022

				2,6-di-tert	-butyl-p-creso	ol			
Threshold Limit Valu	ie								
Туре	Country	TWA/8h		STEL/15min		Remarks / O	oservations		
		mg/m3	ppm	mg/m3	ppm				
OEL E	U	10							
Predicted no-effect of	concentrati	ion - PNEC	;						
Normal value in fre	sh water						0,0002	mg/l	
Normal value in ma						0,00002	mg/l		
Health - Derived no-	effect level	- DNEL / I	OMEL						
	Effect	Effects on consumers				Effects on workers			
Route of exposure	Acute	Acu	te	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	syst	temic	local	systemic		systemic	local	systemic
Inhalation		•			-		-	VND	3,5
									mg/kg
Skin								VND	0,5
									mg/kg
									bw/d



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 5 / 12 Replaced revision:7 (Dated 17/07/2017)

SECTION 8. Exposure controls/personal protection .../>>

-		•		•							
		Hy	ydroca	rbons, C9	-C11, n-alkanes	, isoalkanes,	cyclics, <2% arc	matics			
Threshold Limit Value											
Туре	Count	ry TV	TWA/8h		STEL/15	STEL/15min		Remarks / Observations			
		mg	g/m3	ppm	mg/m3	ppm					
TLV	GRC	12	00								
Health - Derived no-effect level - DNEL / DMEL											
Effects on consumers					E		Effects on worl	Effects on workers			
Route of expo	sure	Acute	Acı	ute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic	
		local	sys	temic	local	systemic		systemic	local	systemic	
Oral			-		VND	300		-		·	
						mg/kg/d					
Inhalation					VND	900	VND	1500			
						mg/m3		mg/m3			
Skin					VND	300			VND	300	
						mg/kg/d				mg/kg/d	

2-(2-BUTOXYETHOXY)ETHANOL									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15m	nin	Remarks / Observation	าร		
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	67,5	10	101,2	15				
AGW	DEU	67	10	100,5 (C)	15 (C)	Hinwe	is		
MAK	DEU	67	10	100,5	15	Hinwe	is		
TLV	GRC	67,5	10	101,2	15				
VLEP	ITA	67,5	10	101,2	15				
TLV	ROU	67,5	10	101,2	15				
WEL	GBR	67,5	10	101,2	15				
OEL	EU	67,5	10	101,2	15				
TLV-ACGIH		66	10			INHAL			

		Hydrocar	bons, C9-C	11, n-alkanes	, isoalkanes,	cyclics, <2% aro	matics		
Threshold Limit Value	•	_							
Type C	ountry	TWA/8h		STEL/15min		Remarks / Ob	servations		
		mg/m3	ppm	mg/m3	ppm				
TLV G	RC	1200							
Health - Derived no-effect level - DNEL / DMEL									
Effects on consumers			mers			Effects on workers			
Route of exposure	Acute	Acu	ite	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	syst	temic	local	systemic		systemic	local	systemic
Oral				VND	300				
					mg/kg/d				
Inhalation				VND	900	VND	1500		
					mg/m3		mg/m3		
Skin				VND	300		-	VND	300
					mg/kg/d				mg/kg/d

Legend

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 6 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 8. Exposure controls/personal protection/>>

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
рН	not available	
Kinematic viscosity	635-1275 mm2/s	Method:Converting Formula from Dynamic
		Viscosity & Density
		Temperature: 25 °C
Dynamic viscosity	70-90 KU	Method:ASTM D 562-05
		Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,90-0,94 g/cm3	Method:ISO 2811
		Temperature: 25 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 61,00 % Method:ISO 3251 Temperature: 25 °C

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 7 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 10. Stability and reactivity .../>>

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances.May form peroxides with: oxygen.Develops hydrogen on contact with: aluminium.May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat.

Keep away from: oxidising agents.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Avoid exposure to: heat. Keep away from: oxidising agents.

10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics LD50 (Dermal): > 5000 mg/kg Rabbit LD50 (Oral): > 5000 mg/kg Rat LC50 (Inhalation vapours): > 20 mg/l/4h Rat



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 8 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 11. Toxicological information .../>>

2-(2-BUTOXYETHOXY)ETHANOL

 LD50 (Dermal):
 2700 mg/kg Rabbit

 LD50 (Oral):
 3384 mg/kg Rat

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

 $Hydrocarbons,\,C9\text{-}C11,\,n\text{-}alkanes,\,isoalkanes,\,cyclics,\,<\!2\%\,\,aromatics$

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms

 EC50 - for Crustacea
 > 100 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

 Chronic NOEC for Fish
 > 0,1 mg/l

 Chronic NOEC for Crustacea
 > 0,1 mg/l

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LC50 - for Fish > 100 mg/l/96h Fish / Aquatic Invertebrates / Algae / Microorganisms

 EC50 - for Crustacea
 > 100 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

 Chronic NOEC for Fish
 > 0,1 mg/l



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 9 / 12 Replaced revision:7 (Dated 17/07/2017)

SECTION 12. Ecological information .../>>

Chronic NOEC for Crustacea

> 0,1 mg/l

12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol

Degradability: information not available

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

2-(2-BUTOXYETHOXY)ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

12.3. Bioaccumulative potential

2,6-di-tert-butyl-p-cresol

Partition coefficient: n-octanol/water 5,1 Log Kow BCF < 1800

2-(2-BUTOXYETHOXY)ETHANOL

Partition coefficient: n-octanol/water

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT OF PAINT RELATED MATERIAL IMDG: PAINT OF PAINT RELATED MATERIAL IATA: PAINT OF PAINT RELATED MATERIAL



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 10 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30 Limited Quantities: 5 L Tunnel restriction code: (D/E)

Special provision: 163, 367, 650

IMDG: EMS: F-E, <u>S-E</u> Limited Quantities: 5 L

IATA: Cargo: Maximum quantity: 220 L Packaging instructions: 366
Passengers: Maximum quantity: 60 L Packaging instructions: 355

Special provision: A3, A72, A192

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

ΕN



DRUCKFARBEN HELLAS SA

KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 11 / 12

Replaced revision:7 (Dated 17/07/2017)

SECTION 15. Regulatory information .../>>

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Asp. Tox. 1 Aspiration hazard, category 1
Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament



KRAFT YACHT CARE

Revision nr.8 Dated 21/04/2023 Printed on 21/04/2023 Page n. 12 / 12 Replaced revision:7 (Dated 17/07/2017)

SECTION 16. Other information .../>>

- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.