

Spachtel™ Light



THINNING
0%



APPLICATION
Putty knife



DRYING
30 mins

Lightweight putty
for easy filling

» Easy Application

Ready-to-use white lightweight putty with acrylic copolymer resins and glass beads for indoor and outdoor use. It is suitable for easy filling and patching of cracks and holes up to 5cm on surfaces such as plaster, brick, plasterboard, wood, concrete, etc. It is very easy to apply, dries fast and does not shrink. Can be painted quickly without cracks or detachments.

A/g (WB) Primers.

- VOC Limit Value: 30g/L.
- Maximum content of VOC of the ready-to-use product: 29 g/L

» Non-shrinking

» Dries quickly

TECHNICAL DATA

Density ISO 2811 @ 25°C	0.34 g/mL(±0.04)
Surface Drying	~30 mins
Overpainting time	At least 1 h

Spachtel™ Light

Lightweight putty
for easy filling

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease residues, blistered paint etc.

APPLICATION INSTRUCTIONS

- » Apply with a putty knife on the desired spot. Then put some pressure and smoothen to properly fill the hole.
- » Minimum time for sanding: After 30 minutes (if necessary).

AFTER USE INSTRUCTIONS

- » Clean the tools thoroughly with water and detergent.
- » Close the bucket well to preserve it in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.
- » Over paint: After 1 hour.
- » The topcoat is applied after priming the KRAFT SPACHTEL LIGHT with a layer of KRAFT ECO DUR AQUA or KRAFT HAFT.
- » On wood surfaces, priming with KRAFT VELATOURA or KRAFT VELATOURA AQUA is necessary prior to applying the topcoat.
- » Avoid applying at temperatures below 5°C or over 35°C and at a relative humidity over 65%.

PACKAGING

Available in white in 0,6L canisters.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product before and after opening at temperatures between 5°C to 35°C away from direct sunlight and rain, for maximum 24 months from the date of production.

Keep containers tightly closed when not in use.

06/23 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr