

# Sport Coat



**THINNING**  
0%



**COVERAGE**  
4 - 6 m<sup>2</sup>/L



**APPLICATION**  
roller, brush,  
squeegee or  
airless spray gun



**DRYING**  
1 - 2 hours

100% Acrylic paint  
for courts

» **Ideal for tennis, basketball, volleyball courts, etc.**

» **High resistance to friction & external conditions**

» **Great resistance to UV radiation**

Colored, 100% water-based acrylic paint enriched with rock crystals, featuring high resistance to friction and to external conditions. It is specifically developed for use on tennis courts (category ITF:3, medium), basketball, volleyball courts, etc. It creates a self-leveling, anti-skid surface, of great elasticity and high durability over time. It offers great waterproofing and high resistance to UV radiation and to weathering, keeping the surface clean and the shades consistent over time. It can be applied on previously painted or new surfaces of concrete (cement or asphalt).

#### A/i (WB) One-pack performance coatings.

- VOC Limit Value: 140 g/L.
- Maximum VOC concentration of the ready to use product: 139 g/L.

#### TECHNICAL DATA

Density ISO 2811 @ 25°C	1.05g/mL (±0.05)
Viscosity ASTM D 562-05 @ 25°C	120KU (±15)
pH	8.5 - 9.5
Coverage per coat	4 - 6 m <sup>2</sup> /L*

\* Depending on the application method and the surface absorption.

# Sport Coat

100% Acrylic paint  
for courts

## SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean, and free of dust, grease, salts, rust, residues, blistered paints, etc.

- » Flatten out the surface and remove all moss, fungi and algae by mechanical abrasion, wash with soapy water and allow the substrate to dry.
- » Use KRAFT PUTTY for filling gaps, cracks and damaged parts.
- » On fresh cement, leave to dry at least for 3 weeks before applying and prime first with KRAFT ECO DUR AQUA or KRAFT DUR.

## APPLICATION INSTRUCTIONS

- » You can apply with a brush, a roller, a squeegee (elastic spatula) or an airless spray gun.
- » Thinning: Not recommended.
- » **Dry to touch:** 1-2 hours at 25°C and 50% relative humidity (drying time is longer in humid/cold conditions).
- » **Recoating time:** Minimum 6 hours after application of the first coat in favorable drying conditions. Apply 2-3 coats of KRAFT SPORT COAT.
- » **Complete hardening time:** Minimum 7 days to dry in favorable drying conditions for complete hardening and walkability.
- » Stir well before and regularly during application.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 65% or higher.
- » Avoid application under direct sunlight.
- » Do not apply in case of expected rain.

## AFTER USE INSTRUCTIONS

- » Clean the tools and product residues immediately with warm water and soap or detergent.

## PACKAGING

Available in 10L plastic containers. Available in brick red, green, blue and other shades upon request.

## HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

**+30 210 7793 777**

## STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

08/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

**DISCLAIMER:** The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website [www.kraftpaints.com](http://www.kraftpaints.com), as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarbengroup.com](http://www.druckfarbengroup.com) | [www.kraftpaints.com](http://www.kraftpaints.com)



Toll-free number

**800 111 7700** Monday - Friday, 8.00 am - 04.00 pm  
e-mail: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)