

Stone Care Aqua™



THINNING
0%



COVERAGE
8 - 10 m²/L



APPLICATION
brush, roller or
airless spray gun



DRYING
1 hour

Acrylic water-based
stone varnish

» High impregnation properties

High quality water-based acrylic varnish for stones and porous mineral substrates for exterior and interior use. It protects and decorates porous substrates such as stones, bricks, cementitious substrates, etc. Its special formula penetrates deeply into the substrate and forms a waterproof film, thus preventing mold growth on its surface and protecting from air pollutants, corrosion and wear. In addition, the UV filters in its formula provide resistance to weather conditions and to intense sunlight. Thanks to its hard end elastic surface it is suitable for stone floors.

A/h (WB) Binding Primers.

- VOC Limit Value: 30 g/L.
- Maximum VOC concentration of the ready to use product: 29 g/L.

» Protects stone from corrosion

» Refreshes the stone appearance

TECHNICAL DATA

Binder Type	Acrylic
Density ISO 2811 @ 25°C	1.02 g/mL (±0.02)
Solids Content w/w ISO 3251	21.5% (±2)
Viscosity Flow Cup 4 ISO 2431 @ 25°C	18 sec (±3)
pH	8.8-9.8
Coverage per coat	8-10 m ² /L*

* Depending on the application method and the surface absorption.

Stone Care Aqua™

Acrylic water-based
stone varnish

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, grease, residues, blistered paint, previous paints or varnishes, etc.

- » **On new stone surfaces:** Before applying the varnish, wash the surface with water and dry it well.
- » **On painted surfaces with mold/algae:** Remove all residues, sand and clean the surface. Then apply KRAFT MOLD BLOCKER and after 24 hours apply 1-2 coats of KRAFT STONE CARE AQUA.
- » **On stone floors:** Before applying the varnish, remove all residues, wash the surface with water and let it dry well.

APPLICATION INSTRUCTIONS

- » The product is ready to use.
- » Check the surface moisture prior to application. The surface must be completely dry.
- » You can apply with a brush, a roller or an airless spray gun.
- » Stir well before application.
- » Apply 1-2 coats of KRAFT STONE CARE AQUA on vertical surfaces and 2 coats on floors.
- » Minimum recoating time: ~5 hours.
- » Dry to touch: ~1 hour at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » Do not apply at temperatures below 10°C or above 35°C and at a relative humidity 65% or higher.

AFTER USE INSTRUCTIONS

- » Close the canister well to preserve it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Clean the tools immediately with warm water and soap.

PACKAGING

Available in transparent, in 0.75L and 2.5L containers.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION INSTRUCTIONS

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for maximum 24 months from the date of production. Keep containers tightly closed when not in use.

08/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarbengroup.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr