

Teak & Deck Oil



THINNING
0%



COVERAGE
12-16 m²/L



APPLICATION
brush,
cloth



DRY TO TOUCH
2 - 3 hours

Special impregnation oil
for hard woods

» PU modified

Special polyurethane modified blend of natural oils, enriched with wax and UV filters. Ideal for preserving and refreshing hard and exotic woods such as teak, iroko, bangkirai, oak, mahogany (such as niangon and meranti) and bare woods. Ideal for outdoor furniture, pergolas, fences and wooden boat decks. It fills the wood pores in depth, prevents the penetration of water and it features great resistance to severe weather conditions. When used on a regular basis, it nourishes the wood making it more durable against climate changes and fading.

A/h (SB) Binding Primers

- VOC Limit Value: 750g/L
- Maximum VOC concentration of the ready to use product: 590g/L

» With wax. It waterproofs the surface

» High technology UV filters

TECHNICAL DATA

| | |
|--|--------------------------|
| Binder Type | PU / Oil mixture |
| Density ISO 2811 @ 25°C | 0,84 g/mL(±0.02) |
| Solids Content w/w ISO 3251-03 | 43% (±3) |
| Viscosity Flow Cup No4 @ 25°C ISO 2431 | 13sec (±2) |
| Coverage per coat | 12-16 m ² /L* |

* Depending on the application method and the type of the wood

Teak & Deck Oil

Special impregnation oil
for hard wood

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry and free of dust, residues, resins or grease. Remove all residues of old varnishes. In case the surface has been previously painted with wood-stain or impregnation varnish, first it must be cleaned with KRAFT REMOVER paint stripper. The surfaces should be sanded with a proper sandpaper (preferably No120) to a dull finish. Wet sanding is advisable wherever possible to avoid dust generation or exposure to it. In case extra protection is needed against wormwood or fungi, first apply one coat of KRAFT WOOD CARE preservative.

APPLICATION INSTRUCTIONS

- » Make sure the wood is dry and there is no rain forecast for the next 48 hours after completion of the final coating.
- » Do not apply in the sun.
- » The product is ready to use.
- » Stir well before application. Apply 1 coat of **KRAFT TEAK & DECK OIL**.
- » After 24 hours apply the second coat.
- » After 5 minutes remove the excess product with a dry cloth.
- » On surfaces exposed to adverse weather conditions apply 2 coats of KRAFT TEAK & DECK OIL.
- » If the wood is highly absorbent or very stressed, an additional coat might be required up to full saturation. Again, remove excess product after 5 minutes with a cloth along the side of the wood.
- » You can apply the material on the surface using a brush or a cloth, along the side of the wood.
- » Dry to touch: 2-3 hours at 25°C and 60% relative humidity. Drying time is subject to weather conditions.
- » The final color of the wood depends on its initial color and its age.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 65% or higher.

AFTER USE INSTRUCTIONS

- » Clean the tools immediately with KRAFT BRUSH SOLVENT.
- » Close the canister well and turn it upside down so as the product to cover the interior walls for an airtight sealing, to preserve it in good condition for future use.
- » For maintenance and refreshment repeat application once every year.

PACKAGING

Available in transparent, in 0.75L and 2.5L containers.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr