

Total Proof™ FLEECE 110

ETA EAD 030350-00-0402
25 YEARS
 WORKING LIFE



Polyester non-woven geotextile

- » **Compatible with waterproofing systems of liquid membranes Total Proof**
- » **Excellent tear strength**
- » **High elasticity and resistance to pedestrian usage**
- » **UV resistant**

DESCRIPTION

Total Proof FLEECE 110 is a 110 g/m² polyester non-woven geotextile for reinforcing waterproofing liquid membranes.

FIELD OF APPLICATION

Total Proof FLEECE 110 is compatible and is used to reinforce TOTAL PROOF waterproofing liquid membranes of KRAFT Paints in case of local or multiple cracklings. It is also part of the Total Proof PU FIBER 25 SYSTEM to achieve 25 years working life.

ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

Weight EN12127	110 g/m ²
Tensile strength EN 29073-3	375 N/5cm MD
	350 N/5cm CD
Elongation at brake EN 29073-3	50% MD
	65% CD

Total Proof™ FLEECE 110

Transparent acrylic impregnation primer
for horizontal porous surfaces

DIRECTIONS FOR USE

- » APPLICATION: During application of two layers of liquid membrane "wet on wet" in the interval, lay the 110 g/m² polyester reinforcement Total Proof FLEECE 110 carefully to avoid air entrapment.
- » For the local reinforcement of the waterproofing membrane and for applications in cracks, joints, corners, and joints of horizontal-vertical surfaces, use the 60g/m² reinforcement tape Total Proof TAPE 60.

PACKAGING - SHADE


It is white and available in roller of total length 100m and width 1m.

CONSUMPTION

The consumption per roller is 100m².

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain. Keep it tightly closed when not in use.

 1020
DRUCKFARBEN HELLAS SA Megaridos Ave., Kallistiri area, GR-19300 Aspropyrgos, greece
24
DoP: ONo 04.20 Total Proof PU Fiber 25 System Liquid applied roof waterproofing kits, W3
EAD 030350-00-0402 ETA 24/0356

08/2024 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarbengroup.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
 e-mail: paints.orders@druckfarben.gr