

Total Proof™ TAPE 60



Polyester non-woven tape

» **Suitable for local cracklings, corners and joints**

» **Excellent tear strength**

» **Easy to apply**

» **UV stable**

Total Proof TAPE 60 is a 60 g/m² polyester non-woven tape for reinforcing waterproofing liquid membranes.

FIELD OF APPLICATION

Total Proof TAPE 60 is compatible and is used to reinforce Total Proof waterproofing liquid membranes of KRAFT Paints in case of local cracklings, corners, joints of horizontal & vertical surfaces etc. If applied on the entire surface, a 5-10 cm overlapping between the fabric strips must be calculated.

TECHNICAL DATA

Weight EN12127

60 g/m² (±10%)

Total Proof™ TAPE 60

Polyester non-woven tape

DIRECTIONS FOR USE

1.APPLICATION: During application of two layers of liquid membrane "wet on wet" in the interval, lay the 60 g/m² polyester reinforcement tape Total Proof TAPE 60 carefully to avoid air entrapment.

PACKAGING - SHADE

It is white and available in roller of total length 50m and width 10cm.

CONSUMPTION

The consumption per roller is 5m².

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain. Keep it tightly closed when not in use.

08/2024 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.com | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr