

Eco Velatoura Aqua



THINNING
8-15%



COVERAGE
8-10 m²/L



APPLICATION
brush, roller or
airless spray gun



DRY TO TOUCH
1-2 hours

Ecological- enamel
undercoat

» Very easy sanding

The ideal ecological substrate for the preparation of wooden surfaces before the application of enamel paint. It is certified by the Hellenic Council for EU Ecolabel and fulfills the criteria of the EU Ecolabel. It is user-friendly and has a very mild odor. It provides exceptional coverage while it effectively fills the pores of the surface blocking the wood tannins and ensuring excellent adhesion on wood, walls, glass and hard PVC. It is very easy to sand and thus prepare the surface properly before the enamel paint application. It features excellent leveling, covering minor imperfections of the substrate, workability and great coverage leaving an even surface.

A/h (WB) Binding Primers

- VOC Limit Value: 30g/L
- Maximum VOC concentration of the ready to use product: 14.9g/L

» Exceptional coverage

» Perfect adhesion

TECHNICAL DATA

Binder Type	Acrylic
Density ISO 2811 @ 25°C	1,437g/mL (±0,03)
Solids Content w/w ISO 3251	59,5% (±3)
Viscosity ASTM D 562-05 @ 25°C	90KU (±15)
Application Viscosity ASTM D 562-05 @ 25°C	70KU (±15)
Gloss Level @ 60° ISO 2813	<4,0 GU
Gloss Level @ 85° ISO 2813	<7,0 GU
pH	8.5-9.5
Whiteness Index ASTM E 313-98	88.0 (±2)
Yellowness Index ASTM E 313-98	0.0 (±1)
Cross-Cut (Adhesion) ISO 2409	Class: 0 No defoliation
Pull-Off Test (Adhesion) ISO 4624	2.5MPa
Coverage per coat	8-10 m ² /L*
Recommended dry film thickness (2 coats)	40µm (±5)

* Ανάλογα τη μέθοδο εφαρμογής και την απορροφητικότητα της επιφάνειας

Eco Velatura Aqua

Ecological- enamel
undercoat

SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, solid, and free of dust, residues, blistered paint, etc. Avoid dust generation. Wet sanding is recommended for the surface preparation.

- » **On new surfaces:** Before applying the topcoat, apply 1-2 coats of **KRAFT VELATOURA AQUA**.
- » **On surfaces that need repair:** Use KRAFT SPACHTEL. When it dries prepare the surface by wet sanding.
- » **On surfaces with stains/tannins:** Apply 2 coats of KRAFT VELATOURA AQUA.

APPLICATION INSTRUCTIONS

- » Minimize the paint waste by calculating the quantity you are going to need beforehand.
- » Thin 8-15% v/v with tap water before application and stir well.
- » You can apply it with a brush, a roller or an airless spray gun.
- » The product is white and should be tinted only with the KRAFT INSPIRED COLOR tinting system in thousands of light shades.
- » Apply 1-2 coats of KRAFT VELATOURA AQUA for an ideal result. Then apply 2 coats of the chosen KRAFT topcoat.
- » To be applied in an open or well-ventilated space only.
- » Minimum recoating time: 16 hours.
- » Dry to touch: 1-2 hours at 25°C and 50% relative humidity. Drying time is subject to weather conditions.
- » If a dark shade of low coverage or a shade with the relevant labeling from the KRAFT INSPIRED COLLECTION color fan deck is chosen, it is recommended to pre-apply KRAFT VELATOURA AQUA tinted in a lighter shade of the same color family.
- » Do not apply at temperatures below 5°C or above 35°C and at a relative humidity 65% or higher.

AFTER USE INSTRUCTIONS

- » Recover unused paint for reuse.
- » Close the canister well to keep it in good condition for future use. Store before or after opening in a cool place, avoiding sunlight or frost conditions.
- » Reuse of paint can effectively minimize the environmental impact of a product's life cycle.
- » Clean the tools immediately with warm water and soap.

PACKAGING

Available in white, in 0.75L and 2.5L containers.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read the label carefully before use. For more information, please refer to the Safety Data Sheet.

Poison Centre Tel:

+30 210 7793 777

STORAGE

Store the product at temperatures between 5°C and 35°C away from direct sunlight and rain, for a maximum of 24 months from the date of production. Keep containers tightly closed when not in use.

09/2023 THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations, and instructions are based on our scientific and technical knowledge, laboratory studies and long experience. However, the above information should be considered indicative and should be reviewed in any case in relation to each specific condition and practical application. Consequently, the suitability of the product for each specific application must be evaluated after referring to the updated Technical Data Sheet and to our website www.kraftpaints.com, as well as after contacting our technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable consequences after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300, ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.com



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm
e-mail: paints.orders@druckfarben.gr